285 STERILE PROCESSING SERVICE

A. FA1: DECONTAMINATION AREA

1. ANTEROOM, SOILED TRANSITION / DROP-OFF (CSCR1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A5075	Dispenser, Soap, Disposable	1	V V	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	10 28 00
A5077	Dispenser, Hand Sanitizer, Hands-Free	1	V V	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	C C	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	V V	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
F0510	Cart, Linen, Soiled	1	V V	Soiled linen collection cart, approximately 70" H x 68" W x 28" D with four (4) casters. Used to transport clean or soiled laundry.	N/A
F2010	Basket, Wastepaper, Step-On	1	V V	"Step-on" wastepaper basket with inner liner and foot petal activated flip top.	N/A
F2020	Can, Trash, 44 Gallon	1	V V	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).	N/A
M3072	Frame, Infectious Waste Bag w/Lid	1	V V	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.	N/A
P2000	Eyewash, Wall Mounted, Hands-Free	1	C C	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.	22 11 00
P2450	Valve, Mixing, Thermostatic	1	C C	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	C C	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
2. ALCOVE, PPE (CSPE1)					
JSN	**NAME**	**QTY**	**ACQ / INS**	**DESCRIPTION**	**SPEC**
A5145	Hook, Garment, Double, SS, Surface Mounted	4	C C	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5160	Shelf, 8"Depth, SS, Surface Mounted	1	C C	A surface mounted, satin finish, stainless steel shelf with a minimum depth of 8". Mounting brackets are welded to shelf. Shelf is available in various widths. For general purpose use in scrub areas/rooms or other areas of the facility where a SS shelf is required. Pricing based upon a 36" width.	12 32 00
F2020	Can, Trash, 44 Gallon	1	V V	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).	N/A
M2035	Rack, Storage, Mobile, Wire, CRS	1	V V	Mobile, wire, storage rack. Unit has open, fully adjustable, corrosion resistant wire surfaces and is mounted on stem casters. Used for linen or other general purpose storage and transport. Racks are provided in various sizes and configurations. The price provided is for a unit approximately 68"H x 18"D x 48"W with four shelves, bumpers, two swivel and two braking casters.	N/A
3. DECONTAMINATION WORK AREA (CSDE1)					
JSN	**NAME**	**QTY**	**ACQ / INS**	**DESCRIPTION**	**SPEC**
A1010	Telecommunication Outlet	1	C C	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	C C	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1195	Counter, Cleanup, With 2 or 3 Sinks	2	C C	Two or three sink cleanup counter. Unit is constructed of type 304 corrosion resistant stainless steel. It consists of three sinks 14"W X 16"H X 10"D, hot and cold water faucet, and pre-rinse spray hose. Equipped with channel reinforced drainboards, and backsplash, and supported by tubular stainless steel legs. Unit is designed for use in control sterile supply decontamination areas.	11 71 11
A5075	Dispenser, Soap, Disposable	1	V V	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	10 28 00
A5077	Dispenser, Hand, Sanitizer, Hands Free	1	V V	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5080	Dispenser, Paper Towel, Surface, Mounted	1	C C	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposable Unit, Sharps w/Glove Dispenser	1	V V	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	N/A
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	1	V V	A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA compliant unit with a load capacity of up to 130 lbs.	N/A
_0064	Cabinet, Wall Mounted, SS, Sloping Top	1	N/A	Wall hung stainless steel cabinet with adjustable shelves, solid hinged clear glass doors, and sloping top. For storing purpose in areas where stainless steel cabinets are used.	12 31 00

PG-18-5: 285 STERILE PROCESSING SERVICE

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
K6300	Sink, Cook's, 1 Compartment	1	C C	Single compartment stainless steel sink, floorstanding for soiled rooms such us utility or decontamination. 14" Bowl depth, 3/4" radius at all intersecting planes, Stainless steel gussets machine welded 360 degree to a stainless steel triangular plate, Polished to a # 4 blended finish. 10" backsplash, Stainless steel feet, Legs shall have stainless steel crossbracing with aluminum castings at all intersections.	22 40 00
CT050	Countertop, Staniless Steel	AR	C C	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.	12 36 00
F2020	Can, Trash, 44 Gallon	1	V V	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).	N/A
F2700	Reader, Bar Code, Hand Held, With Interface	2	V V	Hand held laser bar code reader with computer interface. Used for automated inventory, using bar code stickers / labels. Convenience outlet required at point of use.	N/A
F3200	Clock, Battery, 12" Diameter	1	V V	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
_0025	Mixing Valve, Emergency Fixture	1	C C	Thermostatic mixing valve is used to maintain a tempered water supply at the minimum pressure required by ANSI. Used to supply water to eye or face wash and combination units. Flow capacity is at least 8 GPM at 30 psi.	22 40 00
_0041	Window, Pass-Thru	1	C C	Pass through window which can be open from both sides. Window has 1/4 inch thick tempered glass. Window has a shelf extended at least 12 inches on both sides.	08 56 19
M0512	Television, HDTV, Large Screen, 60"	1	V V	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	V V	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers.	N/A
M1803	Workstation, Computer, Wall Mounted, Adjustable	1	V V	A wall mounted computer workstation with height adjustable monitor and keyboard arms. Keyboard and monitor can be stored within 5" to 10" of wall. Adjustable keyboard and monitor for frequent position changes. Unit contains an integrated cable management system to hide wires. A separate wall-mounted CPU holder is included.	N/A
M3072	Frame, Infectious Waste Bag w/Lid	1	V V	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.	N/A
P2000	Eyewash, Wall Mounted, Hands-Free	1	C C	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.	22 11 00
P3200	Lavatory, Vitreous China, Slab Type w/Sens Op Fauc	1	C C	Wall mounted, slab type, vitreous china, lavatory (approximately 7 x 15 x 10 inches) with faucet holes on 4 inch centers; electronic sensor operated, goose neck spout and grid strainer. It shall be suitable for use in clinics, offices and patient care areas.	22 40 00

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
_0065	Shower, Emergency, Ceiling Mounted	1	C C	Deluge safety shower. This is a complete, semi concealed safety station consisting of a ceiling mounted emergency shower. Used anywhere exposure to hazardous substances may occur.	22 40 00
S0940	Washer/Disinfector,STM,1DO,RSCD1WLL,26X24X24 Cham	2	V V	A recessed mounted (through one wall), single door (vertical sliding with tempered glass window), multi-level, mechanical, washer/disinfector, minimum chamber size 26X24X24, utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. Processing cycles are pre-programmed with pre-wash, wash/cleaning, rinse, and thermal rinse/disinfection. For use in health care facilities and laboratories where reusable items (instruments, utensils, anesthesia/respiratory goods, and glassware) are handled for decontamination purposes. This unit is not a substitute for terminal sterilization. Unit available with manual or power door, various electrical configurations, options, and accessories. Price based upon power door, 208V, 3-phase, with various options.	11 71 00
S2635	Cleaner, Ultrasonic, SNGL Chamber, CAB, F/S	1	C C	A free-standing, cabinet mounted, single stainless steel chamber (minimum size 10X24X12), ultrasonic cleaner. The cleaning unit includes the following minimum features: power lid, automatic detergent injector, automatic level controls, automatic timer, and switch fill and drain controls. Sonic cleaning energy provided to the chamber by transducers which are powered by a solid-state generator(s) at a frequency of 40 kHz. Designed for use in surgery reprocessing areas, central processing departments and laboratories to clean surgical instruments and other hardware with sonic energy.	11 71 00

4. AUTOMATED CART WASHER (CWSH2)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
S3185	Washer, Cart & Utensil, 2 DO, PIT MNTD, RCSD 2 WLL	1	C C	A recessed (through two walls), pit mounted, double door (right or left-hinged, appropriate configuration to be indicated on equipment elevation drawings), cart and utensil washer (minimum chamber load capacity 78X34X76). A microprocessor-based controller monitors and controls system operations and functions. The unit provides: visual and/or audible indication of cycle operation, programmable treatment time and temperatures, and a minimum of three cycles (wash with detergent, rinse, and drying). For use in central processing to clean and decontaminate, carts, patient-care utensils (IV poles, wheel chairs, stretchers, etc.) and other bulk items. Various electrical configurations are available, for pricing 208V, 60HZ, 3-phase is used.	11 71 00

5. MANUAL CART WASH (CWSH3)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	C C	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	V V	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.	N/A

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
P6150	Sink, Cage Washing, SS, Single Compartment, F/S	1	C C	A free standing, single compartment (16"x36"x24"), #14 gauge Type 304 stainless steel, cage washing sink with gooseneck spout and lever handle drain. Sink is all welded construction with rolled rims. Ends and integral drainboards are welded. Sink has 15" high back, stainless steel adjustable angle frame legs and soap dish. It is available with or without drainboard(s). For general purpose use in laboratory research and vet areas for washing small animal cages. Pricing based upon a sink with 24" left drainboard.	22 40 00

6. STORAGE ROOM, WATER TREATMENT AND DETERGENT (CSWT1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
K2020	Dispenser, Detergent, Automatic	1	C C	Automatic detergent dispenser. Characteristics/components include supporting chemicals; detergent additive and rinse additive. This unit is used in conjunction with commercial dishwashers in hospitals and restaurants. Wall mounted unit, sized for the operation.	11 71 01
M4871	System, Reverse Osmosis, Water	1	V V	Reverse osmosis system to purify water in hemodialysis clinics and other clinical areas. The system consists of a pump, water softener, media and carbon filters, processing unit, ultraviolet sterilizer, final filtration, deionizers, osmosis units, controls and monitors. The system alarms when a malfunction occurs. The system usually requires a room of its own. Refer to the manufacturers specifications for exact installation requirements. Database system weight does not include the water in the piping or holding tanks of an operating system.	22 67 19.67

7. HOUSEKEEPING AIDES CLOSET (HAC) (JANC2)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A5075	Dispenser, Soap, Disposable	1	V V	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	10 28 00
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	C C	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5135	Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd	1	C C	A surface mounted, satin finish stainless steel, utility shelf with a maximum of 6 mop/broom holders and 5 rag hooks. Utility shelf features: 8" deep shelf; mounting brackets welded to shelf; spring activated rubber cam holders; and drying rod. Unit is available in various widths 30" (minimum, 3 holders and 2 hooks) to 48" (maximum, 6 holders and 5 hooks). For use in janitor closets. Pricing based on a 36" width.	10 28 00
F0505	Bucket, Mop, With Wringer, 26 Quart	1	V V	Mobile mop bucket / wringer combination, approximately 35" H x 17" W x 22" D with four 2" casters. Total capacity is 26 quarts. Unit used for general hard surface floor maintenance.	N/A
_0025	Mixing Valve, Emergency Fixture	1	C C	Thermostatic mixing valve is used to maintain a tempered water supply at the minimum pressure required by ANSI. Used to supply water to eye or face wash and combination units. Flow capacity is at least 8 GPM at 30 psi.	22 40 00
_0053	Dispensing System, Cleaning Solution	1	V V	Cleaning chemical dispensing system. Includes wall mounted dispenser, lockable cabinet, brass quick-connect hardware, low and high flow dispense hoses, and application chart.	11 71 01
	or				

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
_0049	Micro Scrubber, Floor, Automatic	1	V V	Floor cleaning device used to scrub small and congested areas and has either rotary or cylindrical scrubbing head with an automated cleaning solution dispensing system and vacuuming system. Device can be battery operated.. For clean side of SPS only.	N/A
M2080	Shelving, Storage, Solid, CRS, w/Adjustable Shelves	1	V V	Stationary, solid, shelving unit. Unit has fully adjustable shelves constructed of solid stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 76"H x 18"D x 48"W with four shelves.	12 31 00
M2600	Vacuum, Wet/Dry, HEPA Filtration	1	V V	Wet/dry vacuum cleaner with HEPA filtration. Unit consists of a minimum 10 gallon capacity corrosion resistant waste tank, two stage vacuum motor and dual filtering system mounted on casters. Vacuum is designed for use in patient care areas and operating room suites. For soiled side of SPS only.	N/A
P2000	Eyewash, Wall Mounted, Hands-Free	1	C C	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.	22 11 00
P4700	Sink, Mop, Molded Stone	1	C C	Mop service sink. Also called a mop service basin and a mop receptor. Unit is made of molded stone and is a one piece item. It shall include a service faucet hose, hose bracket and mop hanger. Used in utility rooms for cleaning mops and floor cleaning equipment.	22 40 00

B. FA2: SCOPE PROCESSING AREA

1. ANTEROOM, SCOPE PROCESSING (CSAR1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1010	Telecommunication Outlet	1	C C	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	C C	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1066	Mirror, Float, Glass, With SS Frame	1	C C	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.	10 28 00
A5075	Dispenser, Soap, Disposable	1	V V	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	10 28 00
A5077	Dispenser, Hand Sanitizer, Hands Free	1	V V	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	C C	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
CT050	Countertop, Staniless Steel	AR	C C	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.	12 36 00
F2010	Basket, Wastepaper, Step-On	1	V V	"Step-on" wastepaper basket with inner liner and foot petal activated flip top.	N/A
P3100	Lavatory, Vitreous China, Slab type	1	C C	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

2. ALCOVE, PPE (CSPE1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
See Above: A. Decontamination Area, 2. Alcove, PPE (CSPE1)					

3. DECONTAMINATION ROOM (CSSD1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1195	Counter, Cleanup, With 2 or 3 Sinks	2	C C	Two or three sink cleanup counter. Unit is constructed of type 304 corrosion resistant stainless steel. It consists of three sinks 14"W X 16"H X 10"D, hot and cold water faucet, and pre-rinse spray hose. Equipped with channel reinforced drainboards, and backsplash, and supported by tubular stainless steel legs. Unit is designed for use in control sterile supply decontamination areas.	12 36 00
A5075	Dispenser, Soap, Disposable	1	V V	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	10 28 00
A5077	Dispenser, Hand Sanitizer, Hands Free	1	V V	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	C C	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5106	Waste Disposable Unit, Sharps w/Glove Dispenser	1	V V	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked	N/A
CT050	Countertop, Staniless Steel	AR	C C	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.	12 36 00
F0540	Cart, Scope, Transport	1	V V	A cart designed specifically for the safe transport of endoscopy scopes. The cart will have a lightweight frame of a tubular welded construction. The sides and back panels will be of a foamed resin with a work top of seamless, raised edge plastic. The cart will have rectangle or round trays with lids and will have 4 casters with 2 locking. Cart may have a roll-top door with a key lock.	N/A

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
F3200	Clock, Battery, 12" Diameter	1	V V	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
_0025	Mixing Valve, Emergency Fixture	1	C C	Thermostatic mixing valve is used to maintain a tempered water supply at the minimum pressure required by ANSI. Used to supply water to eye or face wash and combination units. Flow capacity is at least 8 GPM at 30 psi.	22 40 00
_0041	Window, Pass-Thru	1	C C	Pass through window which can be open from both sides. Window has 1/4 inch thick tempered glass. Window has a shelf extended at least 12 inches on both sides.	08 56 19
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	V V	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers.	N/A
M1803	Workstation, Computer, Wall Mounted, Adjustable	1	V V	A wall mounted computer workstation with height adjustable monitor and keyboard arms. Keyboard and monitor can be stored within 5" to 10" of wall. Adjustable keyboard and monitor for frequent position changes. Unit contains an integrated cable management system to hide wires. A separate wall-mounted CPU holder is included.	N/A
M3072	Frame, Infectiuos Waste Bag w/Lid	1	V V	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.	N/A
P2000	Eyewash, Wall Mounted, Hands-Free	1	C C	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.	22 11 00
P3100	Lavatory, Vitreous China, Slab Type	AR	C C	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00

4. SCOPE PROCESSING ROOM (CSSP1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1010	Telecommunication Outlet	1	C C	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	C C	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A1066	Mirror, Float, Glass, With SS Frame	1	C C	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas.	10 28 00
A5075	Dispenser, Soap, Disposable	1	V V	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	10 28 00
A5077	Dispenser, Hand, Sanitizer, Hands Free	1	V V	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	C C	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
CT050	Countertop, Stainless Steel	AR	C C	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.	12 36 00
F0540	Cart, Scope Transport	1	V V	A cart designed specifically for the safe transport of endoscopy scopes. The cart will have a lightweight frame of a tubular welded construction. The sides and back panels will be of a foamed resin with a work top of seamless, raised edge plastic. The cart will have rectangle or round trays with lids and will have 4 casters with 2 locking. Cart may have a roll-top door with a key lock.	N/A
F2010	Basket, Wastepaper, Step-On	1	V V	"Step-on" wastepaper basket with inner liner and foot petal activated flip top.	N/A
F3200	Clock, Battery, 12" Diameter	1	V V	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
_0025	Mixing Valve, Emergency Fixture	1	C C	Thermostatic mixing valve is used to maintain a tempered water supply at the minimum pressure required by ANSI. Used to supply water to eye or face wash and combination units. Flow capacity is at least 8 GPM at 30 psi.	22 40 00
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	V V	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers.	N/A
P2000	Eyewash, Wall Mounted, Hands-Free	1	C C	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.	22 11 00
P3100	Lavatory, Vitreous China, Slab Type	1	C C	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00
S2615	Washer, Disinfecting, Ultrasound Probe	1	V V	A complete ultrasound transducer high-level disinfection system that is fast, easy to use and environmentally friendly. It uses a unique platform technology to effectively disinfect the transducer, including the shaft and handle in just seven minutes with no exposure to harmful chemicals. The process operates within a closed system.	11 71 01
S2627	Automatic Endoscope Reprocessor(AER)	1	V V	A low temperature sterile processing system for sterilizing immersible surgical and diagnostic scopes, cameras, instruments and accessories. The unit shall provide a digital display of cycle data and shall record and print a permanent record of cycles. Units are available in floor, counter top or cart models.	11 71 01

5. SCOPE STAGING ROOM (CSST1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
F0540	Cart, Scope, Transport	1	V V	A cart designed specifically for the safe transport of endoscopy scopes. The cart will have a lightweight frame of a tubular welded construction. The sides and back panels will be of a foamed resin with a work top of seamless, raised edge plastic. The cart will have rectangle or round trays with lids and will have 4 casters with 2 locking. Cart may have a roll-top door with a key lock.	N/A
_0038	Cabinet, Scope Drying	3	V V	Scope drying cabinet. Cabinet uses HEPA filtered medical grade dry air supply to efficiently dry scopes at low temperatures. Cabinet has the capacity to hold up to 6 scopes.	11 71 01

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC

C. FA3: PREPARATION AND ASSEMBLY AREA

1. CLEAN WORKROOM, INSTRUMENT SET ASSEMBLY (CSIA1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1010	Telecommunication Outlet	1	C C	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	C C	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A5075	Dispenser, Soap, Disposable	1	V V	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	10 28 00
A5077	Dispenser, Hand, Sanitizer, Hands Free	1	V V	A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	N/A
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	C C	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
CT050	Countertop, Stainless Steel	AR	C C	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.	12 36 00
F0230	Chair, Drafting, Rotary	3	V V	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.	N/A
F2700	Reader, Bar Code, Hand Held, With Interface	1	V V	Hand held laser bar code reader with computer interface. Used for automated inventory, using bar code stickers / labels. Convenience outlet required at point of use.	N/A
_0045	Cabinet, Instrument, SS surface	4	C C	Instrument Cabinet is made of solid steel. Cabinet top working surface is stainless steel. Cabinet has separate drawer storage compartments. Each drawer has a maximum load capacity of at least 440 lbs evenly distributed. 28"w x 33"h x 28"d. Used for instrument storage.	12 31 00
_0046	Cabinet, FS, Peg Board	2	C C	Floor standing storage cabinet approximately 35"w x 76"h x 16"d, with removable stainless pegboard, 2 framed glass hinged doors, and sloping top. Used to store endoscopy equipment, large instruments and other equipment items.	12 31 00
_0064	Cabinet, Wall Mounted, SS, Sloping Top	2	C C	Wall hung stainless steel cabinet with adjustable shelves, solid hinged clear glass doors, and sloping top. For storing purpose in areas where stainless steel cabinets are used.	12 31 00
_0047	Rack, Sterile Wrap	1	V V	Chrome plated rack used to hang sterile wrapping materiel. The unit is mobile consisting of 4 swivel casters, 4 posts, 4 support bars and wire bottom shelf. 60"w x 24"d	N/A
_0048	Cart, Washer Transfer	2	V V	Stainless steel transfer cart for transferring instruments and accessories into and out of washer / disinfector. Includes one storage shelf with 4 casters and an integrated tub / docking and rack locking devices. Fixed height.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	4	V V	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers.	N/A

PG-18-5: 285 STERILE PROCESSING SERVICE

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
M1825	Printer, Computer	2	V V	High resolution computer printer with minimum 600dpi resolution and a variety of type styles and sheet/envelope feeder trays. Printer will have network and wireless capability with USB port, ethernet port and RJ-11 telephone port. Printer will have light or heavy use capabilities are available.	N/A
P3100	Lavatory, Vitreous China, Slab Type	1	C C	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	22 40 00
S9610	Station, Utility / Rack	3	C C	Rack / utility station. The station consists of a stainless steel countertop, 4-1/2" apron, legs and necessary cross-member supports. The stations are specially designed to handle loading racks or trays for use with a specific manufacturer's related equipment and accessories but may also serve a variety of general uses, such as an accumulating, sorting, inspecting, or processing station. Various station widths/lengths (25" to 126", depending upon manufacturer) are available. Pricing based on 48' width/length.	11 71 00

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
S0940	Washer / Disinfector	2	C C	A recessed mounted (through one wall), single door (vertical sliding with tempered glass window), multi-level, mechanical, washer/disinfector, minimum chamber size 26X24X24, utilizing facility supplied steam. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. Processing cycles are pre-programmed with pre-wash, wash/cleaning, rinse, and thermal	N/A

2. STORAGE, STERILE PROCESSING SUPPLIES (SRSP1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
_0066	Cabinet, Floor Standing, SS, Sloping Top, 84" x 30"	2	C C	Floor standing stainless steel cabinet with adjustable shelves, solid hinged clear glass doors, and sloping top. For storing purpose in areas where stainless steel cabinets are used. 30"w x 24"d x 84"h.	12 31 00
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	4	V V	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.	N/A

D. FA4: STERILIZATION AREA

1. STERILIZATION AREA, STEAM (CSSS1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1010	Telecommunication Outlet	1	C C	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	C C	Telephone, wall mounted, 1 line, with speaker.	27 31 00
A5160	Shelf, 8"Depth, SS, Surface Mounted	AR	C C	A surface mounted, satin finish, stainless steel shelf with a minimum depth of 8". Mounting brackets are welded to shelf. Shelf is available in various widths. For general purpose use in scrub areas/rooms or other areas of the facility where a SS shelf is required. Pricing based upon a 36" width.	12 32 00
CT050	Countertop, Stainless Steel	AR	C C	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.	12 36 00
_0042	Reader, Biological	1	V V	A rapid readout biological that monitors the effectiveness of the sterilization process with results usually within one hour. System consists of biological indicators and auto-reader. Auto-reader has advance electronics LCD panel and audible alarm.	N/A
_0044	Sterilizer, Stm, VAC, 2DO, RCSD 2WLL, 26"w x 26"h x 49"d ch	2	C C	A recessed mounted (through two walls), double door (right or left-hinged, appropriate door configuration to be indicated on equipment elevation drawings), vacuum sterilizer. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. Doors may be power operated.	11 71 01

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
_0050	Loading Cart & Transfer Carriage	4	V V	Loading cart and transfer carriage for use with sterilizers having a 26"w x 26"h x 49"d chamber. Loading cart is a framework with two full-length adjustable shelves of CRS welded sheet metal and wire. Transfer carriage is constructed of a welded CRS or painted for corrosion protection frame. Loading cart is secured to the transfer carriage by a locking mechanism. For loading and unloading 26"w x 26"h x 49"d sterilizers and for transferring goods to / from processing areas.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	V V	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers.	N/A

2. STERILIZATION AREA, LOW TEMP (CSLT1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1010	Telecommunication Outlet	1	C C	Telecommunication outlet location.	27 31 00
S5505	Sterilizer, Hydrogen Peroxide Gas, 3.5 cu ft Cham	2	V V	A floor mounted, low temperature hydrogen peroxide gas plasma sterilizer. Sterilization chamber shall have a capacity of approximately 3.5 cubic feet (100 liters). The sterilizer shall be capable of processing metal instruments, plastics, heat and moisture sensitive devices in approximately 75 minutes with no aeration required. Unit shall be equipped with a visual display and audible alarm. A built in printer will provide system performance record for each cycle.	11 71 01

3. ETHYLENE OXIDE GAS STERILIZATION (EtO) ROOM (CSEO1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1010	Telecommunication Outlet	1	C C	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	C C	Telephone, wall mounted, 1 line, with speaker.	27 31 00
F2000	Basket, Wastepaper, Round, Metal	1	V V	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	V V	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M2015	Cabinet, Storage, Flammable, Freestanding	1	V V	Freestanding flammable safety storage cabinet. Size as required. Unit is of all welded steel wall construction with vented grounding attachments, raised leak proof door sill and adjustable shelving. Equipped with swinging doors and built-in key lock. Designed for storage of flammable fluids. Complies with OSHA standards, is FM approved and designed IAW NFPA 30.	N/A
S0290	Rack, 2SH, 20x20x38 CHMBR	2	C C	Rack with two extendable shelves for use with sterilizers having a 20X20X38 chamber. For use in providing loading efficiency for a wide variety of mixed or single item loads.	11 71 00
_0056	Sterilizer, Ethylene Oxide (EtO)	2	C C	A recessed mounted (through one wall), low temperature, single door, vacuum, Ethylene Oxide (EtO) sterilizer. Sterilizer uses single-dose EtO cartridges for sterilization. Chamber shall have a capacity of approximately 7.9 cubic feet (223.7 liters). The sterilizer shall be capable of processing metal instruments, and heat and moisture sensitive devices. Unit shall be equipped with a visual display and audible alarm. A built-in printer will provide a system performance record for each cycle.	11 71 00
_0058	Monitoring System, Ethylene Oxide (EtO)	1	V V	An Ethylene Oxide area monitoring systems with multiple sampling points. Remote alarm available with audible and visual alarms and back up power.	11 71 00

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC

4. ETHYLENE OXIDE GAS STERILIZATION (EtO) ABATOR ROOM (CSEO2)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1010	Telecommunication Outlet	1	C C	Telecommunication outlet location.	27 31 00
_0057	Abator, Ethylene Oxide (EtO)	2	C C	A system device which removes Ethylene Oxide (EtO) from the exahust of an EtO steilizer and converts the exhaust into carbon dioxide before bieng emiitted into the atmosphere.	11 71 00

5. CART RETURN AREA (CHC01)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1010	Telecommunication Outlet	1	C C	Telecommunication outlet location.	27 31 00
M8910	Cart, Surgical Case	6	V V	Surgical case cart. Unit consists of two hinged cabinet sections, each section equipped with two pull-out shelves with stops. The entire unit is mounted on four heavy duty conductive swivel casters. Used to transport surgical packs and supplies to surgery and soiled items back to central supply	12 31 00

6. UNLOADING / COOLING AREA (CHC01)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
See Above: D. Sterilization Area, 5. Cart Return Area (CHC01)					

7. EQUIPMENT, CLEAN STEAM GENERATOR (CSCG1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
_0040	Steam to Steam Heat Exchanger	1	C C	A steam to steam heat exchanger is designed to use facility provided utilities for sterilization where pure steam is required. The system can be single or double verically mounted. May be a stand alone system.	11 71 00

E. FA5: RECEIVING, STORAGE AND DISPATCH AREA

1. VENDOR DROP-OFF / PICK-UP AREA (SRS01)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1010	Telecommunication Outlet	1	C C	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	C C	Telephone, wall mounted, 1 line, with speaker.	27 31 00
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	4	V V	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.	N/A

2. DISPATCH AREA (CHC01)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
See Above: D. Sterilization Area, 5. Cart Return Area (CHC01)					

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
3. WORKSTATION, CASE CART DISPATCH (OFA07)					
JSN	**NAME**	**QTY**	**ACQ / INS**	**DESCRIPTION**	**SPEC**
A1010	Telecommunication Outlet	1	C C	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	1	C C	Telephone, desk, multiple line.	27 31 00
E0123	Workstation, Straight, Free Standing, 72" W	1	V V	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File	N/A
F0275	Chair, Swivel, High Back	1	V V	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	V V	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers.	N/A
4. STORAGE, STERILE DURABLES (STERILE INSTRUMENTS) (SRS05)					
JSN	**NAME**	**QTY**	**ACQ / INS**	**DESCRIPTION**	**SPEC**
A1010	Telecommunication Outlet	1	C C	Telecommunication outlet location.	27 31 00
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	C C	Telephone, wall mounted, 1 line, with speaker.	27 31 00
F3200	Clock, Battery, 12" Diameter	1	V V	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	5	V V	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.	N/A
5. CASE CART ASSEMBLY AREA (CSCQ1)					
JSN	**NAME**	**QTY**	**ACQ / INS**	**DESCRIPTION**	**SPEC**
A1010	Telecommunication Outlet	1	C C	Telecommunication outlet location.	27 31 00

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
M8910	Cart, Surgical Case	6	V V	Surgical case cart. Unit consists of two hinged cabinet sections, each section equipped with two pull-out shelves with stops. The entire unit is mounted on four heavy duty conductive swivel casters. Used to transport surgical packs and supplies to surgery and soiled items back to central supply	12 31 00

6. HOUSEKEEPING AIDES CLOSET (HAC) (JANC2)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
See Above: A. Decontamination Area, 7. SPS Housekeeping Aides Closet (HAC) (JANC2)					

F. FA6: STAFF AND ADMINISTRATIVE AREA

1. OFFICE, STERILE PROCESSING SERVICE (SPS) CHIEF (OFA09)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1010	Telecommunication Outlet	2	C C	Telecommunication outlet location.	27 31 00
A1015	Telephone, Desk, Multiple Line	1	C C	Telephone, desk, multiple line.	27 31 00
E0090	Workstation, L-Shaped, Festanding, 72x72	1	V V	THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels	N/A
F0205	Chair, Side With Arms	1	V V	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.	N/A
F0275	Chair, Swivel, High Back	1	V V	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.	N/A
F0420	Cabinet, Filing, Lateral, Half Height	1	V V	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	V V	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	V V	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	V V	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers.	N/A
M1825	Printer, Computer	1	V V	High resolution computer printer with minimum 600dpi resolution and a variety of type styles and sheet/envelope feeder trays. Printer will have network and wireless capability with USB port, ethernet port and RJ-11 telephone port. Printer will have light or heavy use capabilities are available.	N/A

2. OFFICE, STERILE PROCESSING SERVICE (SPS) ASSISTANT CHIEF (OFA09)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
See Above: F. FA6: Staff and Administrative Area, 1. Office, Sterile Processing Service (SPS) Chief (OFA09)					

3 WORKSTATION, CLERICAL (OFA07)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
See Above: E. FA5: Receiving, Storage and Dispatch Area, 3. Workstation, Case Cart Dispatch (OFA07)					

4. CONFERENCE ROOM / TRAINING ROOM (CRA01)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1010	Telecommunication Outlet	3	C C	Telecommunication outlet location.	27 31 00
A1011	Telephone, Desk, 1 Line	1	C C	Telephone, desk, 1 line.	27 31 00
A5145	Hook, Garment, Double, SS, Surface Mounted	2	C C	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	1	V V	A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA compliant unit with a load capacity of up to 130 lbs.	N/A
A5220	Bracket, Television, Wall Backing	1	C C	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12” 16” or 24” stud spacing.	N/A
A6046	Artwork, Decorative, With Frame	2	V V	This JSN is to be used for determining and defining location of decorative artwork.	N/A
F0220	Chair, Conference	8	V V	Conference chair designed to complement the executive furniture package selected. Foam rubber cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel casters.	N/A
F0690	Workstation, Computer, Enclosed, With Lock	1	V V	Computer operator workstation ,approximately 58" high X 36" wide X 25" deep. A fully enclosed workstation for a computer, monitor, printer and supplies. Cabinet has two lockable doors.	N/A
F0755	Table, Conference, Wood	1	V V	Executive conference table. Dimensions are approximately 30" high, 48" wide with lengths varying from 74" to 96". These tables add traditional elegance to any conference room.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	V V	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	V V	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
M0385	Projector, Multimedia/Data	1	V V	The projector shall provide computer and video projections. Minimum features included: Brightness of not less than 1500 ANSI (American National Standards Institute) Lumens, and a minimum resolution format of 1024 X 768 pixels (XGA). The projector shall be portable and weigh no more than 10 pounds. It shall include a zoom lens and computer and video input ports.	N/A
M0400	Screen, Projection, 144x144, Remote Control	1	C C	Wall or ceiling mounted, roll-up type screen with remote control. Includes multiple controls to operate the screen from two or more locations, wireless remote control, adjustable preset limit switches, and black borders on all sides. Screen is housed in a solid wood or metal case with removable motor module. For a classroom, conference room, or large auditorium.	N/A
M0507	Video Teleconferencing System	1	V V	Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing capabilities to dispersed geographic sites.	N/A
M0512	Television, HDTV, Large Screen, 60"	1	V V	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand.	N/A
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	V V	Desk top microprocessing computer. The unit shall consist of a central processing micro tower, flat panel monitor, keyboard, mouse and speakers.	N/A
M1875	Board, Copy, Electronic Facsimile	1	V V	Electronic facsimile copy board for use in conference rooms and classrooms. Available in a variety of sizes. Unit scans writing surface and makes a paper copy of the board's contents. The user can make multiple copies of a single scanning. Single sided version, single copy version, and office size boards are options. May have a PC interface option. Database pricing reflects a mobile two-panel copy-board with a minimum 33" x 66" writing surface. Depth dimension refers to depth at the caster level of the supporting frame.	N/A

5. COPIER / OFFICE SUPPLY ROOM (RPR01)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1010	Telecommunication Outlet	2	C C	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	C C	Telephone, wall mounted, 1 line	27 31 00
F0102	Cabinet, Distribution, Mail	1	V V	Mail distribution cabinet. Horizontal style distribution boxes. Unit consists of adjustable horizontal dividers and/or adjustable shelves. Unit can be customized to fit the client needs. Used for mail distribution.	N/A
F0465	Cabinet, Storage, 2 Door, 5 Shelf	1	V V	Storage cabinet, 78" high X 48" wide X 24" deep with two (2) doors and five (5) adjustable shelves.	N/A
F0775	Table, Work, 2 Drawer	1	V V	Work table approximately 32" high X 72" wide X 30" deep with two drawers and a hard wood top.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	V V	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F2550	Shredder, Paper Heavy Duty	1	V V	Shredder shall be able to process a minimum of 25 sheets of paper per pass at a minimum rate of 20 feet per minute. The unit shall have a 16 inch throat to accept paper. Paper shall be shredded into 1/4 inch strips.	N/A

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
M1810	Copier, Floor Standing, Digital	1	V V	Floor standing copier. Unit features automatic paper size selection, automatic document feeder and sorter. The system also has zoom capabilities and automatic two-sided copying. For use where medium volume reproduction is required in the range of 30 to 40 copies per minute.	N/A
M1835	Printer, Color Laser, Large	1	V V	Color laser printer designed for high volume use and network capable. The printer shall be capable of printing a minimum of 25 pages per minute (ppm) of black print and 20 ppm color print. Resolution shall be no less than 600 X 600 dpi. It shall be capable of printing on multiple media types (plain, inkjet, photo paper and transparencies) and be capable of accepting media sizes of 3 X 5 to 8.5 X 14 inches. The printer is used in multi-user network offices.	N/A
M1855	Facsimile Machine	1	V V	Plain paper facsimile unit used to transmit printed matter or images over standard telephone lines. The unit operates at a modem speed of 33.6 Kbps and automatically recognizes and communicates with a variety of standard facsimile machines. Commonly referred to as "fax" unit.	N/A

6. LOUNGE, STAFF (SL001)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1010	Telecommunication Outlet	1	C C	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	C C	Telephone, wall mounted, 1 line.	27 31 00
A1080	Mirror, Posture, Wall Mounted	1	C C	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.	10 28 00
A5075	Dispenser, Soap, Disposable	1	V V	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	10 28 00
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	C C	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	10 28 00
A5145	Hook, Garment, Double, SS, Surface Mounted	AR	C C	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	C C	Wall mounted television bracket with adjustable arm. Consists of platform movable arm with full 120 degree swivel. Designed for holding wall mounted television units in patient rooms.	N/A
A5220	Bracket, Television, Wall Backing	1	C C	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12” 16” or 24” stud spacing.	N/A
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	C C	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.	12 32 00
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	C C	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.	12 32 00
C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	C C	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.	12 32 00

PG-18-5: 285 STERILE PROCESSING SERVICE

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
CB020	Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 38x24x13	2	C C	Wall hung cabinet with two adjustable shelves, solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a solid hinged single door case. For general purpose use throughout the facility.	12 32 00
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	C C	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.	22 40 00
CT020	Countertop, Solid Surface	7	C C	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.	12 36 00
F0225	Chair, Dining Room	4	V V	Dining room chair with glides. Chair has straight legs with cushioned cloth or vinyl seat.	N/A
F0795	Table, Dining	1	V V	Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons.	N/A
F2015	Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	1	V V	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.	N/A
F3065	Whiteboard/Bulletin Board, Combination	1	V V	A combination whiteboard and bulletin board, half LCS and half cork. Available with either aluminum or wood frame. It can be used in patient rooms or in any appropriate space in the facility.	N/A
F3200	Clock, Battery, 12" Diameter	1	V V	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
K1552	Brewer, Coffee, Auto, Elec, 3 Burner, Front/Back	1	V V	Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.	N/A
K4665	Oven, Microwave, Consumer	1	V V	Counter mounted microwave oven for average duty use. The exterior cabinet can be metal or heavy duty impact resistant plastic. The oven delivers instant energy for rapid heating, defrosting or prime cooking. The oven has touch pad controls, digital timer, power level selector and preprogrammed selectors for commonly cooked items. This oven is commonly found in staff lounges.	N/A
M0515	Television, Plasma	1	V V	42" diagonal screen, high definition (HDTV) multimedia flat panel plasma display television. The TV will have a 16:9 wide screen aspect ratio, a minimum of 1024 x 768 display resolution, NTSC tuner, built-in stereo speakers and surround sound.	N/A

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
R7250	Refrigerator/Freezer, 20 Cubic Feet	1	V V	Refrigerator/freezer unit. This type unit includes a food saver system that helps keep food fresher. It also includes roll out wheels and is equipped for an optional automatic icemaker. This unit is of commercial or residential design and use.	N/A

7. TOILET, STAFF (TLTU1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A1067	Mirror, Float Glass, ADA Acessible	1	C C	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.	10 28 00
A5075	Dispenser, Soap, Disposable	1	V V	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	10 28 00
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	C C	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are place in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.	10 28 00
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	C C	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.	10 28 00
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	C C	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.	10 28 00
A5145	Hook, Garment, Double, SS, Surface Mounted	1	C C	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	C C	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.	10 28 00
F2010	Basket, Wastepaper, Step-On	1	V V	"Step-on" wastepaper basket with inner liner and foot petal activated flip top.	N/A
P3000	Lavatory, Vitreous China, Straight Back	1	C C	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.	22 40 00
P9050	Toilet, Wall Hung, Siphon Jet	1	C C	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flush valve, seat with open front and check hinge, and carrier. Used throughout the health care facility in restrooms.	22 40 00

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
8. LOCKER / CHANGING ROOM, MALE (LR002)					
JSN	**NAME**	**QTY**	**ACQ / INS**	**DESCRIPTION**	**SPEC**
A1010	Telecommunication Outlet	1	C C	Telecommunication outlet location.	27 31 00
A1012	Telephone, Wall Mounted, 1 Line	1	C C	Telephone, wall mounted, 1 line.	27 31 00
A1030	Locker, 2 Person, Over/Under	10	V V	Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal belongings. Other width and depths are available.	27 31 00
A1080	Mirror, Posture, Wall Mounted	1	C C	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.	10 28 00
A5025	Bench, Locker Room, Portable	AR	V V	Portable locker room bench. Approximately 1-1/2" thick. Benches shall be laminated hardwood with a moisture resistant sealer or anodized aluminum Units are mounted on strong pedestals.	N/A
F2000	Basket, Wastepaper, Round, Metal	1	V V	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.	N/A
F3200	Clock, Battery, 12" Diameter	1	V V	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).	N/A
9. LOCKER / CHANGING ROOM, FEMALE (LR002)					
JSN	**NAME**	**QTY**	**ACQ / INS**	**DESCRIPTION**	**SPEC**
See Above: F. Staff and Administration Area, 10. Locker / Changing, Male (LR002)					
10. TOILET / SHOWER, MALE (TLTS1)					
JSN	**NAME**	**QTY**	**ACQ / INS**	**DESCRIPTION**	**SPEC**
A1090	Mirror, Float Glass, With SS Frame & Shelf	1	C C	A high quality 1/4" polished float glass mirror, approximately 36' H X 18' W framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners and an integral stainless steel, stain finish, shelf. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in restroom areas, Doctor examination areas, offices, etc. May also be used above double lavatories, either wall or countertop mounted.	10 28 00
A5030	Bench, Stall, Shower, Built In	1	C C	Shower bench; built-in. Eighteen (18) gauge stainless steel frame with anchors built-in into the wall. Size and shape as required.	10 28 00
A5075	Dispenser, Soap, Disposable	2	V V	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.	10 28 00

PG-18-5: 285 STERILE PROCESSING SERVICE

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	C C	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are place in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.	10 28 00
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	C C	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.	10 28 00
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	AR	C C	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.	10 28 00
A5110	Grab Bar, 1-1/4" Dia., SS, 2 Wall, Shower Use	AR	C C	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall shower, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical applications in shower stalls where ADA (American's With Disabilities Act) requirements must be met.	10 28 00
A5145	Hook, Garment, Double, SS, Surface Mounted	1	C C	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.	10 28 00
A5170	Rod, Shower Curtain, 1"Diameter, W/Curtain & Hooks	1	C C	A concealed mounted, 1" outside diameter, satin finish stainless steel, shower curtain rod with white vinyl shower curtain (72" H) and SS shower curtain hooks. Rod and curtain available in various widths. For general purpose use at shower stall or bathtub locations. Pricing based upon standard shower stall dimensions of 36" x 36" and a standard curtain height of 72".	10 28 00
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	C C	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.	10 28 00
A5205	Bar, Towel, 1" Diameter, SS, Surface Mounted	1	C C	A surface mounted, satin finish stainless steel, 1" diameter, towel bar. Support posts and flanges are one piece, chrome-plated, cast heavy brass with satin finish. Towel bar shall not rotate within support posts. Available in 18", 24" and 30" widths. For general purpose use in shower or bathtub rooms. Pricing based upon a suggested standard width of 18".	10 28 00
F2010	Basket, Wastepaper, Step-On	1	V V	"Step-on" wastepaper basket with inner liner and foot petal activated flip top.	N/A
P3000	Lavatory, Vitreous China, Straight Back	1	C C	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.	22 40 00

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
P5040	Shower, Single, Hand-Held	1	C C	A complete, barrier-free, single hand-held, personal shower system. The shower system includes: pressure balanced mixing valve with high temperature limit stop; personal hand shower; shower hose; wall supply; and slide bar. For general purpose use throughout the facility in shower stalls.	22 40 00
P9050	Toilet, Wall Hung, Siphon Jet	1	C C	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.	22 40 00

11. TOILET / SHOWER, FEMALE (TLTS1)

JSN	NAME	QTY	ACQ / INS	DESCRIPTION	SPEC
See Above: F. Staff and Administration Area, 12. Toilet / Shower, Male (TLTS1)					