

NUTRITION AND FOOD SERVICE (224)

1 - MAIN KITCHEN STAFF AND ADMINISTRATIVE AREA

1 - OFA09 - Office, Nutrition and Food Service Chief

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

NUTRITION AND FOOD SERVICE (224) - Contents - VA PG-18-5 (18 Jul 2016 04:58PM ET)

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
2 - SEC01 - Secretary / Waiting				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0305	Chair, Waiting Room, Single	2	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.
F0405	Cabinet, Filing, Full Height, 4-5 Drawer	1	VV	Four (4) or five (5) drawer letter size, vertical filing cabinet, 53" high X 15" wide X 29" deep with locking device. Each drawer has label holder, handle and roller cradle.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.

3 - OFA07 - Workstation, Clerical

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.

NUTRITION AND FOOD SERVICE (224) - Contents - VA PG-18-5 (18 Jul 2016 04:58PM ET)

F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

4 - OFA09 - Office, Nutrition and Food Service Assistant Chief

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

5 - OFA07 - Workstation, Internship Director

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
-------	---	---	----	--

6 - OFA07 - Workstation, Clinical Administration Section Chief

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

7 - OFA07 - Workstation, Dietitian				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
8 - OFA07 - Workstation, Food Production and Service Foreman				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
9 - OFA09 - Office, Supervisor				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.

E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

10 - OFA07 - Workstation, Technician

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

NUTRITION AND FOOD SERVICE (224) - Contents - VA PG-18-5 (18 Jul 2016 04:58PM ET)

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

11 - OFA07 - Workstation, Cost Clerk Accountant

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

NUTRITION AND FOOD SERVICE (224) - Contents - VA PG-18-5 (18 Jul 2016 04:58PM ET)

E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

12 - OFDC2 - Consult Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.

NUTRITION AND FOOD SERVICE (224) - Contents - VA PG-18-5 (18 Jul 2016 04:58PM ET)

A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
CD040	Cabinet, W/H, 2 Shelf, 2 DO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, solid hinged doors, and sloping top. Also referred to as a solid hinged double door wall case. For general purpose use throughout the facility.
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.
CT030	Countertop, High Pressure Laminate	3	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.
F0205	Chair, Side With Arms	3	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0340	Stool, Self Adjusting	1	VV	Self adjusting stool. Consists of a foam padded upholstered seat with attached foot rest for added comfort. Mounted on swivel casters. Designed for doctor's use during examinations.
F0740	Table, Occasional, Lamp	1	VV	Occasional lamp table (end table) approximately 20" high X 27" wide X 27" deep with choice of finishes (wood, oak veneer, or high pressure laminate).
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1802	Work Station, Computer, Retractable, Wall Mounted	1	VV	A wall mounted retractable work station. Work station is used as a computer station in treatment rooms, exam rooms and areas where physical space is limited.

13 - COM C1 - Communications Center, Food Service

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
-----	------	-----	---------	-------------

NUTRITION AND FOOD SERVICE (224) - Contents - VA PG-18-5 (18 Jul 2016 04:58PM ET)

A0900	Relay Rack, Aluminum	3	VV	Rack used to hold network components such as servers, switches, hubs, patch panels, router, etc. Racks are available in varying heights, channel depths, and channel width. The model numbers specified may be U.L. Listed version with 2 Top Angles, 7' height, 19" wide, blank Aluminum, with mounting holes on both sides (front and back).
A0901	Cable Management, Horizontal Base Unit	26	VV	Horizontal cable management unit for a 19" rack with a channel approximately 2"x2". Provides for professional finish to hide cables in a switch rack. Various models are quoted with fingered type exits or brackets and/or rear access holes.
A0902	Rear Wire Frame	13	VV	For use with horizontal base unit for double sided management. This item is intended to be used with JSNs A0901 and/or A0903 model HC219 series from Hubbell only.
A0903	Rear Hinged Cover, for LAN Rack	13	VV	This item is intended to be used with JSNs A0901 and/or A0902 model HC219 series from Hubbell only.
A0904	Fiber Optic Cabinet, 36 Port, Rack Mounted	1	VV	This cabinet is designed to accommodate up to 6 six-packs of adapters or blank panels. This cabinet is specifically designed to accommodate Hubbell adapter panels as reflected in JSNs A0905 and A0906.
A0908	Patch Panel, 110 Block/RJ-45, Cat 5E, 48 Port,568A	13	VV	This 48 Port/RJ45, Cat 5e (or better) patch panel is designed for the following applications. Gigabit 1000BASE-T, 100BASE-TX, ATM 155, TP-PMD (CDDI).
A0911	Power Supply, Uninterruptable, Rack Mounted	1	VV	Uninterruptable Power Supply, Approximately 2200VA/1600W, Rack Mount with extendable Run Time. Unit must incorporate hot user swappable batteries and must have an overload indicator, replace battery indicator, audible alarm, automatic voltage regulation and include Smart Slot card and software. It must use RS232 DB-9 interface for communication. NEMA L5-30P power connector, and (8) NEMA 5-15R outlets.
A0912	Battery Pack, Extended for use with UPS (A0911)	1	VV	Battery Pack for use with JSN A0911 to extend backup power availability. Battery rated at approximately 1600 VA.
A0913	Switch, Local Area Network (LAN)	1	VV	Omni switch router, 9 slot chassis, 725W AC power supply and rack mount brackets. Supports high speed frame switching fabric. Software and Manual included. Requires management module JSN A0914 and works with Power Supply A0915.
A0914	Management Processor Module for LAN Switch	1	VV	Management processor module with 10BaseT with layer-3 switching (HRE-X); 32 MB DRAM & 8 MB flash memory. Operates over the 22G distributed switching fabric. Works with Switch LAN JSN A0913 and Power Supply A0915.
A0915	Power Supply, 725 W, for LAN Switch	1	VV	725 Watt powersupply. Redundant or spare power supply for the 9 slot Omni Switch Router. Works with Switch LAN JSN A0913 and Management Processor JSN A0914.

14 - CRA01 - Conference Room/ Training, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	3	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	1	VV	A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA compliant unit with a load capacity of up to 130 lbs.

NUTRITION AND FOOD SERVICE (224) - Contents - VA PG-18-5 (18 Jul 2016 04:58PM ET)

A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.
F0220	Chair, Conference	8	VV	Conference chair designed to complement the executive furniture package selected. Foam rubber cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel casters.
F0690	Workstation, Computer, Enclosed, With Lock	1	VV	Computer operator workstation ,approximately 58" high X 36" wide X 25" deep. A fully enclosed workstation for a computer, monitor, printer and supplies. Cabinet has two lockable doors.
F0755	Table, Conference, Wood	1	VV	Executive conference table. Dimensions are approximately 30" high, 48" wide with lengths varying from 74" to 96". These tables add traditional elegance to any conference room.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0385	Projector, Multimedia/Data	1	VV	The projector shall provide computer and video projections. Minimum features included: Brightness of not less than 1500 ANSI (American National Standards Institute) Lumens, and a minimum resolution format of 1024 X 768 pixels (XGA). The projector shall be portable and weigh no more than 10 pounds. It shall include a zoom lens and computer and video input ports.
M0400	Screen, Projection, 144x144, Remote Control	1	CC	Wall or ceiling mounted, roll-up type screen with remote control. Includes multiple controls to operate the screen from two or more locations, wireless remote control, adjustable preset limit switches, and black borders on all sides. Screen is housed in a solid wood or metal case with removable motor module. For a classroom, conference room, or large auditorium.
M0507	Video Teleconferencing System	1	VV	Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing capabilities to dispersed geographic sites.
M0512	Television, HDTV, Large Screen, 60"	1	VV	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

NUTRITION AND FOOD SERVICE (224) - Contents - VA PG-18-5 (18 Jul 2016 04:58PM ET)

M1875	Board, Copy, Electronic Facsimile	1	VV	Electronic facsimile copy board for use in conference rooms and classrooms. Available in a variety of sizes. Unit scans writing surface and makes a paper copy of the board's contents. The user can make multiple copies of a single scanning. Single sided version, single copy version, and office size boards are options. May have a PC interface option. Database pricing reflects a mobile two-panel copy-board with a minimum 33" x 66" writing surface. Depth dimension refers to depth at the caster level of the supporting frame.
15 - SL001 - Lounge, Staff				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CB020	Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 38x24x13	2	CC	Wall hung cabinet with two adjustable shelves, solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a solid hinged single door case. For general purpose use throughout the facility.

NUTRITION AND FOOD SERVICE (224) - Contents - VA PG-18-5 (18 Jul 2016 04:58PM ET)

CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.
CT020	Countertop, Solid Surface	7	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.
F0225	Chair, Dining Room	4	VV	Dining room chair with glides. Chair has straight legs with cushioned cloth or vinyl seat.
F0795	Table, Dining	1	VV	Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons.
F2015	Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.
F3065	Whiteboard/Bulletin Board, Combination	1	VV	A combination whiteboard and bulletin board, half LCS and half cork. Available with either aluminum or wood frame. It can be used in patient rooms or in any appropriate space in the facility.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
K1552	Brewer, Coffee, Auto, Elect, 3 Burner, Front/Back	1	VV	Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.
K4665	Oven, Microwave, Consumer	1	VV	Counter mounted microwave oven for average duty use. The exterior cabinet can be metal or heavy duty impact resistant plastic. The oven delivers instant energy for rapid heating, defrosting or prime cooking. The oven has touch pad controls, digital timer, power level selector and preprogrammed selectors for commonly cooked items. This oven is commonly found in staff lounges.
M0515	Television, Plasma	1	VV	42" diagonal screen, high definition (HDTV) multimedia flat panel plasma display television. The TV will have a 16:9 wide screen aspect ratio, a minimum of 1024 x 768 display resolution, NTSC tuner, built-in stereo speakers and surround sound.
R7250	Refrigerator/Freezer, 20 Cubic Feet	1	VV	Refrigerator/freezer unit. This type unit includes a food saver system that helps keep food fresher. It also includes roll out wheels and is equipped for an optional automatic icemaker. This unit is of commercial or residential design and use.

16 - LR001 - Locker Room, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1030	Locker, 2 Person, Over/Under	4	VV	Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal belongings. Other width and depths are available.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.
17 - TLTU1 - Toilet, Staff				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.

P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

2 - MAIN KITCHEN RECEIVING AND STORAGE AREA

1 - MMRP1 - Receiving Area

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.

NUTRITION AND FOOD SERVICE (224) - Contents - VA PG-18-5 (18 Jul 2016 04:58PM ET)

F0775	Table, Work, 2 Drawer	1	VV	Work table approximately 32" high X 72" wide X 30" deep with two drawers and a hard wood top.
F2700	Reader, Bar Code, Hand Held, With Interface	1	VV	Hand held laser bar code reader with computer interface. Used for automated inventory, using bar code stickers/ labels. Convenience outlet required at point of use.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1840	Printer/Copier/Fax Combination	1	VV	Multifunctional printer, fax, scanner and copier (PFC) all-in-one machine.
M2020	Cabinet, Storage, Safety, Built-In, Vented	1	CC	Safety storage cabinet. This unit is of double steel wall construction, with vented grounding attachment, raised leak proof door sill, and adjustable shelving. Equipped with two doors and three-point key lock. The construction meets standards set by OSHA and NFPA Code 30 requirements. Designed for storage of flammable type liquids. The cabinet fits into a laboratory casework configuration and its ventilation ports are in the back to leave the counterspace free. The cabinet requires ventilation ducting and an exhaust fan as part of the HVAC (heating, ventilation and air conditioning) system.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	1	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
M2105	Pallet Lift, Hydraulic, Manual, 48" Pallet	1	VV	Hydraulic manual pallet equipped with floor lock and wheels for easy transport. Unit accommodates 48" pallets and is designed to handle all types of lifting tasks.
M2115	Truck, Hand, 2 Wheel	1	VV	2 wheel hand truck. Double handled with three supportive crossbars for heavy duty use. 800 pound weight capacity with two 8 or 10 inch wheels. For use in the warehouse.
M2125	Stacker, Straddle, 127" Lift, 2000 lb Capacity	1	VV	Straddle stacker. Battery powered with 2000 pound lifting capacity. Unit lifts to heights up to 127". Equipped with a extra heavy duty hydraulic system. Unit has a built-in automatic battery charger. Electrical requirements are for the charger. Designed for pallet lifting.
M2130	Truck, Hydraulic Lift, Electric	1	VV	Electric lift truck. Equipped with heavy duty hydraulic system and 12 V battery. For use within enclosed warehouse spaces. Adjustable 25" (approx) long forks. Complete with 10 amp charger. Counterweight must be used to help prevent tipping. NOTE: Not recommended for moving long distances or over uneven surfaces.

M7780	Scanner, Document	1	VV	Scanner for recording printed material in an electronic format. Some models process both color and black-and-white images. Options include automatic paper feeders and transparency adapters. Most models require connection to a microcomputer for independent operation or use as part of a network. Larger models for high use applications which connect directly to a network without passing information through a microcomputer are available.
-------	-------------------	---	----	---

2 - SRS01 - Storage, Non-Food

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	6	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

3 - SRS01 - Storage, Dry Food and Ingredient Control

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	6	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

4 - RER01 - Storage, Refrigerated and Frozen Food

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1000	Extinguisher, Fire	1	VV	10 pound dry chemical fire extinguisher with charging gauge. Other types and sizes are available.
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
M2070	Shelving, Storage, 77hx36wx18d	1	VV	Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room.

3 - MAIN KITCHEN FOOD PREPARATION AREA

1 - FSTD1 - Food Preparation and Production

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
-----	------	-----	---------	-------------

K1000	Cabinet, Pastry, Mobile, Medium	1	VV	Mobile pastry cabinet. The cabinet is made from aluminum or stainless steel, is mounted on four swivel casters and holds thirty 18 inch by 26 inch full sheet pans. The cabinet can be equipped with push handles and bumpers (which will change the exterior dimensions). Smaller capacity units are available. For larger capacity units see JSN K1010. The cabinet is used for storage and transport of pastries in hotels, restaurants, hospitals, and commercial food service operations.
K1010	Cabinet, Pastry, Mobile, Large	1	VV	Mobile pastry cabinet. This is a heavy duty, aluminum or stainless steel unit on four swivel casters which holds approximately forty 18 inch by 26 inch full sheet pans. The cabinet can be equipped with push handles and bumpers (which will change the exterior dimensions). See JSN K1000 for smaller capacity units. The cabinet is used for storage and transport of pastries in hotels, restaurants, hospitals, and commercial food service operations.
K1020	Cabinet, Heated, Food, Mobile, Large	1	VV	Insulated food warming cabinet. The cabinet is made of aluminum or stainless steel and is mounted on four heavy duty casters. The interior of the cabinet has slide ledges on both sides spaced at 1-1/2 inch intervals. The unit holds thirty or more 18 inch by 26 inch full size pans or trays. Double door and non-insulated cabinets are available, the second door reduces the tray capacity by one. The cabinet can be equipped with push handles and bumpers (which will change the exterior dimensions). The cabinet is used in commercial and hospital kitchens for food storage prior to serving.
K1030	Cabinet, Hot/Cold, Food, Mobile, Counter Height	1	VV	Half-height food holding cabinet (adjunct to cafeteria counter) which can heat stored food or keep it cold. The cabinet is made of corrosion resistant steel or a composite material and is fully insulated. It has a full length hinged door with lock, four lifting handles and channel type interior slides to hold seven or eight 12 inch wide, 20 inch long and 2-1/2 inch deep pans. The cabinet will also hold 4 inch and 6 inch deep pans. The cabinet has a heating unit, a cold holding plate or cooling unit and four 4 inch casters. For dual compartment cabinets, see JSN K6250. This unit is used to hold hot and cold food in commercial kitchens and hospitals.
K6250	Cabinet, Food, Heated, Mbl, 2 Compart, Counter Ht	1	VV	Mobile electric hot food warmer and server with dual side by side compartments, temperature and moisture controls, full insulation and casters. The unit holds sixteen 2-1/2" x 12" x 20" pans. Models are also available with heating wells on the top of the cabinet. The unit is used in food service operations for keeping hot food warm in the kitchen prior to serving.

2 - SRS01 - Storage, Refrigerated Blast-Chilled Food (Two-Day Food Bank)

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	6	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

3 - SRS01 - Storage, Refrigerated Blast-Chilled Food (One-Day Food Bank)				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	6	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
6 - FSNP1 - Nourishment Preparation				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
F2020	Can, Trash, 44 Gallon	1	VV	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).
K0800	Blender, Heavy Duty, 1 Gal, CRS Bowl	1	VV	Heavy duty blender. This is a one gallon blending device with a stainless steel container. It has a heavy duty motor with a 3 speed switch. The unit is used to blend foods in restaurants and hospital kitchens.
K0810	Blender, Heavy Duty, 1/2 Gal, CRS Bowl	1	VV	Heavy duty blender. This is a 64 ounce capacity blender with a stainless steel container. It has a four cutter, one piece stainless steel blade. The unit is used to blend foods in commercial restaurants, hotels and hospital kitchens.
K1910	Table, Work, Stainless Steel	1	VV	Work table approximately 36x120x30. The table is made of heavy duty stainless steel with all edges rolled down at 90 degrees. The edges are 2" high and have rounded corners. The table has stainless steel legs and a stainless steel under-shelf. The unit is used as a work station in large kitchens, hotels, restaurants and hospitals.
K2260	Dispenser, Milk Shake, 8 Gal	1	VV	Shake-maker dispenser. The dispenser is made of stainless steel and can serve eight gallons or more of milk shakes per hour in ambient room temperatures.
K4210	Mixer, Table Mounted, 5 Quart	1	VV	Tabletop mixer with a 5 quart capacity stainless steel bowl. The unit comes complete with beater and whip attachments. Other attachments are available. The unit is used to prepare food in hotels, restaurants and hospital food service areas.

K5550	Rack, Mobile, Refrigerator/Freezer/Transport	1	VV	Mobile food storage rack for use in food preservation and transport. The unit is made of stainless steel or aluminum, has four heavy duty recessed plate casters and matching pan ledges on the sides. The unit can be used in room temperature, freezer or refrigerated storage and can roll from one type of storage to another. The unit's sides are open or perforated to permit air circulation around the pans when used for refrigerated or freezer storage. Models come with varying types of and distances between the pan ledges. The unit must be able to pass through refrigerator and freezer doorways. The doorway dimensions of the refrigeration equipment selected will determine the size of the rack to procure.
K6260	Rack, Storage, Food, CRS	1	VV	Four (4) shelf open food storage rack approximately 61" H x 48" W x 15" D. The unit has heavy duty construction with solid 16 or 18 gauge CRS shelves and posts. Some manufacturers' models have galvanized steel shelves which are primed, polyurethane coated and baked to a hard finish. Wire, louvered, perforated and mobile shelving variations are available. The unit is used for open food storage in hospital kitchens.
K6300	Sink, Cook's, 1 Compartment	1	CC	Single compartment cook's sink. The sink bowl is 24" long x 24" wide x 14" deep. The sink meets specification MIL-S-19114 for a type I, style C unit. This sink has no drainboards.
K6800	Scale, Ingredient, Dial Or Digital	1	VV	Ingredient scale with a stainless steel platform and a dial or digital readout for controlling portion size or ingredient amount. The database electrical requirements are for a digital scale.
R1700	Freezer, 2 Section, CRS	1	VV	Freezer cabinet approximately 84x53x36. The unit is a two section, 46 cu. Ft. self contained freezer with adjustable shelves. The cabinet front and doors are constructed of heavy gauge polished stainless steel to maintain an attractive appearance. The unit is used in hospitals and commercial kitchen operations.
R7050	Refrigerator, 25 Cubic Feet	1	VV	General purpose refrigerator approximately 84x27x37. This unit is corrosion resistant stainless steel. It has a single self closing door with safety stops. This refrigerator is generally used in commercial kitchens, hospitals and schools.
R7300	Refrigerator/Freezer, 40 Cubic Feet	1	VV	Refrigerator/freezer. This unit has a stainless steel exterior with dual temperature controls. The unit is normally used in restaurants and hospitals, for storage of perishable items.

4 - MAIN KITCHEN PATIENT TRAY SERVICE AREA

1 - FSTD1 - Tray Assembly Area

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
K1000	Cabinet, Pastry, Mobile, Medium	1	VV	Mobile pastry cabinet. The cabinet is made from aluminum or stainless steel, is mounted on four swivel casters and holds thirty 18 inch by 26 inch full sheet pans. The cabinet can be equipped with push handles and bumpers (which will change the exterior dimensions). Smaller capacity units are available. For larger capacity units see JSN K1010. The cabinet is used for storage and transport of pastries in hotels, restaurants, hospitals, and commercial food service operations.

K1010	Cabinet, Pastry, Mobile, Large	1	VV	Mobile pastry cabinet. This is a heavy duty, aluminum or stainless steel unit on four swivel casters which holds approximately forty 18 inch by 26 inch full sheet pans. The cabinet can be equipped with push handles and bumpers (which will change the exterior dimensions). See JSN K1000 for smaller capacity units. The cabinet is used for storage and transport of pastries in hotels, restaurants, hospitals, and commercial food service operations.
K1020	Cabinet, Heated, Food, Mobile, Large	1	VV	Insulated food warming cabinet. The cabinet is made of aluminum or stainless steel and is mounted on four heavy duty casters. The interior of the cabinet has slide ledges on both sides spaced at 1-1/2 inch intervals. The unit holds thirty or more 18 inch by 26 inch full size pans or trays. Double door and non-insulated cabinets are available, the second door reduces the tray capacity by one. The cabinet can be equipped with push handles and bumpers (which will change the exterior dimensions). The cabinet is used in commercial and hospital kitchens for food storage prior to serving.
K1030	Cabinet, Hot/Cold, Food, Mobile, Counter Height	1	VV	Half-height food holding cabinet (adjunct to cafeteria counter) which can heat stored food or keep it cold. The cabinet is made of corrosion resistant steel or a composite material and is fully insulated. It has a full length hinged door with lock, four lifting handles and channel type interior slides to hold seven or eight 12 inch wide, 20 inch long and 2-1/2 inch deep pans. The cabinet will also hold 4 inch and 6 inch deep pans. The cabinet has a heating unit, a cold holding plate or cooling unit and four 4 inch casters. For dual compartment cabinets, see JSN K6250. This unit is used to hold hot and cold food in commercial kitchens and hospitals.
K6250	Cabinet, Food, Heated, Mbl, 2 Compart, Counter Ht	1	VV	Mobile electric hot food warmer and server with dual side by side compartments, temperature and moisture controls, full insulation and casters. The unit holds sixteen 2-1/2" x 12" x 20" pans. Models are also available with heating wells on the top of the cabinet. The unit is used in food service operations for keeping hot food warm in the kitchen prior to serving.

2 - FSCS1 - Tray Cart Storage Area, Clean Cart

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
K1350	Washer, Pressure, Mobile w/Sanitizer	1	VV	Pressure washer for cleaning and sanitizing kitchen or other areas. This is a mobile, motor operated unit with a spray gun. The washer sprays a detergent solution on each item to be cleaned and then rinses them using a combination of water and high pressure that blasts away the loosened dirt and grease. The washer can be either a stand alone unit or part of a set of stations operating from a central control. Refer to K9300 for a fixed version of this equipment. The unit is used for cleaning in commercial areas and institutions such as hospitals.
K2020	Dispenser, Detergent, Automatic	1	CC	Automatic detergent dispenser. Characteristics/components include supporting chemicals; detergent additive and rinse additive. This unit is used in conjunction with commercial dishwashers in hospitals and restaurants. Wall mounted unit, sized for the operation.
K3420	Hose, Retractable, Wall Mounted	1	CC	Retractable hose. The hose is wall mounted and has a stainless steel casing. The unit is used for washing and spraying down areas in commercial and institutional food service operations.

3 - SRR01 - Refrigerator, Tray Retherm Cart Holding				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
R8600	Refrigerator, Prefab, 320 Cubic Feet	1	CC	Prefabricated refrigerator, approximately 108x108x108. Unit is an architect planned, custom-sized, walk-in cooler. It has a side or ceiling mounted self-contained and easily serviced refrigeration system. Unit is used for bulk, indoor cold storage in commercial institutions and hospital kitchens. Size and shape may vary depending on site configuration.

4 - SRR01 - Refrigerator, Central Tray Retherm				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
R8600	Refrigerator, Prefab, 320 Cubic Feet	1	CC	Prefabricated refrigerator, approximately 108x108x108. Unit is an architect planned, custom-sized, walk-in cooler. It has a side or ceiling mounted self-contained and easily serviced refrigeration system. Unit is used for bulk, indoor cold storage in commercial institutions and hospital kitchens. Size and shape may vary depending on site configuration.

5 - SRR01 - Tray Retherm Cart System, Centralized				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
R8600	Refrigerator, Prefab, 320 Cubic Feet	1	CC	Prefabricated refrigerator, approximately 108x108x108. Unit is an architect planned, custom-sized, walk-in cooler. It has a side or ceiling mounted self-contained and easily serviced refrigeration system. Unit is used for bulk, indoor cold storage in commercial institutions and hospital kitchens. Size and shape may vary depending on site configuration.

6 - FSCS1 - Bulk Food Cart Holding Area, Cook / Serve				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
K1350	Washer, Pressure, Mobile w/Sanitizer	1	VV	Pressure washer for cleaning and sanitizing kitchen or other areas. This is a mobile, motor operated unit with a spray gun. The washer sprays a detergent solution on each item to be cleaned and then rinses them using a combination of water and high pressure that blasts away the loosened dirt and grease. The washer can be either a stand alone unit or part of a set of stations operating from a central control. Refer to K9300 for a fixed version of this equipment. The unit is used for cleaning in commercial areas and institutions such as hospitals.
K2020	Dispenser, Detergent, Automatic	1	CC	Automatic detergent dispenser. Characteristics/components include supporting chemicals; detergent additive and rinse additive. This unit is used in conjunction with commercial dishwashers in hospitals and restaurants. Wall mounted unit, sized for the operation.
K3420	Hose, Retractable, Wall Mounted	1	CC	Retractable hose. The hose is wall mounted and has a stainless steel casing. The unit is used for washing and spraying down areas in commercial and institutional food service operations.

5 - MAIN KITCHEN SANITATION AREA				
1 - FSDW1 - Dishwashing				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
F2020	Can, Trash, 44 Gallon	1	VV	Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash compactor at housekeeping).
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
K1695	Conveyor, Meal Tray Return	1	CC	Fixed conveyor for returning soiled meal trays from the main dining room to the tray processing area for cleaning. The database pricing is based on 24 feet of straight conveyor and 4 corner sections. This conveyor could lead to a second conveyor for tray processing or directly to a dishwasher with tray processing en route. Multiple power outlets will be required depending on the conveyors length.
K1800	Sink/Drainboard, Dishwashing, Triple Bowl	1	CC	Triple bowl dishwashing sink with two drainboard counters. The sink is made of 16 gauge stainless steel, has three 20" x 20" sink bowls, has supporting legs and/or wall attachment points and is pre-drilled for faucet and drain connections. Custom sized units are available. The database price includes the cost of welding the disposal cone to the bottom of one sink. See JSN K2620 for disposal units and JSN K9320 for accessory spray arms. The database height dimension is to the top of the backsplash; see the specification sheets for the sink rim height. Larger and smaller units are available as well as units with fewer sink bowls. This unit is used to wash dishes in institutions and commercial kitchens.
K2020	Dispenser, Detergent, Automatic	1	CC	Automatic detergent dispenser. Characteristics/components include supporting chemicals; detergent additive and rinse additive. This unit is used in conjunction with commercial dishwashers in hospitals and restaurants. Wall mounted unit, sized for the operation.

K2290	Dishwasher, Conveyor, Steam, 2 Tank	1	CC	<p>Automatic dishwasher which uses steam to heat the water in its two tanks. The unit is constructed of stainless steel and has a pre-wash, wash and rinse cycle. A 1/10 HP or larger electric motor powers the conveyor on which the dishracks ride. Three 1 HP or larger motors power the pre-wash, wash and rinse water circulating pumps. The unit collects and disposes of food dislodged from dishware, has curtains at each end and has large doors for inspection of the machine. The dishwasher's controls are mounted for ease of operator use. Optional blower/dryer units remove the last of the rinse water. Accessory condensing units may eliminate the need to vent the dishwasher to the atmosphere. Propane, natural gas and electrically heated models are also available. Because they vary widely from model to model, the dishwasher's final physical and utility configurations should be carefully reconciled with the facility drawings. The database height dimension reflects the clearance required to raise a machine door for servicing but not the clearance required beneath a ventilation hood. The machine listed in the database is each manufacturer's top line unit for the specified number of tanks.</p>
K2490	Dishwasher, Conveyor, Steam, 1 Tank	1	CC	<p>Automatic dishwasher which uses steam to heat the water in the single tank. The unit is constructed of stainless steel and has a pre-wash, wash and rinse cycle. A 1/10 HP or larger electric motor powers the conveyor on which the dishracks ride. Two 1/2 HP or larger motors power the pre-wash and wash water circulating pumps. The unit collects and disposes of food dislodged from dishware, has curtains at each end and has large doors for inspection of the machine. The dishwasher's controls are mounted for ease of operator use. Optional blower/dryers remove the last of the rinse water. Accessory condensing units may eliminate the need to vent the dishwasher to the atmosphere. Propane, natural gas and electrically heated models are also available. Because they can vary widely from model to model, the dishwasher's final physical and utility configurations should be carefully reconciled with the facility drawings. The database height dimension reflects the clearance required to raise a machine door for servicing but not the clearance required beneath a ventilation hood. The machine listed in the database is each manufacturers top line unit for the specified number of tanks.</p>
K2500	Dishwasher, Conveyor, Steam, 3 Tank	1	CC	<p>Automatic dishwasher which uses steam to heat the water in its 3 tanks. The unit is constructed of stainless steel and has a pre-wash, wash and rinse cycle. A 1/10 HP or larger electric motor powers the conveyor on which the dishracks ride. Three 1 HP or larger motors power the pre-wash, wash and rinse water circulating pumps. The unit collects and disposes of food dislodged from dishware, has curtains at each end and has large doors for inspection of the machine. The dishwashers controls are mounted for ease of operator use. Optional blower/dryer units remove the last of the rinse water. Accessory condensing units may eliminate the need to vent the dishwasher to the atmosphere. Propane, natural gas and electrically heated models are also available. The dishwasher's final physical and utility configuration should be carefully reconciled with the facility drawings. The database height dimension reflects the clearance required to raise a machine door for servicing but not the clearance required beneath a ventilation hood. The machine listed in the database is each manufacturers top line unit for the specified number of tanks.</p>

NUTRITION AND FOOD SERVICE (224) - Contents - VA PG-18-5 (18 Jul 2016 04:58PM ET)

K2620	Disposal, Waste, Heavy Duty	1	CC	Food waste disposal. The unit has a 10 HP heavy duty motor, a heavy cast alloy body, a 3 inch outlet and a cast-in deflector in upper chamber that force feeds waste down onto a 15" rotor. This unit is used for disposing large quantities of the heavy waste material generated in the central areas of commercial and institutional food service operations.
K3420	Hose, Retractable, Wall Mounted	1	CC	Retractable hose. The hose is wall mounted and has a stainless steel casing. The unit is used for washing and spraying down areas in commercial and institutional food service operations.
K6670	Sink, Soak, Mobile, 1 Compartment	1	VV	Mobile soak sink. This is a single compartment stainless steel unit. The sink legs are fitted with 4 or 5 inch swivel casters. Two casters have foot locking brakes. The unit is used in kitchens for soaking flatware and other kitchen items.
K8200	Rack, Wash, Pan/Utensil	1	VV	Pan and utensil wash rack. This unit can be a set of racks to accommodate a specific dishwashing unit. The racks are all stainless steel and can be used in large food service operations for cleaning pots and pans.
K9300	Washer, Pressure w/Sanitizer	1	VC	Pressure washer for cleaning and sanitizing kitchen or other areas. This is a wall mounted, motor operated unit with a spray gun. The washer sprays a detergent solution on each item to be cleaned and then rinses them using a combination of water and high pressure that blasts away the loosened dirt and grease. The washer can be either a stand alone unit or part of a set of stations operating from a central control. See JSN K1350 for the mobile version of this unit. The unit is used for cleaning in commercial areas and institutions such as hospitals.
K9320	Hose, Spray, Pre-Rinse	1	CC	Pre-rinse spray hose. The unit is a chrome plated wall or back deck mount design used to rinse dishes before racking in the dishwasher. It has a dual lever control which permits quick water temperature selection, large non-slip grip spray valve and spring loaded goose neck with storage hook.
K9450	Washer, Tray, Automatic Stacking, Electric	1	CC	Tray washer. This unit has eye thermometers, vacuum breaker, motor starter and standard overload protection mounted in a stainless steel enclosure. The unit features a remote stop button on the unloading side of the unit. The continuously moving belt has fingers or racks for easily mounting trays for cleaning. The database height dimension includes the clearance to open and remove a door panel. These washers vary widely in length and capacity; consult the manufacturer's specifications for the specific model. This washer can be found in food service operations of hotels, restaurants and hospitals.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.

2 - FSPW1 - Pot Washing

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
-----	------	-----	---------	-------------

K1800	Sink/Drainboard, Dishwashing, Triple Bowl	1	CC	Triple bowl dishwashing sink with two drainboard counters. The sink is made of 16 gauge stainless steel, has three 20" x 20" sink bowls, has supporting legs and/or wall attachment points and is pre-drilled for faucet and drain connections. Custom sized units are available. The database price includes the cost of welding the disposal cone to the bottom of one sink. See JSN K2620 for disposal units and JSN K9320 for accessory spray arms. The database height dimension is to the top of the backsplash; see the specification sheets for the sink rim height. Larger and smaller units are available as well as units with fewer sink bowls. This unit is used to wash dishes in institutions and commercial kitchens.
K1860	Sink, Pot, Triple Compartment, w/Drainboards	1	CC	Pot washing and scraping counter. This unit has three sink compartments and is constructed of stainless steel. The dimensions should be specified as required. See JSN K2620 for disposers and K9320 for pre-rinse hoses. Some models are built to accommodate two faucets. See related dishwashing and scullery triple compartment sinks at JSNs K1800 and K6660. This unit is used to wash pots in food service operations of hospitals, hotels and restaurants.
K2020	Dispenser, Detergent, Automatic	1	CC	Automatic detergent dispenser. Characteristics/components include supporting chemicals; detergent additive and rinse additive. This unit is used in conjunction with commercial dishwashers in hospitals and restaurants. Wall mounted unit, sized for the operation.
K2620	Disposal, Waste, Heavy Duty	1	CC	Food waste disposal. The unit has a 10 HP heavy duty motor, a heavy cast alloy body, a 3 inch outlet and a cast-in deflector in upper chamber that force feeds waste down onto a 15" rotor. This unit is used for disposing large quantities of the heavy waste material generated in the central areas of commercial and institutional food service operations.
K3420	Hose, Retractable, Wall Mounted	1	CC	Retractable hose. The hose is wall mounted and has a stainless steel casing. The unit is used for washing and spraying down areas in commercial and institutional food service operations.
K9300	Washer, Pressure w/Sanitizer	1	VC	Pressure washer for cleaning and sanitizing kitchen or other areas. This is a wall mounted, motor operated unit with a spray gun. The washer sprays a detergent solution on each item to be cleaned and then rinses them using a combination of water and high pressure that blasts away the loosened dirt and grease. The washer can be either a stand alone unit or part of a set of stations operating from a central control. See JSN K1350 for the mobile version of this unit. The unit is used for cleaning in commercial areas and institutions such as hospitals.
K9320	Hose, Spray, Pre-Rinse	1	CC	Pre-rinse spray hose. The unit is a chrome plated wall or back deck mount design used to rinse dishes before racking in the dishwasher. It has a dual lever control which permits quick water temperature selection, large non-slip grip spray valve and spring loaded goose neck with storage hook.
K9760	Washer, Pot/Pan, Electric	1	CC	Pot and pan washer. This unit's wash and rinse cycles pump water and cleaning solution under pressure through its upper and lower spray arms. The washer cleans pots, large preparation bowls and kitchen appliance parts. The unit drains after each cycle. The database information is for a straight pass through unit with an electric tank heater. Corner units and units with chemical or low temperature sterilization are available. The database physical specifications include the clearance needed to remove the unit's vertical doors and the extra footprint of exterior mounted control boxes and pipe connections. This unit is used in hospitals and large food service areas.

K9770	Washer, Pot/Pan, Steam And Electric	1	CC	Pot and pan washer with a steam heated tank. The washer is made of stainless steel and has a 5 HP wash pump motor, hot water spray rinse, sanitizing hot fresh water rinse, steam or electric water temperature booster, exhaust fan and basket screens. See K8200 for the washing racks for this machine.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
P2100	Disposal, Garbage, 2 HP Motor	1	CC	Garbage disposal. A two (2) horsepower versatile waste disposal unit suitable for facilities where 500 to 1000 meals are prepared and served daily. Requires eight (8) gallons per minute water flow rate, and outlet flange tapped for a two (2) inch pipe. Unit will have a manual reversing switch and shall comply with MIL SPEC No. MIL-G-15840. Multiple electrical configurations are available.

3 - FSCS1 - Cart Wash Area, Manual

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
K1350	Washer, Pressure, Mobile w/Sanitizer	1	VV	Pressure washer for cleaning and sanitizing kitchen or other areas. This is a mobile, motor operated unit with a spray gun. The washer sprays a detergent solution on each item to be cleaned and then rinses them using a combination of water and high pressure that blasts away the loosened dirt and grease. The washer can be either a stand alone unit or part of a set of stations operating from a central control. Refer to K9300 for a fixed version of this equipment. The unit is used for cleaning in commercial areas and institutions such as hospitals.
K2020	Dispenser, Detergent, Automatic	1	CC	Automatic detergent dispenser. Characteristics/components include supporting chemicals; detergent additive and rinse additive. This unit is used in conjunction with commercial dishwashers in hospitals and restaurants. Wall mounted unit, sized for the operation.
K3420	Hose, Retractable, Wall Mounted	1	CC	Retractable hose. The hose is wall mounted and has a stainless steel casing. The unit is used for washing and spraying down areas in commercial and institutional food service operations.

4 - FSCS1 - Cart Wash Area, Automated

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
K1350	Washer, Pressure, Mobile w/Sanitizer	1	VV	Pressure washer for cleaning and sanitizing kitchen or other areas. This is a mobile, motor operated unit with a spray gun. The washer sprays a detergent solution on each item to be cleaned and then rinses them using a combination of water and high pressure that blasts away the loosened dirt and grease. The washer can be either a stand alone unit or part of a set of stations operating from a central control. Refer to K9300 for a fixed version of this equipment. The unit is used for cleaning in commercial areas and institutions such as hospitals.
K2020	Dispenser, Detergent, Automatic	1	CC	Automatic detergent dispenser. Characteristics/components include supporting chemicals; detergent additive and rinse additive. This unit is used in conjunction with commercial dishwashers in hospitals and restaurants. Wall mounted unit, sized for the operation.

K3420	Hose, Retractable, Wall Mounted	1	CC	Retractable hose. The hose is wall mounted and has a stainless steel casing. The unit is used for washing and spraying down areas in commercial and institutional food service operations.
-------	---------------------------------	---	----	--

5 - FSCS1 - Tray Cart Storage Area, Soiled Carts

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
K1350	Washer, Pressure, Mobile w/Sanitizer	1	VV	Pressure washer for cleaning and sanitizing kitchen or other areas. This is a mobile, motor operated unit with a spray gun. The washer sprays a detergent solution on each item to be cleaned and then rinses them using a combination of water and high pressure that blasts away the loosened dirt and grease. The washer can be either a stand alone unit or part of a set of stations operating from a central control. Refer to K9300 for a fixed version of this equipment. The unit is used for cleaning in commercial areas and institutions such as hospitals.
K2020	Dispenser, Detergent, Automatic	1	CC	Automatic detergent dispenser. Characteristics/components include supporting chemicals; detergent additive and rinse additive. This unit is used in conjunction with commercial dishwashers in hospitals and restaurants. Wall mounted unit, sized for the operation.
K3420	Hose, Retractable, Wall Mounted	1	CC	Retractable hose. The hose is wall mounted and has a stainless steel casing. The unit is used for washing and spraying down areas in commercial and institutional food service operations.

6 - MAIN KITCHEN SUPPORT AREA

1 - JANC1 - Housekeeping Aides Closet (HAC)

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5135	Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd	1	CC	A surface mounted, satin finish stainless steel, utility shelf with a maximum of 6 mop/broom holders and 5 rag hooks. Utility shelf features: 8" deep shelf; mounting brackets welded to shelf; spring activated rubber cam holders; and drying rod. Unit is available in various widths 30" (minimum, 3 holders and 2 hooks) to 48" (maximum, 6 holders and 5 hooks). For use in janitor closets. Pricing based on a 36" width.
F0500	Cart, Janitor's	1	VV	Janitors cart, 38" high X 66" wide X 20" deep with 25 gallon heavy duty collection bag. Accommodations for locking vault and janitorial support items (broom, dust pan, chemicals, mop and mop bucket; not included).

NUTRITION AND FOOD SERVICE (224) - Contents - VA PG-18-5 (18 Jul 2016 04:58PM ET)

F0505	Bucket, Mop, With Wringer, 26 Quart	1	VV	Mobile mop bucket / wringer combination, approximately 35" H x 17" W x 22" D with four 2" casters. Total capacity is 26 quarts. Unit used for general hard surface floor maintenance.
P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P4700	Sink, Mop, Molded Stone	1	CC	Mop service sink approximately 10"H x 36"W x 24"D. Also called a mop service basin and a mop receptor. Unit is made of molded stone and is a one piece item. It shall include a service faucet hose, hose bracket and mop hanger. Used in utility rooms for cleaning mops and floor cleaning equipment.

2 - SRHM 1 - Storage, Hazardous Supplies

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
M2005	Cabinet, Storage, Acid, Floor Standing, Shelves	1	VV	Floor standing acid storage cabinet. A 30 gallon capacity standard two door cabinet with adjustable shelves, three-point latch with key-lock and 2" raised leak proof sill. An 18-gauge steel frame with vents, 1 1/2" airspace between walls and epoxy finish resistant to chemical attack. Note: Not for use with nitric and sulfuric acids.
M2015	Cabinet, Storage, Flammable, Freestanding	1	VV	Freestanding flammable safety storage cabinet. Size as required. Unit is of all welded steel wall construction with vented grounding attachments, raised leak proof door sill and adjustable shelving. Equipped with swinging doors and built-in key lock. Designed for storage of flammable fluids. Complies with OSHA standards, is FM approved and designed IAW NFPA 30.
M2070	Shelving, Storage, 77hx36wx18d	1	VV	Storage shelving unit approximately 77" H X 36" W X 18" D. Corrosion resistant baked enamel, galvanized or stainless steel open unit with adjustable shelves. The closed version is also available. For use in the storage room.
P5210	Shower, Safety, Freestanding, With Eye/Face Wash	1	CC	Deluge safety shower. This is a complete, maximum protection safety station consisting of a free-standing emergency shower and an eye/face wash fixture. Used anywhere exposure to hazardous substances may occur.

3 - UTC01 - Storage, Refrigerated Garbage

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.

F0530	Cart, Trash	1	VV	Heavy duty trash cart, approximately 42" high X 74" wide X 34" deep with two (2) solid non-marking rubber roller bearing wheels, one (1) or two (2) swivel casters, 2000 pound capacity and tilt mechanism.
F2026	Container, Recycling, Large	1	VV	Recycling container shall be approximately 30-gallons in capacity. The container may include a lid and be Recycle Blue in color with the recycle symbol identified on the container.

4 - JANC1 - Storage, Cleaning Supplies

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5135	Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd	1	CC	A surface mounted, satin finish stainless steel, utility shelf with a maximum of 6 mop/broom holders and 5 rag hooks. Utility shelf features: 8" deep shelf; mounting brackets welded to shelf; spring activated rubber cam holders; and drying rod. Unit is available in various widths 30" (minimum, 3 holders and 2 hooks) to 48" (maximum, 6 holders and 5 hooks). For use in janitor closets. Pricing based on a 36" width.
F0500	Cart, Janitor's	1	VV	Janitors cart, 38" high X 66" wide X 20" deep with 25 gallon heavy duty collection bag. Accommodations for locking vault and janitorial support items (broom, dust pan, chemicals, mop and mop bucket; not included).
F0505	Bucket, Mop, With Wringer, 26 Quart	1	VV	Mobile mop bucket / wringer combination, approximately 35" H x 17" W x 22" D with four 2" casters. Total capacity is 26 quarts. Unit used for general hard surface floor maintenance.
P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P4700	Sink, Mop, Molded Stone	1	CC	Mop service sink approximately 10"H x 36"W x 24"D. Also called a mop service basin and a mop receptor. Unit is made of molded stone and is a one piece item. It shall include a service faucet hose, hose bracket and mop hanger. Used in utility rooms for cleaning mops and floor cleaning equipment.

5 - UTC01 - Recycling / Holding Area				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
F0530	Cart, Trash	1	VV	Heavy duty trash cart, approximately 42" high X 74" wide X 34" deep with two (2) solid non-marking rubber roller bearing wheels, one (1) or two (2) swivel casters, 2000 pound capacity and tilt mechanism.
F2026	Container, Recycling, Large	1	VV	Recycling container shall be approximately 30-gallons in capacity. The container may include a lid and be Recycle Blue in color with the recycle symbol identified on the container.
6 - MECH1 - Mechanical Area				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1000	Extinguisher, Fire	1	VV	10 pound dry chemical fire extinguisher with charging gauge. Other types and sizes are available.
D4001	Compressor, Dental Air, System	2	CC	Dental air compressor system. Two or more equally sized compressors, with provisions for automatic, alternating and simultaneous operation shall be provided for dental air (DA). Each compressor is to be sized to operate at 65% duty cycle for maintenance of standard demand. Dental compressed air (DCA), 90 PSIG, is used for utility control in dental units, power for lifts, locks, rotary and other pneumatic dental instruments and equipment. DCA shall be oil-free air with the following air standards as maximums: Water - dry to a pressure dew point of 33 degrees F at not less than 90 PSIG; Condensed hydrocarbons - 0.1ppm by weight or 0.1 mg/L; Permanent particulates - 1.0 ppm by weight or 1.0 mg/L. Dental lab air (DLA), 30 PSIG, which is normally used for laboratory restorative and fabrication techniques may be combined with DCA. The system consists of, but not limited to, the following: compressor intake filters, compressors, after-coolers (air cooled), air receiver, pre-filter, dryer (refrigerated), after-filter. Pricing, electrical data and dimensions based upon 16-17 DTRs, each pump sized at approximately 17.5 cfm @ 100 PSIG. Other sizes and configurations are available to meet specified demands.