

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240)

1 - PATIENT SPECIMEN COLLECTION AREA

1 - WRC01 - Waiting

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5076	Dispenser, Hand Sanitizer, Free Standing	1	VV	A free standing hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.
F0206	Chair, Side, Bariatric, With Arms	1	VV	A bariatric side chair with arms for use in a waiting room, lobby or other patient area. Chair will have a padded seat and back and have a capacity of 800 pounds.
F0305	Chair, Waiting Room, Single	4	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2300	Rack, Magazine, Wall Mounted	1	VV	Wall mounted magazine rack with nine (9) magazine holding compartments.
F2310	Rack, Pamphlet, Wall Mounted	1	VV	Wall mounted pamphlet rack up to 12 (twelve) pamphlet holding pockets. Unit is used to store and display educational pamphlets.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0506	Television, Flat Screen	1	VV	Flat screen television with approximately 32" to 40' diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.

2 - RECP1 - Reception

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	2	VV	Telephone, desk, multiple line.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

A6105	Counter, Reception Control, Built-In	1	CC	Counter, control, inpatient, built-in. Consists of two 18" wide base cabinets with two drawers and file drawer, two 30" wide pencil drawers and two 18" wide base cabinet with four drawers. The countertop shall be a composition of wood particle core with plastic laminate surface having a hard smooth surface finish, standard thickness of 1" and a 4" butt backsplash/curb. Pricing based on a 30" depth.
F0275	Chair, Swivel, High Back	2	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	2	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2540	Shredder, Paper, Security	1	VV	Paper shredder, approximately 21" high X 15" wide X 12" deep with shredding unit and waste receptacle. Security features will include cross-cut shredding.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1840	Printer/Copier/Fax Combination	1	VV	Multifunctional printer, fax, scanner and copier (PFC) all-in-one machine.

3 - LBBD1 - Blood Specimen Collection Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

A5180	Track, Cubicle, Surface Mounted, With Curtain	1	VV	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
C04E0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C04F0	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
CE040	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.
CS140	Sink, SS, Single Compartment, 10x14x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CT030	Countertop, High Pressure Laminate	1	CC	High pressure laminate countertop (composition of wood particle core with plastic laminate surface) having a hard smooth surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a wide choice of colors, patterns, and depths. Used in general purpose areas requiring a basic work surface arrangement with limited heat resistance and poor chemical resistance. Pricing based upon a 24" depth.
E0948	Cart, General Storage, Mobile, 42"H x 32"W x 22"D	1	VV	THIS TYPICAL INCLUDES: 1 Cart Body, Style-A Narrow, w/Raised Edge Top 2 Drawers, 3" H 4 Drawers, 6" H 1 Accessory Rail, Side Drawer Organizer Bins
F2010	Basket, Wastepaper, Step-On	2	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

M1405	Chair, Blood Donor, Recliner, w/Motor, Armrest	1	VV	Donor chair, with motor and armrest. Contour chair with extra wide armrests, remote control, and power slide control.
M1450	Sealer, Electronic, Blood Bag	1	VV	Electronic blood bag sealer. Used for sealing blood-filled plastic tubing of blood collecting-dispensing bag.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.

4 - TLTU1 - Toilet, Urine Specimen Collection

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.

A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

2 - CORE LABORATORY WORK AREA

1 - LBBD2 - Specimen Accessioning, Processing and Distribution Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
C0025	Cabinet, Wardrobe, 1 Door, 84x24x22	1	CC	Wardrobe cabinet with a fixed shelf, clothing rod, and a solid or louvered right or left-hinged door (appropriate door hinge configuration to be indicated on the equipment elevation drawings), an optional locking door is available. Also referred to as a wardrobe case, unit or storage unit. Used for storage of clothing and personal items.
C0046	Frame, Apron, 2 Drawer, 4x48x22	1	CC	Apron frame with two standard drawers. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawers to support a top between base cabinets or a base cabinet and a wall.
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
C04E0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CE090	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 41x36x16	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.
CG040	Cabinet, W/H, 2 SH, 2 SGDO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass sliding doors, and sloping top. Also referred to as a framed-glass sliding double door wall case. For general purpose use throughout the facility.
CG090	Cabinet, W/H, 2 SH, 2 SGDO, Sloping Top, 41x36x16	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass sliding doors, and sloping top. Also referred to as a framed-glass sliding double door wall case. For general purpose use throughout the facility.
CS270	Sink, Epoxy Resin, 11x18x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backslash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
D3295	Chair, Rotary, Laboratory, Dental	1	VV	Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.
F3010	Board, Bulletin, 48 x 48	1	VV	Open face bulletin board. Cork posting panel with moisture proof backing. Variety of frames to choose from. Used for posting notes and messages.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
L1502	Centrifuge, Tabletop	1	VV	Tabletop laboratory centrifuge. This unit has a variable speed range of 1500 to 13000 RPM in part dependent on rotor assembly used. It includes a no brake option allowing rotor to spin to a gradual stop as well as the capability to enter combinations of time and RPM into the memory, and a door lock safety system. Heads accommodate a wide variety of tubes and can accommodate up to at least 76 tubes. Used in laboratories to prepare samples for further analysis.
L1670	Centrifuge, Refrigerated, Floor Model	1	VV	Refrigerated centrifuge. This is a floor standing unit with a solid state speed control system that has speeds ranging from approximately 150 to 6000 RPM. Other characteristics include a temperature range of -9 to +39 degrees C., dual range digital timer, rotor imbalance detection, a programmable memory and a dynamic brake with three deceleration rates. The unit also has a refrigeration system that consists of a low maintenance compressor and a coil wrapped insulated guard bowl. Used in laboratories for processing heat sensitive samples.
L2280	Hood, Laminar Flow, Horizontal, Free Standing, 6ft	1	CC	Horizontal laminar flow hood. This is a freestanding unit that meets or exceeds Class 100 requirements set for Federal Standard 209B. The unit will have HEPA filters, a washable and reusable pre-filter, a work surface and side walls of type 304 stainless steel construction, duplex electrical receptacles, high velocity return air slots that provide an air curtain at the work area, work surface and side walls and blowers with an average velocity of 100 fpm. Used for work with non-hazardous materials where clean particle free air is required. 6 foot model, other sizes available.
L2336	Cabinet, Bio Safety, Class II/B2, Bench Top, 4ft	1	CC	Class II, Type B2, benchtop biological safety cabinet. The unit includes two HEPA filters, one supply and one exhaust, zero probed, high intake velocity that averages 105 fpm, an audible alarm to notify operator of unsafe window positions an audio-visual alarm to monitor exhaust pressure, interior of type 304 stainless steel with side walls slotted for high velocity air return, an exterior of 16 gauge or heavier steel, two ground key petcocks, a grounded duplex receptacle. Used for low to moderate risk biological agents treated with toxic chemicals and radionuclotides. This unit requires 100% exhaust to the atmosphere. 4 foot model presented, other sizes are available.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M1855	Facsimile Machine	1	VV	Plain paper facsimile unit used to transmit printed matter or images over standard telephone lines. The unit operates at a modem speed of 33.6 Kbps and automatically recognizes and communicates with a variety of standard facsimile machines. Commonly referred to as "fax" unit.
M2015	Cabinet, Storage, Flammable, Freestanding	1	VV	Freestanding flammable safety storage cabinet. Size as required. Unit is of all welded steel wall construction with vented grounding attachments, raised leak proof door sill and adjustable shelving. Equipped with swinging doors and built-in key lock. Designed for storage of flammable fluids. Complies with OSHA standards, is FM approved and designed IAW NFPA 30.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	1	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
R4700	Ice Maker, Cubes, 250 Pound	1	CC	Ice cube maker approximately 39" H x 29" D x 26" W. This unit is self-contained and provides 250 pounds of ice every 24 hours. The exterior is made of sturdy stainless steel. It is used in hospitals, hotels, and restaurants for dispensing ice.
R5100	Freezer, Biological, -85, 19-25 Cubic Feet, Upright	1	VV	Biological freezer, -85 degrees centigrade, 19-25 cubic feet with temperature recorder, remote alarm, and storage baskets. Optional auxiliary water cooling available. Upright type freezer.
R6280	Refrigerator, Lab, SS, 2 Door, 6 Shelves	1	VV	Laboratory refrigerator approximately 83x56x33 in size. This unit will have double-doors; stainless steel interior; six stainless steel shelves that are fully adjustable to one-half centers; blower coil cooler with automatic off cycle defrost and a seven day precision temperature recording clock. This unit is used in hospitals and research laboratories for general cold storage.

3 - CLINICAL PATHOLOGY WORK AREA

1 - LMCH3 - Clinical Chemistry

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
C0025	Cabinet, Wardrobe, 1 Door, 84x24x22	1	CC	Wardrobe cabinet with a fixed shelf, clothing rod, and a solid or louvered right or left-hinged door (appropriate door hinge configuration to be indicated on the equipment elevation drawings), an optional locking door is available. Also referred to as a wardrobe case, unit or storage unit. Used for storage of clothing and personal items.
C0046	Frame, Apron, 2 Drawer, 4x48x22	1	CC	Apron frame with two standard drawers. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawers to support a top between base cabinets or a base cabinet and a wall.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS270	Sink, Epoxy Resin, 11x18x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.

D3295	Chair, Rotary, Laboratory, Dental	1	VV	Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.
E0042	Workcenter, Computer, Free Standing, 48" W	1	VV	THIS TYPICAL INCLUDES: 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray
E0721	Table, Process, Adj Height, 10 Drawer, 72"W x 36"D	1	VV	THIS TYPICAL INCLUDES: 1 Height Adjustable Table 4 Storage Frames 2 Drawers, 3"H; 6 Drawers, 6"H; 2 Drawers, 9"H; Drawer organizer bins
F2010	Basket, Wastepaper, Step-On	2	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F3010	Board, Bulletin, 48 x 48	1	VV	Open face bulletin board. Cork posting panel with moisture proof backing. Variety of frames to choose from. Used for posting notes and messages.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
L1030	Analyzer, Chemistry, Stat, High Capacity	1	VV	Stat chemistry analyzer, high capacity. The unit performs tests in 3-1/2 to 10 minutes. The test parameters are serum, urine and CSF. The unit performs at least 33 routine tests. The analyzer can process at least 63 samples at a time with a maximum analytical rate of at least 600 tests per hour. It is used for electrolytes, blood hematocrit and other routine chemistries.
L1035	Analyzer, Chemistry, Stat	1	VV	Stat chemistry analyzer. The unit performs tests in <10 minutes. The test parameters are serum, urine and CSF. The unit performs over 37 routine tests. The analyzer can process 100 samples at a time with a maximum analytical rate of 420 tests per hour. It is used for electrolytes, blood hematocrit and other routine chemistries.
L1080	Analyzer, Chemistry, Multichannel	2	VV	Laboratory chemistry analyzer. The unit is capable of at least 23 chemistries including electrolytes by ISE (ion-selective electrode). The analyzer can perform any combination of tests, panels or stats on a given sample. The unit has automatic QC and maintenance functions. The instrument is programmable for as many as 400 patient samples.
L1502	Centrifuge, Tabletop	2	VV	Tabletop laboratory centrifuge. This unit has a variable speed range of 1500 to 13000 RPM in part dependent on rotor assembly used. It includes a no brake option allowing rotor to spin to a gradual stop as well as the capability to enter combinations of time and RPM into the memory, and a door lock safety system. Heads accommodate a wide variety of tubes and can accommodate up to at least 76 tubes. Used in laboratories to prepare samples for further analysis.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

L1931	Analyzer, Blood Gas	1	VV	Blood/gas analyzer. The unit measures for pH, PO ₂ , and PCO ₂ using a standard sample of 90 microliters or greater. A measurement range of 6.4 to 8.0 for pH, 8 to 200mmHg for PCO ₂ and 0 to 800 mmHg for PO ₂ is accommodated by the unit. Used in laboratories to measure blood gas parameters of patient samples. System to provide for the measurement of: pH, pCO ₂ , pO ₂ , BP, tHb, NA+, K+, and CL-, or CA++. Calculated values to include: tCO ₂ , O ₂ Saturation, CT, HCO ₃ (actual and standardized), BE (vv and vt) and Hct.
L5610	Pipettor, Micro, 3 Range	1	VV	Micro-pipetting system. It is a sampler unit for precision pipetting of 1, 2, or 3 reagent volumes. It can accommodate different volume ranges from 25 micro-liter to 25 milliliters with dilution ratios up to 1:100.
L5630	Pipettor, 20-100 Micro Liter	1	VV	Pipettor. Unit operates with a plus or minus 0.5% reproducibility and precision. Used for repetitive deliveries of pre-set reagent volumes from chemicals to sterile solutions.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	3	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
R5100	Freezer, Biological, -85, 19-25 Cubic Feet, Upright	1	VV	Biological freezer, -85 degrees centigrade, 19-25 cubic feet with temperature recorder, remote alarm, and storage baskets. Optional auxiliary water cooling available. Upright type freezer.
R6280	Refrigerator, Lab, SS, 2 Door, 6 Shelves	1	VV	Laboratory refrigerator approximately 83x56x33 in size. This unit will have double-doors; stainless steel interior; six stainless steel shelves that are fully adjustable to one-half centers; blower coil cooler with automatic off cycle defrost and a seven day precision temperature recording clock. This unit is used in hospitals and research laboratories for general cold storage.

2 - LM CH4 - Chemistry, Special Chemistry

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
C0025	Cabinet, Wardrobe, 1 Door, 84x24x22	1	CC	Wardrobe cabinet with a fixed shelf, clothing rod, and a solid or louvered right or left-hinged door (appropriate door hinge configuration to be indicated on the equipment elevation drawings), an optional locking door is available. Also referred to as a wardrobe case, unit or storage unit. Used for storage of clothing and personal items.
C0039	Rail, Apron, 4x48x1	1	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.
C0046	Frame, Apron, 2 Drawer, 4x48x22	1	CC	Apron frame with two standard drawers. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawers to support a top between base cabinets or a base cabinet and a wall.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS260	Sink, Epoxy Resin, 10x25x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in suspended or U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CS270	Sink, Epoxy Resin, 11x18x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.

CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backslash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
D3295	Chair, Rotary, Laboratory, Dental	1	VV	Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.
E0042	Workcenter, Computer, Free Standing, 48" W	1	VV	THIS TYPICAL INCLUDES: 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray
E0703	Table, Process, Adj Height, 5 Drawer, 48"W x 24"D	1	VV	Height adjustable table. The table top is available in a plastic laminate or chemical resistant material (Chem-Surf). Casters or glides are options with some tables. All tables will accept various storage components underneath. These work surfaces are available in 24" or 30" depth. THIS TYPICAL INCLUDES: 1 height adjustable table; 1 storage frame; 3 drawers, 3"H; 1 drawer, 6"H; 1 drawer, 9"H and drawer organizer bins.
E0721	Table, Process, Adj Height, 10 Drawer, 72"W x 36"D	1	VV	THIS TYPICAL INCLUDES: 1 Height Adjustable Table 4 Storage Frames 2 Drawers, 3"H; 6 Drawers, 6"H; 2 Drawers, 9"H; Drawer organizer bins
F2000	Basket, Wastepaper, Round, Metal	6	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3010	Board, Bulletin, 48 x 48	1	VV	Open face bulletin board. Cork posting panel with moisture proof backing. Variety of frames to choose from. Used for posting notes and messages.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
L0205	E.I.A. Analysis System, Advanced	1	VV	Enzyme Immunoassay Analysis (E.I.A.) system for use in the clinical laboratory. System includes sample management center, dynamic incubator and parallel processing system.
L0210	E.I.A. Analysis System, Basic	1	VV	Basic Enzyme Immunoassay Analysis (E.I.A.) system for use in the clinical laboratory. System includes sample management center, analyzer module, and plate washing system.

L0211	E.I.A. Plate Washer System	1	VV	Enzyme Immunoassay Analysis (E. I. A.) plate washer system for use in the clinical laboratory.
L1005	Chromatograph, Gas, General	1	VV	General gas chromatograph. Unit can access all types of columns and has a dual module capability for combination of injection systems. It is equipped with automatic or manual sampling valves, programmable temperature vaporizer, six detectors to choose from, four independent heated zones, two signal outputs and memory protection for 24 hours. The gas chromatograph operates in the range of 10-40 degrees Centigrade with a 0-95% relative humidity. Used for packed or capillary column chromatography.
L1010	Chromatograph, Gas, Mass Spectrometer	1	VV	Gas Chromatograph with mass spectrometer. The unit provides single or simultaneous dual channel operation, a range of injector and detector combinations, a full color display unit and a visual comparison of samples internally or externally.
L1020	Chromatograph, Ion	1	VV	Ion chromatograph. Capabilities/components include automatic compensation for different carrier samples, multi-linear temperature programmability, 4 isothermal plateaus and injectors and detectors. It operates in the temperature range of 100-450 degrees C. The injection ports accept 1/8" and 1/4" columns and glass on-column. It has two auxiliary head zones and manual or automatic pneumatic controls.
L1120	Electrophoresis, General	1	VV	General purpose electrophoresis work center. All of the electrophoresis chambers, electrophoresis leads, incubator, drying oven, power supplies and staining dishes shall be combined into a single compact work center. The unit will have carbon graphite electrodes for better charge distribution, temperature control to 45 degrees C, and variable voltage settings from 50 to 300 Volts. It is used in research and diagnostic laboratories for various studies.
L1130	Densitometer, Scanning	1	VV	Scanning densitometer. This is a high capacity, fully automated unit. The unit can accommodate routine media, agarose film, cellulose acetate, TLC plates and fluorescence wavelengths. The carrier can accept media up to 150mm and run up to four tests and analyze 64 scans in 12 minutes. Used for electrophoresis scanning. System includes computer and printer.
L1160	Densitometer, Blood	1	VV	Blood densitometer. The characteristics include automatic computer capabilities, automatic calibration and scanning. The densitometer has a fluorescence lamp, two detectors, shall scan all standard media at a rate of 1 per 6 seconds and have a capacity of up to 30 fractions per sample. It can be used to handle both colorimetric and fluorometric procedures. Includes PC computer and printer.
L1502	Centrifuge, Tabletop	2	VV	Tabletop laboratory centrifuge. This unit has a variable speed range of 1500 to 13000 RPM in part dependent on rotor assembly used. It includes a no brake option allowing rotor to spin to a gradual stop as well as the capability to enter combinations of time and RPM into the memory, and a door lock safety system. Heads accommodate a wide variety of tubes and can accommodate up to at least 76 tubes. Used in laboratories to prepare samples for further analysis.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

L2255	Canopy, Hood, Exhaust Stack, Individual	1	CC	Canopy fumehood. The unit is fabricated from corrosion resistant steel or aluminum, dimensions as indicated on design drawings, fire suppression systems and any other special requirements to be defined during the facility design. This approximate 9 inch by 9 inch canopy hood provides for removal of the exhaust from the exhaust stack of an atomic absorption spectrophotometer or flame photometer used in clinical or research laboratory settings. Canopy attaches to a dedicated exhaust stack which is part of the building HVAC system. Device does not have any local motor/blower and flow rate is to be determined by the A&E's mechanical engineers.
L5610	Pipettor, Micro, 3 Range	1	VV	Micro-pipetting system. It is a sampler unit for precision pipetting of 1, 2, or 3 reagent volumes. It can accommodate different volume ranges from 25 micro-liter to 25 milliliters with dilution ratios up to 1:100.
L5630	Pipettor, 20-100 Micro Liter	1	VV	Pipettor. Unit operates with a plus or minus 0.5% reproducibility and precision. Used for repetitive deliveries of pre-set reagent volumes from chemicals to sterile solutions.
L7080	Spectrophotometer, Atomic Absorption, Computerized	1	VV	Double beam atomic absorption spectrophotometer. It is fully automatic, using cold vapor Hg and hydride generation sampling techniques. It's software is designed for use with a PC. It has a stable optical system with high energy wavelengths and high performance dual option system with stainless steel nebulizer.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	3	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	3	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
R5100	Freezer, Biological, -85, 19-25 Cubic Feet, Upright	1	VV	Biological freezer, -85 degrees centigrade, 19-25 cubic feet with temperature recorder, remote alarm, and storage baskets. Optional auxiliary water cooling available. Upright type freezer.
R6280	Refrigerator, Lab, SS, 2 Door, 6 Shelves	1	VV	Laboratory refrigerator approximately 83x56x33 in size. This unit will have double-doors; stainless steel interior; six stainless steel shelves that are fully adjustable to one-half centers; blower coil cooler with automatic off cycle defrost and a seven day precision temperature recording clock. This unit is used in hospitals and research laboratories for general cold storage.

3 - LBRI1 - Radioimmunoassay (RIA)				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
C0036	Rail, Apron, 4x30x1	1	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two steel base cabinets or a steel base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support. Constructed of steel.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS150	Sink, SS, Single Compartment, 10x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CS260	Sink, Epoxy Resin, 10x25x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in suspended or U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT050	Countertop, Stainless Steel	1	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
CW090	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 95" x 36"	1	CC	Floor standing storage cabinet approximately 95" H x 36" W x 16" D with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility.
E0584	Workstation Blood Bank/Serology Lab, Small	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Equip Rail, Wall-Mt, 48"W; 1 Clinical Panel, Open 80"H x 24"W; 2 Clinical Panel, Open 80"H x 30"W; 3 Clinical Panel, Open 80"H x 48"W; 1 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80"H x 48"W; 2 Clinical Panel, 48"H x 30"W; 1 Clinical Panel, 80"H x 48"W; 1 Light, 24"W; 5 Light 48"W; 2 Electric/Data Channel 48"W; 1 Electrical/Data Channel 72"W; 2 Electrical/Data Channel, Corner; 4 Cantilevered Work Surf, 30"D x 48"W; 1 Cantilevered Work Surf, 30"D x 72"W; 1 Height Adjustable Table, 30"D x 48"W; 3 Drw, 3"H; 3 Drw, 6"H; 1 Lockable Flipper Unit, 24"W; 4 Lockable Flipper Unit, 48"W; 3 Mobile Drawer Caddie with Drawers; 1 Adjustable Keyboard Tray; 4 Shelf, Storage/Display 48"W; 1 3-Shelf Unit with Door, 48"W; 1 Shelf, Storage/Display 24"W; 4 Extra Deep Shelf, 48"W; 1 Sink Base Cab, Dbl Doors, Backsplash, w/Corian Top 30"D x 48"W; 1 Swing-Away Eyewash; 1 SS Double Sink 19"D x 33"D; 1 Gooseneck Mixing Faucet ASSY. with Wristbands; 1 Strainer and Tailpiece; 1 Coat Hook; Drawer Organizer Bins. <p>* Connecting hardware required to complete installation.</p>
F0230	Chair, Drafting, Rotary	1	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
L1180	Dilutor, 1:25,000 Dilution	1	VV	Pipetter/Diluter. It has a sample volume of 20 micro liters and a diluent volume of 5 ml and is compatible with most caustic lab solutions such as HCL, H2SO4 glacial acetic acid, cholesterol reagent, total lipid reagent and a vast number of other corrosives. Each instrument is precisely calibrated to assure dilution accuracy and reproducibility with in 1%. The system also has a factory preset volume ration. The cycle light indicates when units are ready to sample or the dispense hand has a reagent draw-back feature that prevents sample reagent mixing inside the pipette after the dispensing cycle. This is a precise automatic instrument for sampling and dispensing. Used for hemoglobin determinations, and other required dilutions.
L1670	Centrifuge, Refrigerated, Floor Model	1	VV	Refrigerated centrifuge. This is a floor standing unit with a solid state speed control system that has speeds ranging from approximately 150 to 6000 RPM. Other characteristics include a temperature range of -9 to +39 degrees C., dual range digital timer, rotor imbalance detection, a programmable memory and a dynamic brake with three deceleration rates. The unit also has a refrigeration system that consists of a low maintenance compressor and a coil wrapped insulated guard bowl. Used in laboratories for processing heat sensitive samples.
L9835	Counter, Radioimmunoassay, Multichannel	1	VV	Multi-channel gamma counter. Unit shall be an automatic gamma counter capable of quantitating hormones, vitamins, drugs, cancer antigen, enzymes, receptors, viruses, antibodies, polypeptides and other proteins. Shall provide a sensitive and specific analytical technique for measuring these analytes in patient samples (Serum, Urine or other body fluids) with detection limits in the nanogram (ng) (10-9g) to picogram (10-12 g) range. Characteristics and components include personal computer data acquisition and analysis software, disk storage, constant quanta detector and dedicated computer.
L9836	Counter, Radioimmunoassay, Single Channel	1	VV	Single-channel gamma counter. Unit shall be an automatic gamma counter capable of quantitating hormones, vitamins, drugs, cancer antigen, enzymes, receptors, viruses, antibodies, polypeptides and other proteins. Shall provide a sensitive and specific analytical technique for measuring these analytes in patient samples (serum, urine or other body fluids) with detection limits in the nanogram (ng) (10-9g) to picogram (10-12 g) range. Characteristics and components include personal computer data acquisition and analysis software, disk storage, constant quanta detector and dedicated computer.
L9840	Counter, Gamma, RIA, Manual	1	VV	Gamma counter. Unit can be either a single well or a multi-well system that requires manual sample changing. It includes a NAI crystal detector. Uses RIA techniques to measure trace quantities of gamma radiation in substances such as hormones, drugs, enzymes, viruses, antibodies, tumor markers and receptors that are found in serum, urine and other body fluids.

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M1830	Printer, Label, Pharmacy	1	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
R6900	Refrigerator, Bio, Radio/Pharm, Approx. 5 CuFt	1	VV	Radiopharmaceutical and biological refrigerator with key-lock door. This unit is lead-lined with 1/8 inch lead on all sides for radiopharmaceuticals, biologicals and other radioactive materials. Freezer compartment and refrigerator eliminates thermal lag placement of cooling units inside the shielding. This unit is used as a storage unit in hospitals and laboratories that handle radioactive materials.
X9305	Cabinet, Storage, Lead Lined	2	VV	Lead lined storage cabinet. This unit is constructed of rigid steel walls with a 1/16" lead liner between each wall. The lead liner is formed into the cover so that when closed, positive x-ray protection is assured. Designed to hold cassettes up to the 14" X 17" size. This unit is used in nuclear medicine and radioisotope lab.

4 - LMU03 - Urine (Urinalysis) and Feces

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
C0046	Frame, Apron, 2 Drawer, 4x48x22	1	CC	Apron frame with two standard drawers. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawers to support a top between base cabinets or a base cabinet and a wall.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C04E0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CE090	Cabinet, W/H, 2 SH, 2 GDO, Sloping Top, 41x36x16	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass hinged doors, and sloping top. Also referred to as a framed-glass hinged double door wall case. For general purpose use throughout the facility.
CS270	Sink, Epoxy Resin, 11x18x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
D3295	Chair, Rotary, Laboratory, Dental	1	VV	Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.
E0703	Table, Process, Adj Height, 5 Drawer, 48"W x 24"D	1	VV	Height adjustable table. The table top is available in a plastic laminate or chemical resistant material (Chem-Surf). Casters or glides are options with some tables. All tables will accept various storage components underneath. These work surfaces are available in 24" or 30" depth. THIS TYPICAL INCLUDES: 1 height adjustable table; 1 storage frame; 3 drawers, 3"H; 1 drawer, 6"H; 1 drawer, 9"H and drawer organizer bins.
F3010	Board, Bulletin, 48 x 48	1	VV	Open face bulletin board. Cork posting panel with moisture proof backing. Variety of frames to choose from. Used for posting notes and messages.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

L0100	Microscope, Binocular	1	VV	Binocular microscope. Equipped with plan achromatic objectives to suit work in brightfield, phase contrast, darkfield, photomicrography, dual viewing and projection screen. Microscope has a high light intensity, 100 watt halogen lamp, for constant color temperature and illumination, a three step variable transformer, focusable aspheric abbe condenser system; heat absorbing glass; centerable field diaphragm; two built-in filter turrets permitting a combination of selective light balancing and color compensating filters. Other components/features include a swing-in condenser, 4X objective, quadruple nosepiece, 10X wide field eyepieces and a graduated stage. Other observation tubes can be added. It is used in laboratories for cell counting and other observation techniques.
L0145	Microscope, Teaching, Multiple Head	1	VV	Multiple head teaching microscope. Designed to accommodate from two to six viewers simultaneously, providing each observer an identical image of the specimen with exact orientation and intensity of the image. Magnification ranges from 4X to 100X and there is a five-place nosepiece with knurled-edge gripping surface for easy rotation. The microscope accepts 32 or 45mm filters and has other accessories available for various configurations.
L0990	Analyzer, Urine, Basic	1	VV	Basic urine analysis system. Automated system provides 8 chemistries. Unit requires only power connection. This unit is a benchtop instrument.
L0995	Analyzer, Urine, Advanced	1	VV	Advanced urine analysis system. Automated system provides chemistry and image analysis of a batch of urine samples. Unit requires only power and a drain connection.
L1182	Refractometer	1	VV	Refractometer. Characteristics/ components include an accommodation of liquids, solids, solids-in-liquids and powders, temperature measured at interface of samples, photosensors measurement, automatic calibration, multi-channel programming, an accuracy of +/- .0001 refractive unit and automatic temperature compensation. Used for glucose and urine refractive indexes.
L1190	Osmometer	1	VV	Osmometer. Characteristics/components include semi-automatic operation, measurement of osmolality of 0.2ml samples, accuracy to (+/-) 0.5%, temperature controlled liquid freezing bath, flow-through cell assembly and high speed testing capability. Used to determine precise concentration of solute particles for urines, urea, free water clearances, electrolyte studies, serum and other applications.
L1300	Centrifuge, Small, Blood Typing, Variable Speed	1	VV	Small laboratory centrifuge with variable speed allowing both regular and delicate centrifugation. It has a brake to allow a complete stop in 10 seconds, 0 to 30 minute timer, interchangeable heads and can accommodate up to 24 tubes. Used for blood grouping and cross matching.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.

M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
R6070	Refrigerator/Freezer, Biological, Upright, 18 Cu Ft	1	VV	Biological refrigerator with freezer. This unit includes a freezer compartment for general laboratory use. Its independent direct-set temperature controllers allow temperature selection for +2° to 14°C for the refrigerator, and from -20° to -30°C for the freezer.

5 - LMHI3 - Hematology, Routine Laboratory

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
D3295	Chair, Rotary, Laboratory, Dental	1	VV	Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.
E0703	Table, Process, Adj Height, 5 Drawer, 48"W x 24"D	1	VV	Height adjustable table. The table top is available in a plastic laminate or chemical resistant material (Chem-Surf). Casters or glides are options with some tables. All tables will accept various storage components underneath. These work surfaces are available in 24" or 30" depth. THIS TYPICAL INCLUDES: 1 height adjustable table; 1 storage frame; 3 drawers, 3"H; 1 drawer, 6"H; 1 drawer, 9"H and drawer organizer bins.
L1085	Analyzer, Coagulation, Automatic	2	VV	Automatic coagulation analyzer. The unit performs on-site blood coagulation tests, prothrombin time (PT), and partial thromboplastin time (PTT) tests on whole blood or plasma samples. The analyzer employs both single and duplicating or stat testing capabilities.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
R5100	Freezer, Biological, -85, 19-25 Cubic Feet, Upright	1	VV	Biological freezer, -85 degrees centigrade, 19-25 cubic feet with temperature recorder, remote alarm, and storage baskets. Optional auxiliary water cooling available. Upright type freezer.

R6280	Refrigerator, Lab, SS, 2 Door, 6 Shelves	1	VV	Laboratory refrigerator approximately 83x56x33 in size. This unit will have double-doors; stainless steel interior; six stainless steel shelves that are fully adjustable to one-half centers; blower coil cooler with automatic off cycle defrost and a seven day precision temperature recording clock. This unit is used in hospitals and research laboratories for general cold storage.
6 - LMHI3 - Hematology, Coagulation Laboratory				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
D3295	Chair, Rotary, Laboratory, Dental	1	VV	Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.
E0703	Table, Process, Adj Height, 5 Drawer, 48"W x 24"D	1	VV	Height adjustable table. The table top is available in a plastic laminate or chemical resistant material (Chem-Surf). Casters or glides are options with some tables. All tables will accept various storage components underneath. These work surfaces are available in 24" or 30" depth. THIS TYPICAL INCLUDES: 1 height adjustable table; 1 storage frame; 3 drawers, 3"H; 1 drawer, 6"H; 1 drawer, 9"H and drawer organizer bins.
L1085	Analyzer, Coagulation, Automatic	2	VV	Automatic coagulation analyzer. The unit performs on-site blood coagulation tests, prothrombin time (PT), and partial thromboplastin time (PTT) tests on whole blood or plasma samples. The analyzer employs both single and duplicating or stat testing capabilities.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
R5100	Freezer, Biological, -85, 19-25 Cubic Feet, Upright	1	VV	Biological freezer, -85 degrees centigrade, 19-25 cubic feet with temperature recorder, remote alarm, and storage baskets. Optional auxiliary water cooling available. Upright type freezer.
R6280	Refrigerator, Lab, SS, 2 Door, 6 Shelves	1	VV	Laboratory refrigerator approximately 83x56x33 in size. This unit will have double-doors; stainless steel interior; six stainless steel shelves that are fully adjustable to one-half centers; blower coil cooler with automatic off cycle defrost and a seven day precision temperature recording clock. This unit is used in hospitals and research laboratories for general cold storage.

7 - LM BB2 - Blood Bank, Blood Product Storage, Testing and Issuance (Transfusion S)				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
C0025	Cabinet, Wardrobe, 1 Door, 84x24x22	1	CC	Wardrobe cabinet with a fixed shelf, clothing rod, and a solid or louvered right or left-hinged door (appropriate door hinge configuration to be indicated on the equipment elevation drawings), an optional locking door is available. Also referred to as a wardrobe case, unit or storage unit. Used for storage of clothing and personal items.
C0043	Frame, Apron, 1 Drawer, 4x24x22	1	CC	Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall.
C0046	Frame, Apron, 2 Drawer, 4x48x22	1	CC	Apron frame with two standard drawers. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawers to support a top between base cabinets or a base cabinet and a wall.
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS270	Sink, Epoxy Resin, 11x18x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
D3295	Chair, Rotary, Laboratory, Dental	1	VV	Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

E0042	Workcenter, Computer, Free Standing, 48" W	1	VV	<p>THISTYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray
E0703	Table, Process, Adj Height, 5 Drawer, 48"W x 24"D	1	VV	<p>Height adjustable table. The table top is available in a plastic laminate or chemical resistant material (Chem-Surf). Casters or glides are options with some tables. All tables will accept various storage components underneath. These work surfaces are available in 24" or 30" depth. THISTYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 height adjustable table; 1 storage frame; 3 drawers, 3"H; 1 drawer, 6"H; 1 drawer, 9"H <p>and drawer organizer bins.</p>
E0721	Table, Process, Adj Height, 10 Drawer, 72"W x 36"D	1	VV	<p>THISTYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 1 Height Adjustable Table 4 Storage Frames 2 Drawers, 3"H; 6 Drawers, 6"H; 2 Drawers, 9"H; <p>Drawer organizer bins</p>
F0120	Bookcase, Executive, 3 Shelf, Wood	1	VV	<p>Freestanding open shelf woodgrain bookcase, approximately 48" high X 36" wide X 13" deep with three (3) adjustable shelves and four (4) non-marking floor glides.</p>
F0235	Chair, Executive, Side	1	VV	<p>Executive side chair, 35" high x 26" wide x 27" deep with cushioned seat, back and arms. Straight leg or sled base available.</p>
F0240	Chair, Executive, Swivel	1	VV	<p>Executive swivel chair, 39" high X 26" wide X 26" deep with arms, a five (5) caster base and tilt mechanism. Seat and back have foam rubber cushions. Upholstery may be either woven fabric or vinyl.</p>
F0405	Cabinet, Filing, Full Height, 4-5 Drawer	1	VV	<p>Four (4) or five (5) drawer letter size, vertical filing cabinet, 53" high X 15" wide X 29" deep with locking device. Each drawer has label holder, handle and roller cradle.</p>
F0415	Cabinet, Filing, Lateral, Full Height, 5 Drawer	1	VV	<p>Full height five (5) drawer lateral filing cabinet, 65" high X 42" wide X 18" deep with floor levelers (front), locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.</p>
F0635	Desk, Double Pedestal	1	VV	<p>Double pedestal flat top desk, 30" high X 60" wide X 30" deep with center pencil drawer, choices of combinations of file and box drawers, floor glides and modesty panel.</p>
F0695	Workstation, Computer, Open	1	VV	<p>Computer operator workstation, 55" high X 60" wide X 27" deep with large work surface and one (1) 17" high X 48" wide X 16" deep hutch. Desk has one (1) pull-out keyboard shelf. Hutch has adjustable open shelves.</p>
F0705	Table, Computer, Small	1	VV	<p>Small sized computer table/workstation, approximately 35" high X 36" wide X 30" deep with enough surface for a CPU, monitor and keyboard.</p>

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F2520	Imprinter, Clock, Day / Date / Time	1	VV	Day / date / time clock imprinter, approximately 5" high X 3" wide X 2" deep.
F2540	Shredder, Paper, Security	1	VV	Paper shredder, approximately 21" high X 15" wide X 12" deep with shredding unit and waste receptacle. Security features will include cross-cut shredding.
F3010	Board, Bulletin, 48 x 48	1	VV	Open face bulletin board. Cork posting panel with moisture proof backing. Variety of frames to choose from. Used for posting notes and messages.
F3030	Board, Scheduling, Magnetic	1	VV	Magnetic scheduling board, 36" X 48". Porcelain enamel magnetic surface. Used for letter transferring while posting messages or scheduling. For use with marker pens.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
L0100	Microscope, Binocular	1	VV	Binocular microscope. Equipped with plan achromatic objectives to suit work in brightfield, phase contrast, darkfield, photomicrography, dual viewing and projection screen. Microscope has a high light intensity, 100 watt halogen lamp, for constant color temperature and illumination, a three step variable transformer, focusable aspheric abbe condenser system; heat absorbing glass; centerable field diaphragm; two built-in filter turrets permitting a combination of selective light balancing and color compensating filters. Other components/features include a swing-in condenser, 4X objective, quadruple nosepiece, 10X wide field eyepieces and a graduated stage. Other observation tubes can be added. It is used in laboratories for cell counting and other observation techniques.
L1300	Centrifuge, Small, Blood Typing, Variable Speed	1	VV	Small laboratory centrifuge with variable speed allowing both regular and delicate centrifugation. It has a brake to allow a complete stop in 10 seconds, 0 to 30 minute timer, interchangeable heads and can accommodate up to 24 tubes. Used for blood grouping and cross matching.
L1502	Centrifuge, Tabletop	1	VV	Tabletop laboratory centrifuge. This unit has a variable speed range of 1500 to 13000 RPM in part dependent on rotor assembly used. It includes a no brake option allowing rotor to spin to a gradual stop as well as the capability to enter combinations of time and RPM into the memory, and a door lock safety system. Heads accommodate a wide variety of tubes and can accommodate up to at least 76 tubes. Used in laboratories to prepare samples for further analysis.
L1660	Cell Washer/Centrifuge	1	VV	Combination cell washer and centrifuge. The unit has two fixed speeds of 3600 or 12000 RPM. It is a microprocessor controlled unit with a programmable memory that can hold up to four wash cycles. It has a built-in peristaltic pump with a drain, dual angle rotor, low saline level alarm and uses 10 X 75mm or 12 X 75mm tubes. Used for compatibility testing, cytological studies and other laboratory applications.
L8005	Incubator, Blood Bank, Tabletop	1	VV	The incubator is used to perform crossmatches, indirect Coombs test, Rh titers, Du tests. It maintains through the use of dry heat blocks a constant temperature of 37degrees centigrade with an accuracy within + or - .5 degrees centigrade. It accommodates up to 40 tubes with diameters of 12mm. It is designed to be placed on a table top and is approximately 5" x 9" x 3".

M1405	Chair, Blood Donor, Recliner, w/Motor, Armrest	1	VV	Donor chair, with motor and armrest. Contour chair with extra wide armrests, remote control, and power slide control.
M1450	Sealer, Electronic, Blood Bag	1	VV	Electronic blood bag sealer. Used for sealing blood-filled plastic tubing of blood collecting-dispensing bag.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	1	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
R4700	Ice Maker, Cubes, 250 Pound	1	CC	Ice cube maker approximately 39" H x 29" D x 26" W. This unit is self-contained and provides 250 pounds of ice every 24 hours. The exterior is made of sturdy stainless steel. It is used in hospitals, hotels, and restaurants for dispensing ice.
R5110	Freezer, Rapid, Blood/Plasma, 4 Cubic Feet	1	VV	Rapid freezer for blood products and plasma. This unit uses a liquid cooling medium for rapid heat reduction and consistent freezing rate. The unit is insulated with a minimum of 3 1/2" of poured in place urethane insulation. Refrigeration system is an air cooled or water cooled compressor system. This unit may be a chest or upright type freezer. Also know as a blast freezer.
R6010	Refrigerator, Blood Bank, Glass Do, Dr, 25 Cu Ft	1	VV	Blood bank refrigerator. This unit has a single glass door, pull-out drawer, 7 day recording thermometer, high/low alarm system, battery-powered power failure alarm and remote alarm. The unit is used for storage of blood as required by AABB, ANRC and FDA for whole blood.
R6200	Refrigerator, U/C or F/S, 5 Cu Ft	1	VV	Utility refrigerator approximately 35" H x 24" W x 26" D. The unit has a two tray ice cube cooling system. The refrigerator fits standard architectural dimensions for undercounter installation. The unit is perfect for use in nurses' station, wards, and laboratories, pharmacies or wherever space is limited.

8 - LMBB3 - Blood Bank, Blood Product Preparation / Modification

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
E0721	Table, Process, Adj Height, 10 Drawer, 72"W x 36"D	1	VV	THIS TYPICAL INCLUDES: 1 Height Adjustable Table 4 Storage Frames 2 Drawers, 3"H; 6 Drawers, 6"H; 2 Drawers, 9"H; Drawer organizer bins
L1090	Cell Washer, Frozen Blood Deglycerolizer	1	VV	Automated cell washer designed to deglycerolize frozen packed red cells. Used in the blood bank and at frozen blood depots to prepare frozen cells for administration to patients.
L1112	Welder, PVC Blood Tubing, Sterile Process	1	VV	PVC blood tubing welder used to provide custom, sterile connections for blood collection units and for determination of apheresis collection units.
L2575	Incubator, Platelet, Freestanding, w/Rotator	1	VV	Freestanding platelet incubator. Unit is equipped with a rotator. The unit can be a single or dual capacity unit and can hold platelet rotators and agitators for continual mixing at 22 degrees centigrade. It has forced air circulation to maintain a uniform temperature throughout the incubator, a temperature range of 15-40 degrees centigrade, an alarm system for temperature deviations or power failure and a rotation speed of 6 rpm to maintain the viability of platelet concentrations.
M1210	Balance, Electronic, Laboratory/Pharmacy	1	VV	Electronic balance with high fluorescent display, built-in auto tracking and tape. Unit has a programmable selection for weight range and automatic calibration. Intended for use in the laboratory or pharmacy. Unit's weight limitation will be no less than 4000 grams.
R5120	Freezer, Blood/Platelet, Upright, -85C, 20-30 Cu Ft	1	VV	Whole blood freezer. This unit has 7 day recording thermometer, high/low alarms, battery powered power failure alarm and remote alarm. The upright unit is used to store blood and blood products. Includes operating temperature set points and is adjustable in 1°C increments from -40°C to -85°C. This unit is used in laboratories and hospital facilities for blood and blood products storage.
R6010	Refrigerator, Blood Bank, Glass Do, Dr, 25 Cu Ft	1	VV	Blood bank refrigerator. This unit has a single glass door, pull-out drawer, 7 day recording thermometer, high/low alarm system, battery-powered power failure alarm and remote alarm. The unit is used for storage of blood as required by AABB, ANRC and FDA for whole blood.

9 - LM BB1 - Blood Bank, Hemotherapeutics Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.

C0025	Cabinet, Wardrobe, 1 Door, 84x24x22	1	CC	Wardrobe cabinet with a fixed shelf, clothing rod, and a solid or louvered right or left-hinged door (appropriate door hinge configuration to be indicated on the equipment elevation drawings), an optional locking door is available. Also referred to as a wardrobe case, unit or storage unit. Used for storage of clothing and personal items.
C0043	Frame, Apron, 1 Drawer, 4x24x22	1	CC	Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS270	Sink, Epoxy Resin, 11x18x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
D3295	Chair, Rotary, Laboratory, Dental	1	VV	Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.
E0721	Table, Process, Adj Height, 10 Drawer, 72"W x 36"D	1	VV	THIS TYPICAL INCLUDES: 1 Height Adjustable Table 4 Storage Frames 2 Drawers, 3"H; 6 Drawers, 6"H; 2 Drawers, 9"H; Drawer organizer bins
F0695	Workstation, Computer, Open	1	VV	Computer operator workstation, 55" high X 60" wide X 27" deep with large work surface and one (1) 17" high X 48" wide X 16" deep hutch. Desk has one (1) pull-out keyboard shelf. Hutch has adjustable open shelves.
F3010	Board, Bulletin, 48 x 48	1	VV	Open face bulletin board. Cork posting panel with moisture proof backing. Variety of frames to choose from. Used for posting notes and messages.
L1110	Pheresis Unit	1	VV	Cyto/plasma pheresis unit. The unit processes blood withdrawn from a donor and separates and retains leukocytes and/or plasma and retransfuses the remainder to the donor. It processes the cells through a centrifugal action that allows separation of the components.
M1405	Chair, Blood Donor, Recliner, w/Motor, Armrest	1	VV	Donor chair, with motor and armrest. Contour chair with extra wide armrests, remote control, and power slide control.

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	1	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
R6200	Refrigerator, U/C or F/S, 5 Cu Ft	1	VV	Utility refrigerator approximately 35" H x 24" W x 26" D. The unit has a two tray ice cube cooling system. The refrigerator fits standard architectural dimensions for undercounter installation. The unit is perfect for use in nurses' station, wards, and laboratories, pharmacies or wherever space is limited.

10 - LM BB2 - Blood Bank, Donor Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
C0025	Cabinet, Wardrobe, 1 Door, 84x24x22	1	CC	Wardrobe cabinet with a fixed shelf, clothing rod, and a solid or louvered right or left-hinged door (appropriate door hinge configuration to be indicated on the equipment elevation drawings), an optional locking door is available. Also referred to as a wardrobe case, unit or storage unit. Used for storage of clothing and personal items.

C0043	Frame, Apron, 1 Drawer, 4x24x22	1	CC	Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall.
C0046	Frame, Apron, 2 Drawer, 4x48x22	1	CC	Apron frame with two standard drawers. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawers to support a top between base cabinets or a base cabinet and a wall.
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CS270	Sink, Epoxy Resin, 11x18x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
D3295	Chair, Rotary, Laboratory, Dental	1	VV	Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.
E0042	Workcenter, Computer, Free Standing, 48" W	1	VV	THIS TYPICAL INCLUDES: 1 Tool Rail 2 Paper Tray 1 Diagonal Tray 1 Freestanding Work Surface 1 Mobile Pedestal, Box/File 1 Adjustable Keyboard Tray

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

E0703	Table, Process, Adj Height, 5 Drawer, 48"W x 24"D	1	VV	Height adjustable table. The table top is available in a plastic laminate or chemical resistant material (Chem-Surf). Casters or glides are options with some tables. All tables will accept various storage components underneath. These work surfaces are available in 24" or 30" depth. THISTYPICAL INCLUDES: 1 height adjustable table; 1 storage frame; 3 drawers, 3"H; 1 drawer, 6"H; 1 drawer, 9"H and drawer organizer bins.
E0721	Table, Process, Adj Height, 10 Drawer, 72"W x 36"D	1	VV	THISTYPICAL INCLUDES: 1 Height Adjustable Table 4 Storage Frames 2 Drawers, 3"H; 6 Drawers, 6"H; 2 Drawers, 9"H; Drawer organizer bins
F0120	Bookcase, Executive, 3 Shelf, Wood	1	VV	Freestanding open shelf woodgrain bookcase, approximately 48" high X 36" wide X 13" deep with three (3) adjustable shelves and four (4) non-marking floor glides.
F0235	Chair, Executive, Side	1	VV	Executive side chair, 35" high x 26" wide x 27" deep with cushioned seat, back and arms. Straight leg or sled base available.
F0240	Chair, Executive, Swivel	1	VV	Executive swivel chair, 39" high X 26" wide X 26" deep with arms, a five (5) caster base and tilt mechanism. Seat and back have foam rubber cushions. Upholstery may be either woven fabric or vinyl.
F0405	Cabinet, Filing, Full Height, 4-5 Drawer	1	VV	Four (4) or five (5) drawer letter size, vertical filing cabinet, 53" high X 15" wide X 29" deep with locking device. Each drawer has label holder, handle and roller cradle.
F0415	Cabinet, Filing, Lateral, Full Height, 5 Drawer	1	VV	Full height five (5) drawer lateral filing cabinet, 65" high X 42" wide X 18" deep with floor levelers (front), locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F0635	Desk, Double Pedestal	1	VV	Double pedestal flat top desk, 30" high X 60" wide X 30" deep with center pencil drawer, choices of combinations of file and box drawers, floor glides and modesty panel.
F0695	Workstation, Computer, Open	1	VV	Computer operator workstation, 55" high X 60" wide X 27" deep with large work surface and one (1) 17" high X 48" wide X 16" deep hutch. Desk has one (1) pull-out keyboard shelf. Hutch has adjustable open shelves.
F0705	Table, Computer, Small	1	VV	Small sized computer table/workstation, approximately 35" high X 36" wide X 30" deep with enough surface for a CPU, monitor and keyboard.
F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F2520	Imprinter, Clock, Day / Date / Time	1	VV	Day / date / time clock imprinter, approximately 5" high X 3" wide X 2" deep.
F2540	Shredder, Paper, Security	1	VV	Paper shredder, approximately 21" high X 15" wide X 12" deep with shredding unit and waste receptacle. Security features will include cross-cut shredding.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

F3010	Board, Bulletin, 48 x 48	1	VV	Open face bulletin board. Cork posting panel with moisture proof backing. Variety of frames to choose from. Used for posting notes and messages.
F3030	Board, Scheduling, Magnetic	1	VV	Magnetic scheduling board, 36" X 48". Porcelain enamel magnetic surface. Used for letter transferring while posting messages or scheduling. For use with marker pens.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
L0100	Microscope, Binocular	1	VV	Binocular microscope. Equipped with plan achromatic objectives to suit work in brightfield, phase contrast, darkfield, photomicrography, dual viewing and projection screen. Microscope has a high light intensity, 100 watt halogen lamp, for constant color temperature and illumination, a three step variable transformer, focusable aspheric abbe condenser system; heat absorbing glass; centerable field diaphragm; two built-in filter turrets permitting a combination of selective light balancing and color compensating filters. Other components/features include a swing-in condenser, 4X objective, quadruple nosepiece, 10X wide field eyepieces and a graduated stage. Other observation tubes can be added. It is used in laboratories for cell counting and other observation techniques.
L1300	Centrifuge, Small, Blood Typing, Variable Speed	1	VV	Small laboratory centrifuge with variable speed allowing both regular and delicate centrifugation. It has a brake to allow a complete stop in 10 seconds, 0 to 30 minute timer, interchangeable heads and can accommodate up to 24 tubes. Used for blood grouping and cross matching.
L1502	Centrifuge, Tabletop	1	VV	Tabletop laboratory centrifuge. This unit has a variable speed range of 1500 to 13000 RPM in part dependent on rotor assembly used. It includes a no brake option allowing rotor to spin to a gradual stop as well as the capability to enter combinations of time and RPM into the memory, and a door lock safety system. Heads accommodate a wide variety of tubes and can accommodate up to at least 76 tubes. Used in laboratories to prepare samples for further analysis.
L1660	Cell Washer/Centrifuge	1	VV	Combination cell washer and centrifuge. The unit has two fixed speeds of 3600 or 12000 RPM. It is a microprocessor controlled unit with a programmable memory that can hold up to four wash cycles. It has a built-in peristaltic pump with a drain, dual angle rotor, low saline level alarm and uses 10 X 75mm or 12 X 75mm tubes. Used for compatibility testing, cytological studies and other laboratory applications.
L8005	Incubator, Blood Bank, Tabletop	1	VV	The incubator is used to perform crossmatches, indirect Coombs test, Rh titers, Du tests. It maintains through the use of dry heat blocks a constant temperature of 37degrees centigrade with an accuracy within + or - .5 degrees centigrade. It accommodates up to 40 tubes with diameters of 12mm. It is designed to be placed on a table top and is approximately 5" x 9" x 3".
M1405	Chair, Blood Donor, Recliner, w/Motor, Armrest	1	VV	Donor chair, with motor and armrest. Contour chair with extra wide armrests, remote control, and power slide control.
M1450	Sealer, Electronic, Blood Bag	1	VV	Electronic blood bag sealer. Used for sealing blood-filled plastic tubing of blood collecting-dispensing bag.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	1	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
R4700	Ice Maker, Cubes, 250 Pound	1	CC	Ice cube maker approximately 39" H x 29" D x 26" W. This unit is self-contained and provides 250 pounds of ice every 24 hours. The exterior is made of sturdy stainless steel. It is used in hospitals, hotels, and restaurants for dispensing ice.
R5110	Freezer, Rapid, Blood/Plasma, 4 Cubic Feet	1	VV	Rapid freezer for blood products and plasma. This unit uses a liquid cooling medium for rapid heat reduction and consistent freezing rate. The unit is insulated with a minimum of 3 1/2" of poured in place urethane insulation. Refrigeration system is an air cooled or water cooled compressor system. This unit may be a chest or upright type freezer. Also know as a blast freezer.
R6010	Refrigerator, Blood Bank, Glass Do, Dr, 25 Cu Ft	1	VV	Blood bank refrigerator. This unit has a single glass door, pull-out drawer, 7 day recording thermometer, high/low alarm system, battery-powered power failure alarm and remote alarm. The unit is used for storage of blood as required by AABB, ANRC and FDA for whole blood.
R6200	Refrigerator, U/C or F/S, 5 Cu Ft	1	VV	Utility refrigerator approximately 35" H x 24" W x 26" D. The unit has a two tray ice cube cooling system. The refrigerator fits standard architectural dimensions for undercounter installation. The unit is perfect for use in nurses' station, wards, and laboratories, pharmacies or wherever space is limited.
11 - LMM 02 - Microbiology, Clinical Microbiology				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
C0043	Frame, Apron, 1 Drawer, 4x24x22	1	CC	Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CG040	Cabinet, W/H, 2 SH, 2 SGDO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass sliding doors, and sloping top. Also referred to as a framed-glass sliding double door wall case. For general purpose use throughout the facility.
CS270	Sink, Epoxy Resin, 11x18x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
D3295	Chair, Rotary, Laboratory, Dental	1	VV	Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.
L0100	Microscope, Binocular	1	VV	Binocular microscope. Equipped with plan achromatic objectives to suit work in brightfield, phase contrast, darkfield, photomicrography, dual viewing and projection screen. Microscope has a high light intensity, 100 watt halogen lamp, for constant color temperature and illumination, a three step variable transformer, focusable aspheric abbe condenser system; heat absorbing glass; centerable field diaphragm; two built-in filter turrets permitting a combination of selective light balancing and color compensating filters. Other components/features include a swing-in condenser, 4X objective, quadruple nosepiece, 10X wide field eyepieces and a graduated stage. Other observation tubes can be added. It is used in laboratories for cell counting and other observation techniques.

M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
R5100	Freezer, Biological, -85, 19-25 Cubic Feet, Upright	1	VV	Biological freezer, -85 degrees centigrade, 19-25 cubic feet with temperature recorder, remote alarm, and storage baskets. Optional auxiliary water cooling available. Upright type freezer.

12 - LMM 03 - Microbiology, Biosafety Laboratory

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.

				<p>THIS TYPICAL INCLUDES:</p> <p>9 Vertical Hanger Strips; 1 Equipment Rail, System-Mt, 24"W; 1 Light 24"W; 2 Light 30"W; 2 Light 48"W; 1 Cantilevered Work Surface 30"D x 48"W; 1 Cantilevered Work Surface 30"D x 60"W; 1 Cantilevered Work Surface 30"D x 72"W; 2 Drw, 6"H; 1 Lockable Flipper Unit, 24"W 2 Lockable Flipper Unit, 30"W; 2 Lockable Flipper Unit, 48"W; 2 Mobile Drawer Caddie with Drawers; 1 Adjustable Keyboard Tray; 1 Shelf, Storage/Display 24"W 2 Shelf, Storage/Display 30"W; 2 Shelf, Storage/Display 48"W; 2 Extra Deep Shelf, 24"W; 2 Extra Deep Shelf, 48"W; 1 Cantilevered Sink Cab, w/Corian Top 30"D x 24"W; 1 SS Sink 19"D x 21"D; 1 Swing-Away Eyewash; 1 Gooseneck Mixing Faucet ASSY. With Wristbands; 1 Strainer and Tailpiece; Drawer Organizer Bins * Hardware required to complete installation.</p>
E0574	Workstation. Microbiology Lab, Minimal	1	VV	
F0230	Chair, Drafting, Rotary	4	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

L0100	Microscope, Binocular	1	VV	Binocular microscope. Equipped with plan achromatic objectives to suit work in brightfield, phase contrast, darkfield, photomicrography, dual viewing and projection screen. Microscope has a high light intensity, 100 watt halogen lamp, for constant color temperature and illumination, a three step variable transformer, focusable aspheric abbe condenser system; heat absorbing glass; centerable field diaphragm; two built-in filter turrets permitting a combination of selective light balancing and color compensating filters. Other components/features include a swing-in condenser, 4X objective, quadruple nosepiece, 10X wide field eyepieces and a graduated stage. Other observation tubes can be added. It is used in laboratories for cell counting and other observation techniques.
L2310	Cabinet, Bio Safety, Class II/A1, F/S, Vert, 4ft	1	VC	Bio safety cabinet, Class II, Type A1. This is a vertical freestanding unit with a face velocity of 100 fpm, constructed of type 304 stainless steel. The inside walls have a high velocity air return. The unit utilizes 70% air recirculation 30% exhaust either into room or through to the outside. It requires HEPA and includes a removable work tray, built-in drain valve, two valve penetrations with blanking plugs, duplex outlet and a fluorescent lamp. Used for low to moderate risk biological agents with the absence of volatile toxic chemicals and radionuclides. 4 foot model, other sizes available.
L2660	Microbiological Identification System	1	VV	Microbiological identification system. The systems basic principles of operation consists of: photometry, fluorescence, radiometry, infrared spectrophotometry, and video image analysis, together with a MPLS (multiple-parameter light scattering technique) and a continuous flow-through detection system. It consists of an auto-prep station, auto filter, incubator, detector/reader, waste reservoir, and computer sample throughput of over 200/day. Designed to detect presence of micro organisms in body fluids, test susceptibility of micro organisms to anti microbial agents, and/or determine the minimum inhibitory concentrations of antibiotics in order to identify pathogens.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
R6280	Refrigerator, Lab, SS, 2 Door, 6 Shelves	2	VV	Laboratory refrigerator approximately 83x56x33 in size. This unit will have double-doors; stainless steel interior; six stainless steel shelves that are fully adjustable to one-half centers; blower coil cooler with automatic off cycle defrost and a seven day precision temperature recording clock. This unit is used in hospitals and research laboratories for general cold storage.

13 - LMM 03 - Microbiology, Mycology Laboratory

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
E0574	Workstation. Microbiology Lab, Minimal	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 9 Vertical Hanger Strips; 1 Equipment Rail, System-Mt, 24"W; 1 Light 24"W; 2 Light 30"W; 2 Light 48"W; 1 Cantilevered Work Surface 30"D x 48"W; 1 Cantilevered Work Surface 30"D x 60"W; 1 Cantilevered Work Surface 30"D x 72"W; 2 Drw, 6"H; 1 Lockable Flipper Unit, 24"W 2 Lockable Flipper Unit, 30"W; 2 Lockable Flipper Unit, 48"W; 2 Mobile Drawer Caddie with Drawers; 1 Adjustable Keyboard Tray; 1 Shelf, Storage/Display 24"W 2 Shelf, Storage/Display 30"W; 2 Shelf, Storage/Display 48"W; 2 Extra Deep Shelf, 24"W; 2 Extra Deep Shelf, 48"W; 1 Cantilevered Sink Cab, w/Corian Top 30"D x 24"W; 1 SS Sink 19"D x 21"D; 1 Swing-Away Eyewash; 1 Gooseneck Mixing Faucet ASSY. With Wristbands; 1 Strainer and Tailpiece; <p>Drawer Organizer Bins</p> <p>* Hardware required to complete installation.</p>
F0230	Chair, Drafting, Rotary	4	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
L0100	Microscope, Binocular	1	VV	Binocular microscope. Equipped with plan achromatic objectives to suit work in brightfield, phase contrast, darkfield, photomicrography, dual viewing and projection screen. Microscope has a high light intensity, 100 watt halogen lamp, for constant color temperature and illumination, a three step variable transformer, focusable aspheric abbe condenser system; heat absorbing glass; centerable field diaphragm; two built-in filter turrets permitting a combination of selective light balancing and color compensating filters. Other components/features include a swing-in condenser, 4X objective, quadruple nosepiece, 10X wide field eyepieces and a graduated stage. Other observation tubes can be added. It is used in laboratories for cell counting and other observation techniques.
L2310	Cabinet, Bio Safety, Class II/A1, F/S, Vert, 4ft	1	VC	Bio safety cabinet, Class II, Type A1. This is a vertical freestanding unit with a face velocity of 100 fpm, constructed of type 304 stainless steel. The inside walls have a high velocity air return. The unit utilizes 70% air recirculation 30% exhaust either into room or through to the outside. It requires HEPA and includes a removable work tray, built-in drain valve, two valve penetrations with blanking plugs, duplex outlet and a fluorescent lamp. Used for low to moderate risk biological agents with the absence of volatile toxic chemicals and radionuclides. 4 foot model, other sizes available.
L2660	Microbiological Identification System	1	VV	Microbiological identification system. The systems basic principles of operation consists of: photometry, fluorescence, radiometry, infrared spectrophotometry, and video image analysis, together with a MPLS (multiple-parameter light scattering technique) and a continuous flow-through detection system. It consists of an auto-prep station, auto filter, incubator, detector/reader, waste reservoir, and computer sample throughput of over 200/day. Designed to detect presence of micro organisms in body fluids, test susceptibility of micro organisms to anti microbial agents, and/or determine the minimum inhibitory concentrations of antibiotics in order to identify pathogens.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
R6280	Refrigerator, Lab, SS, 2 Door, 6 Shelves	2	VV	Laboratory refrigerator approximately 83x56x33 in size. This unit will have double-doors; stainless steel interior; six stainless steel shelves that are fully adjustable to one-half centers; blower coil cooler with automatic off cycle defrost and a seven day precision temperature recording clock. This unit is used in hospitals and research laboratories for general cold storage.

14 - LMM03 - Microbiology, Mycobacteriology (TB) Laboratory

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	1	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
E0574	Workstation. Microbiology Lab, Minimal	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 9 Vertical Hanger Strips; 1 Equipment Rail, System-Mt, 24"W; 1 Light 24"W; 2 Light 30"W; 2 Light 48"W; 1 Cantilevered Work Surface 30"D x 48"W; 1 Cantilevered Work Surface 30"D x 60"W; 1 Cantilevered Work Surface 30"D x 72"W; 2 Drw, 6"H; 1 Lockable Flipper Unit, 24"W 2 Lockable Flipper Unit, 30"W; 2 Lockable Flipper Unit, 48"W; 2 Mobile Drawer Caddie with Drawers; 1 Adjustable Keyboard Tray; 1 Shelf, Storage/Display 24"W 2 Shelf, Storage/Display 30"W; 2 Shelf, Storage/Display 48"W; 2 Extra Deep Shelf, 24"W; 2 Extra Deep Shelf, 48"W; 1 Cantilevered Sink Cab, w/Corian Top 30"D x 24"W; 1 SS Sink 19"D x 21"D; 1 Swing-Away Eyewash; 1 Gooseneck Mixing Faucet ASSY. With Wristbands; 1 Strainer and Tailpiece; Drawer Organizer Bins <p>* Hardware required to complete installation.</p>
F0230	Chair, Drafting, Rotary	4	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.
F0280	Chair, Swivel, Low Back	1	VV	Low back contemporary swivel chair, 37" high X 25" wide X 31" deep with a five (5) caster swivel base, arms and foam padded seat and back upholstered with either woven textile fabric or vinyl.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
L0100	Microscope, Binocular	1	VV	Binocular microscope. Equipped with plan achromatic objectives to suit work in brightfield, phase contrast, darkfield, photomicrography, dual viewing and projection screen. Microscope has a high light intensity, 100 watt halogen lamp, for constant color temperature and illumination, a three step variable transformer, focusable aspheric abbe condenser system; heat absorbing glass; centerable field diaphragm; two built-in filter turrets permitting a combination of selective light balancing and color compensating filters. Other components/features include a swing-in condenser, 4X objective, quadruple nosepiece, 10X wide field eyepieces and a graduated stage. Other observation tubes can be added. It is used in laboratories for cell counting and other observation techniques.
L2310	Cabinet, Bio Safety, Class II/A1, F/S, Vert, 4ft	1	VC	Bio safety cabinet, Class II, Type A1. This is a vertical freestanding unit with a face velocity of 100 fpm, constructed of type 304 stainless steel. The inside walls have a high velocity air return. The unit utilizes 70% air recirculation 30% exhaust either into room or through to the outside. It requires HEPA and includes a removable work tray, built-in drain valve, two valve penetrations with blanking plugs, duplex outlet and a fluorescent lamp. Used for low to moderate risk biological agents with the absence of volatile toxic chemicals and radionuclides. 4 foot model, other sizes available.
L2660	Microbiological Identification System	1	VV	Microbiological identification system. The systems basic principles of operation consists of: photometry, fluorescence, radiometry, infrared spectrophotometry, and video image analysis, together with a MPLS (multiple-parameter light scattering technique) and a continuous flow-through detection system. It consists of an auto-prep station, auto filter, incubator, detector/reader, waste reservoir, and computer sample throughput of over 200/day. Designed to detect presence of micro organisms in body fluids, test susceptibility of micro organisms to anti microbial agents, and/or determine the minimum inhibitory concentrations of antibiotics in order to identify pathogens.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
R6280	Refrigerator, Lab, SS, 2 Door, 6 Shelves	2	VV	Laboratory refrigerator approximately 83x56x33 in size. This unit will have double-doors; stainless steel interior; six stainless steel shelves that are fully adjustable to one-half centers; blower coil cooler with automatic off cycle defrost and a seven day precision temperature recording clock. This unit is used in hospitals and research laboratories for general cold storage.

15 - LMM 02 - Microbiology, Media Preparation Room

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
C0043	Frame, Apron, 1 Drawer, 4x24x22	1	CC	Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CG040	Cabinet, W/H, 2 SH, 2 SGDO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass sliding doors, and sloping top. Also referred to as a framed-glass sliding double door wall case. For general purpose use throughout the facility.
CS270	Sink, Epoxy Resin, 11x18x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
D3295	Chair, Rotary, Laboratory, Dental	1	VV	Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.

L0100	Microscope, Binocular	1	VV	Binocular microscope. Equipped with plan achromatic objectives to suit work in brightfield, phase contrast, darkfield, photomicrography, dual viewing and projection screen. Microscope has a high light intensity, 100 watt halogen lamp, for constant color temperature and illumination, a three step variable transformer, focusable aspheric abbe condenser system; heat absorbing glass; centerable field diaphragm; two built-in filter turrets permitting a combination of selective light balancing and color compensating filters. Other components/features include a swing-in condenser, 4X objective, quadruple nosepiece, 10X wide field eyepieces and a graduated stage. Other observation tubes can be added. It is used in laboratories for cell counting and other observation techniques.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
R5100	Freezer, Biological, -85, 19-25 Cubic Feet, Upright	1	VV	Biological freezer, -85 degrees centigrade, 19-25 cubic feet with temperature recorder, remote alarm, and storage baskets. Optional auxiliary water cooling available. Upright type freezer.

16 - LMHC1 - Immunopathology

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
C0043	Frame, Apron, 1 Drawer, 4x24x22	1	CC	Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall.
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.

C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
C04E0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
CG040	Cabinet, W/H, 2 SH, 2 SGDO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass sliding doors, and sloping top. Also referred to as a framed-glass sliding double door wall case. For general purpose use throughout the facility.
CS270	Sink, Epoxy Resin, 11x18x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
D3295	Chair, Rotary, Laboratory, Dental	1	VV	Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.

5 - ANATOMICAL PATHOLOGY WORK AREA

1 - LMHS2 - Histology Laboratory

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	4	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	2	VV	Telephone, desk, multiple line.
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.

A5106	Waste Disposal Unit, Sharps w/Glove Dispenser	2	VV	The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.
A5230	Cabinet, Blanket, Fire, Wall Mounted	1	CC	Fire blanket cabinet with fire blanket, wall mounted cabinet. Finish is rust and acid resistant baked enamel and designed for storage of fire blankets.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	<p>This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THISTYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File

				<p>2 Module, 48"H x 24"W,w/ 7-1/4 inch utility chase, w/ service shelf; 5 Module, 48"H x 48"W,w/ 7-1/4 inch utility chase, w/ service shelf; 5 Clinical Panel, Open 80"H x 30"W; 6 Clinical Panel, Open 80"H x 48"W; 2 Clinical Panel with Ceiling Entry ELEC/Data Channel, 80"H x 48"W; 6 Clinical Panel, 48"H x 30"W; 1 Clinical Panel, 80"H x 30"W; 2 Vertical Chase Cover; 7 Electrical/Data Channel 48"W; 1 Electrical/Data Channel 60"W; 1 Electrical/Data Channel, Corner; 4 Light, 30"W; 8 Light, 48"W; 12 Cantilevered Work Surface, 30"D x 48"W, With Supports; 1 Cantilevered Work Surface, 30"D x 51"W,With Supports ; 1 Cantilevered Work Surface, 30"D x 60"W, With Supports; 1 Cantilevered Work Surface, 30"D x 72"W,With Supports ; 2 Cantilevered Corner Work Surf, 30"D x 48"W x 48"W; 4 Height Adjustable Table, 36"D x 72"W; 1 Height Adjustable Table, 30"D x 60"W; 2 Adjustable Keyboard Tray; 8 Mobile Drawer Caddie with Drawers; 21 DR, 3"H; 8 DR, 6"H; 7 Storage Cabinet With Door; 4 Lockable Flipper Unit, 30"W; 7 Lockable Flipper Unit, 48"W; 1 3-Shelf Unit with Door, 48"W; 4 Shelf, Storage/Display 30"W; 7 Shelf, Storage/Display 48"W; 4 Extra Deep Shelf, 24"W; 14 Extra Deep Shelf, 48"W; 2 Sink Base Cabinet, w/Double Door, Backsplash, w/Corian Top, 30"D x 60"W; 2 Swing-Away Eyewash;</p>
E0593	Workstation, Histopathology Lab, Medium	1	VV	
F0230	Chair, Drafting, Rotary	4	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.

F2000	Basket, Wastepaper, Round, Metal	4	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F2540	Shredder, Paper, Security	1	VV	Paper shredder, approximately 21" high X 15" wide X 12" deep with shredding unit and waste receptacle. Security features will include cross-cut shredding.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
K4665	Oven, Microwave, Consumer	1	VV	Counter mounted microwave oven for average duty use. The exterior cabinet can be metal or heavy duty impact resistant plastic. The oven delivers instant energy for rapid heating, defrosting or prime cooking. The oven has touch pad controls, digital timer, power level selector and preprogrammed selectors for commonly cooked items. This oven is commonly found in staff lounges.
L0075	Microscope, Stereo, Photographic, Desk Top	1	VV	Photo-Microscope system. Unit produces crisp, high resolution images over the entire photo magnification range. The system includes focusing tube, coupler, shock mounted shutter, distortion-free amplifier lens, cable release and digital camera. The unit has approximate 7.5 magnification factor, a halogen light source for color, balanced photomicrography, plan fluorite objectives for clarity and flatness of field for full image viewing and accurate image production and an automatic match of film to correct reciprocity. Other attachments are available. Unit is a stereo microscope for viewing of non-translucent samples.
L0100	Microscope, Binocular	1	VV	Binocular microscope. Equipped with plan achromatic objectives to suit work in brightfield, phase contrast, darkfield, photomicrography, dual viewing and projection screen. Microscope has a high light intensity, 100 watt halogen lamp, for constant color temperature and illumination, a three step variable transformer, focusable aspheric abbe condenser system; heat absorbing glass; centerable field diaphragm; two built-in filter turrets permitting a combination of selective light balancing and color compensating filters. Other components/features include a swing-in condenser, 4X objective, quadruple nosepiece, 10X wide field eyepieces and a graduated stage. Other observation tubes can be added. It is used in laboratories for cell counting and other observation techniques.
L0115	Microscope, Photographic	1	VV	Photo-Microscope system. Unit produces crisp, high resolution images over the entire photo magnification range. The system includes focusing tube, coupler, shock mounted shutter, distortion-free amplifier lens, cable release and 35mm camera. The unit has a 7.5X magnification factor, halogen light source for color, balanced photomicrography, plan fluorite objectives for clarity and flatness of field for full image viewing and accurate image production and an automatic match of film to correct reciprocity. Other attachments are available.
L0145	Microscope, Teaching, Multiple Head	1	VV	Multiple head teaching microscope. Designed to accommodate from two to six viewers simultaneously, providing each observer an identical image of the specimen with exact orientation and intensity of the image. Magnification ranges from 4X to 100X and there is a five-place nosepiece with knurled-edge gripping surface for easy rotation. The microscope accepts 32 or 45mm filters and has other accessories available for various configurations.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

L0160	Tissue Processor, Vacuum	1	VV	Vacuum infiltrator tissue processor. The unit is computer controlled and has a self-contained cleaning system. A pressure/vacuum cycle is provided for better infiltration and exchange of fluids. Used for specimen preparation for electron microscopes.
L1350	Centrifuge, Table, Small, 3200 RPM, 6 Place	1	VV	Small table centrifuge. Characteristics/components include a speed range up to 3200 RPM, steel guard bowl, electric motor, speed controlled by a dial rheostat, a six place trunnion head to accommodate 15 ml tubes contained in metal shields with rubber cushions, numbered tube slots and a safety cap. Used in a laboratory for general purpose centrifugation of samples.
L1500	Centrifuge, Medium Duty, Refrigerated, Floor Model	1	VV	Laboratory centrifuge. This is a medium to large capacity unit with an operating range of -20 degrees to 40 degrees C. It permits running samples at body temperature. It also has a rotor imbalance detector and an auto-shut down capability if the rotor load is out of balance. The unit is constructed of a stainless steel chamber with a rear exhaust and is a low heat output unit. Used in laboratories to spin samples for further analysis.
L1945	Distilling Apparatus, Xylene Recovery	1	VV	Xylene still for reprocessing used Xylene. Some manufacturers offer an accessory spill catch pan.
L1946	Recycling System, Formalin	1	VV	Formalin recycling system. The system reclaims used formalin by means of a microprocessor controlled automated process. The system is capable of recycling up to 5 gallons in 6 to 8 hours (or less).
L2000	Purification System, Water	1	VV	Water Purification System (also referred to as a water-polishing unit) that is capable of producing not less than 24 liters of water per hour, free of ionic contamination and with reduced Total Organic Compounds (TOC) not to exceed 6 parts per billion and water resistivity up to 18.3 megohm-cm from a clean (tap) water source. Purified water to be used for HPLC or GC/MS applications and TOC analysis. System must utilize operator replaceable cartridges and UV light source to obtain the specified purity. System must be fully automatic and switch to a standby mode during periods of reduced use. Design must incorporate a resistivity indicator and a final bacterial 0.22 micrometer filter.
L2060	Dryer, Glassware, Electric	1	CC	Electrically heated glassware dryer. The unit is constructed of stainless steel, has an adjustable automatic or manual timer and operates to a temperature of 325 degrees Fahrenheit. It has a hot air circulation and exhaust system with a drying compartment that is 25"W X 23"L minimum. Used to dry glassware and non heat sensitive parts in the hospital.
L2250	Hood, Fume, Bench	1	CC	Benchtop fumehood. This is an auxiliary air type to be sized as required. The unit will have a remote switch with a pilot light, a fluorescent light, an acid resistant fan and blower housing. The minimum average face velocity shall be 100 fpm. It shall include a steel frame sash that is heat resistant to 71 degrees centigrade. The static pressure loss shall not exceed 0.22 inches of water at 100 fpm face velocity. Other accessories and gases are as defined during the design of the facility.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

L2337	Canopy, Hood, Fume, 6 foot	1	CC	Canopy fumehood. The unit includes a switched fan unit with pilot light; corrosion resistant steel, aluminum, or chemical resistant and fire retardant seamless fiberglass construction; dimensions as indicated on design drawings; fire suppression systems and any other special requirements to be defined during the facility design. It also includes a 3/4 horsepower motor blower. The static pressure loss shall not exceed 0.91 at 1290 cfm and 1.65 at 1935 cfm. It is equipped with baffles to maximize slot velocities and control fumes. Used in laboratories for low to moderate risk biological agents. Other sizes may be available. Blower motor mounted separate from the canopy and may not be included in the size specification.
L3365	Washer, Labware, Electric, Under Counter	1	CC	Under counter labware washer. It has an electric steam generator to achieve a high temperature wash and steam cycle. It also has a high capacity pump and blower dryer. Used to wash laboratory glassware.
L3400	Microtome, Rotary, Tilt, Bench Mounted	3	VV	Bench mounted tilting rotary microtome. The unit's features include horizontal advancement, a feed indicator and selection dial that provide settings from 1 to 30 microns, a quick change holder system that allows the use of different holders, an angle adjustment from 0 to 15 degrees and a hand wheel that allows speed control without backflash. Used for histological techniques and slide preparation.
L3430	Microtome, Rotary, Tilt, Refrigerated	2	VV	Refrigerated rotary microtome/cryostat. The unit's features include horizontal advancement, sectioning from 2-20 microns, combination unit consisting of an automatic defrost of chamber and microtome, a temperature range from -30 degrees centigrade to room temperature, and a defrost cycle of 10 minutes every 24 hours. Used to prepare samples for slide studies.
L4200	Bath, Water, Serology, Electric	3	VV	Serological water bath. It operates in the temperature range of 60 to 100 degrees centigrade. It has a corrosion-proof stainless steel water tank with a 3 gallon capacity. Models have drain spouts for easy emptying of media. Used to provide a controlled temperature environment for the preparation of samples for study.
L4205	Bath, Water, Tissue Processing	3	VV	Tissue processing water bath. It has a sensitive thermostat providing regulation to +/-0.1 degree C., a temperature range from ambient to 72 degrees centigrade, black coating in chamber to provide visual contrast, fiberglass insulated sides and bottom and a dependable gravity convection.
L4360	Warmer, Slide	1	VV	Slide warmer used to mount paraffin sections. Used in microbiology. Holds 48 slides.
L7300	Stirrer, Hot Plate, Magnetic	1	VV	Magnetic stirrer-hot plate. It has variable stirring speeds of near 1500 RPM, temperatures of up to about 400 degrees centigrade, back up safety thermostat, plate surface of about 49 square inches and Pyroceram glass ceramic top that is corrosion resistant. Used for reagent mixing and heating, preparing culture media, evaporation and distillation procedures.
L8280	Oven, Drying, Medium, 2 Cubic Foot	1	VV	Medium laboratory drying oven. It has a temperature range of ambient to 210 degrees centigrade, a stainless steel interior, temperature control, timer and a 1.7 to 2.2 cubic foot capacity minimum. For drying and heating applications in the laboratory.
L8575	Cabinet, Paraffin Block	5	VV	Paraffin block storage cabinet. This cabinet accommodates 1200 paraffin blocks. Used for archiving paraffin embedded pathology specimens.
L8585	Stainer, Slide, Batch, Histological	1	VV	Batch slide stainer. This is a microprocessor controlled stainer designed for a minimum of 20 slides at one time. It includes a staining station, rinsing station and drying station. For use in microbiology, histology, and hematology laboratories.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

L8600	Slide Cover, Automated	1	VV	Automatic slide cover slipper. Takes standard microscope slides and places a resin-coated film over the slide. This device uses reagent grade Xylene as the fixing agent. Fume exhaust cover available.
L9000	Embedder, Tissue	2	VV	Tissue embedding center. This is a table top unit with a paraffin reservoir and cold plate, grouped together. The unit consists of a paraffin bath and a reservoir draining ledge, a heated work surface, large cold plate, foot pedal or touch plate for dispensing paraffin, a forceps warmer, a heated cassette holder, a temperature range on the paraffin bath of 45-65 degrees centigrade with a paraffin capacity of at least 2 liters, a plate that cools to -5 degrees centigrade or lower, a digital LED temperature display and can accommodate at least 50 cassettes.
L9015	Sharpener, Blade, Microtome	1	VV	Microtome blade sharpener. Sharpens knives while the knife is locked in place and held at proper angle to the honing plate. There is an electrical timer to set the desired time.
L9020	Tissue Processor, Automatic, 2 Level	2	VV	Automatic tissue processor. This is a rotating basket immersion type unit that uses a minimum of 10 solvents and two paraffin processing stations. It is controlled by an electrical or electronic timer. The paraffin bath temperature ranges from 50-65 degrees centigrade and is agitated. The fumes are removed by an integral fume collecting system. The process time/step is adjustable between 15 minutes to 24 hours. The drain time/step is 0 to 1 minute. Used to fix, dehydrate, clear and infiltrate tissue specimens to preserve the integrity of their cellular components for light microscopy.
L9720	Station, Pathology, Gross	1	CC	Gross pathology station. The unit contains four, two-speed electronic fans to reduce the danger of formaldehyde toxicity, an exhaust system with filters that last 2 to 8 months to convert the formaldehyde to CO2 and water, built in fluorescent lamps for shadow-free illumination, a "voice capturing option" to allow the pathologist to dictate without having to fumble with a hand or foot control and a built-in faucet with catch pan in the rear. Used for gross preparation of pathology specimens.
M1210	Balance, Electronic, Laboratory/Pharmacy	1	VV	Electronic balance with high fluorescent display, built-in auto tracking and tape. Unit has a programmable selection for weight range and automatic calibration. Intended for use in the laboratory or pharmacy. Unit's weight limitation will be no less than 4000 grams.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.
M1830	Printer, Label, Pharmacy	1	VV	Label printer for use in pharmacy applications. The printer shall be bench top standing. It shall be flexible enough to accommodate label sizes up to 4 inches, with a minimum print speed of 6 inches per second and a minimum resolution of 203 dpi.
M1840	Printer/Copier/Fax Combination	1	VV	Multifunctional printer, fax, scanner and copier (PFC) all-in-one machine.

M2005	Cabinet, Storage, Acid, Floor Standing, Shelves	1	VV	Floor standing acid storage cabinet. A 30 gallon capacity standard two door cabinet with adjustable shelves, three-point latch with key-lock and 2" raised leak proof sill. An 18-gauge steel frame with vents, 1 1/2" airspace between walls and epoxy finish resistant to chemical attack. Note: Not for use with nitric and sulfuric acids.
M2015	Cabinet, Storage, Flammable, Freestanding	1	VV	Freestanding flammable safety storage cabinet. Size as required. Unit is of all welded steel wall construction with vented grounding attachments, raised leak proof door sill and adjustable shelving. Equipped with swinging doors and built-in key lock. Designed for storage of flammable fluids. Complies with OSHA standards, is FM approved and designed IAW NFPA 30.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P5210	Shower, Safety, Freestanding, With Eye/Face Wash	1	CC	Deluge safety shower. This is a complete, maximum protection safety station consisting of a free-standing emergency shower and an eye/face wash fixture. Used anywhere exposure to hazardous substances may occur.
R6180	Refrigerator/Freezer, Explosion Proof, 13 Cu Ft	1	VV	Explosion-proof refrigerator. This unit offers protection from explosions caused by fume seepage from containers within working chambers. Unit shelves rest on brackets to permit easy removal. Unit has an adjustable temperature range of -20°C to 0°C. This unit is generally used in laboratories and hospitals for cold storage.

2 - LMHC1 - Frozen and Gross Section Laboratory

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
C0043	Frame, Apron, 1 Drawer, 4x24x22	1	CC	Apron frame with one standard drawer. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawer to support a top between base cabinets or a base cabinet and a wall.
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.

C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C02Q0	Cabinet, Sink, U/C/B, 1 Door, 36x24x22	1	CC	Standing height under counter base sink cabinet with a solid right or left-hinged door (appropriate door configuration to be indicated on equipment elevation drawings). Also referred to as a single-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
C04E0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
CG040	Cabinet, W/H, 2 SH, 2 SGDO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass sliding doors, and sloping top. Also referred to as a framed-glass sliding double door wall case. For general purpose use throughout the facility.
CS270	Sink, Epoxy Resin, 11x18x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
D3295	Chair, Rotary, Laboratory, Dental	1	VV	Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.

3 - LMCY3 - Cytology Laboratory

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.

A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0063	Workstation, L-Shaped w/Peninsula, Wall Mtd, 72x72	2	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 3 Vertical Hanging Strips 2 Lockable Flipper Units 2 Shelves, Storage/Display 2 Lights 1 Tackboard 2 Tool Rails 2 Paper Trays 1 Diagonal Tray 1 Cantilevered Work Surface 1 Peninsula Work Surface 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 1 Cpu Holder
F0275	Chair, Swivel, High Back	2	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F2000	Basket, Wastepaper, Round, Metal	2	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
L0105	Microscope, Binocular, Phase Contrast	2	VV	Binocular laboratory microscope. Characteristics include a 6V, 20W tungsten halogen lamp, quadruple revolving nosepiece, a binocular body, un-graduated mechanical stage, 4X, 10X, 40X and 100X plan achromatic objectives. Unit has a 1.25 condenser with mount, an auxiliary swing-in condenser, two (10X) widefield eyepieces, dual diopter adjustment and may include a carrying case. Used in the laboratory to perform observations on laboratory cultures and samples. Microscope to be provided with appropriate light source and filters for phase contrast microscopy.
L1502	Centrifuge, Tabletop	4	VV	Tabletop laboratory centrifuge. This unit has a variable speed range of 1500 to 13000 RPM in part dependent on rotor assembly used. It includes a no brake option allowing rotor to spin to a gradual stop as well as the capability to enter combinations of time and RPM into the memory, and a door lock safety system. Heads accommodate a wide variety of tubes and can accommodate up to at least 76 tubes. Used in laboratories to prepare samples for further analysis.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

L1780	Centrifuge, Cytology	4	VV	Cyto-Centrifuge. The characteristics/components include a specimen chamber designed to avoid slide damage, fluid path for premature absorption and a disinfectant tank for prevention of pathogenic aerosol. The unit has a maximum speed of approximately 2,000 RPM. Used for cell sedimentation and dispersion on a glass slide and other laboratory applications.
L2320	Cabinet, Bio Safety, Class II/B1, F/S, Vert, 4ft	1	CC	Class II, type B1, bio safety cabinet. This is a vertical, freestanding unit. The interior work surfaces shall be constructed of type 304 stainless steel and the exterior shall be of 16 gauge or heavier steel. The unit utilizes a 30% recirculated air and 70% direct exhaust through an in-house duct system, the face velocity is 100 fpm and includes an audible alarm when the window is at an unsafe operating level. It includes grounded duplex receptacles and two HEPA filters zero-probed. Used for low to moderate risk biological agents treated with minute quantities of toxic chemicals and trace amounts of radionuclides. A 4 foot cabinet is presented, other sizes are available.
L2630	Counter/Timer, Digital	2	VV	Digital counter/timer. The unit can perform frequency measurements in the range of 225 MHz and can perform time interval measurements between two events (start and stop events). The unit has not less than a 6 digit read out. Used for a variety of measurement functions such as frequency, period, time interval (Channel A to Channel B), frequency ratio (Channel A/Channel B), totaling, etc.
L2650	Counter, Bacteria	2	VV	Bacteria colony counter. This unit is manually adjusted. It is used in bacteriology, virology and mycology laboratories to count or measure bacteria colonies.
L8290	Oven, Drying, Large, 2 Door	1	VV	Double door laboratory drying oven. Also called a dry air sterilizer. It has a temperature range of 15-325 degrees centigrade, a stainless steel interior, a platinum temperature probe, a horizontal air flow, 12 hour timer and a 34+ cubic foot capacity.
L8570	Cabinet, Microscope Slide	10	VV	Microscope slide storage cabinet. This is a stackable unit and is made of steel with metal partitions that divide drawers vertically. It has pull-bar drawers with optional feature ball suspension design to prevent accident pull-out. Base is mounted on rubber feet to protect bench surfaces. Unit accommodates up to 5,000 slides.
L8585	Stainer, Slide, Batch, Histological	1	VV	Batch slide stainer. This is a microprocessor controlled stainer designed for a minimum of 20 slides at one time. It includes a staining station, rinsing station and drying station. For use in microbiology, histology, and hematology laboratories.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	2	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.

M2020	Cabinet, Storage, Safety, Built-In, Vented	1	CC	Safety storage cabinet. This unit is of double steel wall construction, with vented grounding attachment, raised leak proof door sill, and adjustable shelving. Equipped with two doors and three-point key lock. The construction meets standards set by OSHA and NFPA Code 30 requirements. Designed for storage of flammable type liquids. The cabinet fits into a laboratory casework configuration and its ventilation ports are in the back to leave the counterspace free. The cabinet requires ventilation ducting and an exhaust fan as part of the HVAC (heating, ventilation and air conditioning) system.
P1960	Eyewash, Counter Top	1	CC	Counter top mounted emergency eye wash station. Unit is hand operated to provide streams of water to clear or dilute foreign particles or liquids from the eyes in emergency situations. It is equipped with a stainless steel bowl, face spray ring and dual automatic pressure compensation devices. The valve remains open until manually closed. Used in laboratories and areas of the hospital where employees are subject to exposure to foreign bodies or caustic liquid matter to the eyes.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
R7200	Refrigerator, 20 Cubic Feet	1	VV	Commercial refrigerator, 20 cubic feet approximately 80" H x 32" D x 27" W. This unit is generally used to store perishable goods for safekeeping in commercial kitchens, hospitals and schools.

4 - SRL01 - Slide, Block and Records Files

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
L8570	Cabinet, Microscope Slide	30	VV	Microscope slide storage cabinet. This is a stackable unit and is made of steel with metal partitions that divide drawers vertically. It has pull-bar drawers with optional feature ball suspension design to prevent accident pull-out. Base is mounted on rubber feet to protect bench surfaces. Unit accommodates up to 5,000 slides.

6 - ELECTRON MICROSCOPY SUITE

1 - LBEM 2 - Scope Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.

C0039	Rail, Apron, 4x48x1	1	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.
C0046	Frame, Apron, 2 Drawer, 4x48x22	1	CC	Apron frame with two standard drawers. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawers to support a top between base cabinets or a base cabinet and a wall.
C04E0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 2 DO, 36x36x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CG040	Cabinet, W/H, 2 SH, 2 SGDO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass sliding doors, and sloping top. Also referred to as a framed-glass sliding double door wall case. For general purpose use throughout the facility.
CS260	Sink, Epoxy Resin, 10x25x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in suspended or U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
CW080	Cabinet, Floor Standing, 5 SH, 2 GDO, ST, 95x30x16	1	CC	Floor standing storage cabinet with five adjustable shelves, framed glass hinged doors, and sloping top. Also referred to as a framed glass hinged double door case. For general purpose use throughout the facility.
D3295	Chair, Rotary, Laboratory, Dental	1	VV	Rotary dental laboratory chair. The chair is used by technicians while working at a bench. Chairs also have casters and an adjustable backrest.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.

2 - LBEM 3 - Dark Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
CS150	Sink, SS, Single Compartment, 10x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.

3 - LBEM 3 - Preparation Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
CS150	Sink, SS, Single Compartment, 10x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.

5 - LBEM3 - Developing, Printing and Enlarging Dark Room				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
CS150	Sink, SS, Single Compartment, 10x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.

7 - AUTOPSY SUITE

1 - LBAR1 - Autopsy Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
C04H0	Cabinet, U/C/B, 2 Half Drawer, 3 Drawer, 36x36x22	1	CC	Standing height under counter base cabinet with two half width drawers side-by-side above three full width drawers. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.

C05G0	Cabinet, U/C/B, 2 Shelf, 2 Door, 36x48x22	1	CC	Standing height under counter base cabinet with two adjustable shelves and two solid hinged doors. Also referred to as a cupboard cabinet. For general purpose use throughout the facility.
CG040	Cabinet, W/H, 2 SH, 2 SGDO, Sloping Top, 38x36x13	1	CC	Wall hung cabinet with two adjustable shelves, framed-glass sliding doors, and sloping top. Also referred to as a framed-glass sliding double door wall case. For general purpose use throughout the facility.
CS150	Sink, SS, Single Compartment, 10x19x16 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.
CT050	Countertop, Stainless Steel	9	CC	Stainless steel countertop (composition of heavy-gauge Type No. 304 stainless steel) having a smooth satin finish and integral 4" backsplash/curb. Also referred to as a corrosion-resistant steel work surface or work top. Available in various depths. Used in areas where excellent ease of cleaning, abrasion resistance, bacteria resistance, impact resistance, load capacity and moisture resistance, are of concern. Pricing based upon a 24" depth.
F3050	Whiteboard, Dry Erase	1	VV	Whiteboard unit, approximately 36" H x 48" W consisting of a white porcelain enamel writing surface with an attached chalk tray. Magnetic surface available. Image can be easily removed with a standard chalkboard eraser. For use with water color pens. Unit is ready to hang.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
L5218	Scale, Autopsy	1	VV	Autopsy scale. It has an 8" diameter dial or electronic display (battery operated) with a minimum 30 pound capacity. Used in pathology departments to weigh body parts during autopsies.
L9700	Lift, Manual, Mortuary, 300 Lb. Capacity (Minimum)	1	VV	Manual cadaver lift. This is a manually operated 300 pound (minimal) capacity lift. It has launderable canvas straps or tray for holding and lifting cadavers. It uses a heavy duty manual winch for raising and lowering the cadaver and has heavy duty swivel casters with locks to aid in positioning the unit.
L9710	Table, Autopsy/Dissecting, Tank, CRS	1	VC	Tank type autopsy/dissecting table with submersion tank. The unit is made of corrosion resistant stainless steel and has a 60 gallon capacity reservoir tank.
L9711	Table, Autopsy, Stationary-Fixed-Height	1	CC	Autopsy table shall be constructed of stainless steel. It shall be polished to a smooth finish without crevices, lapped edges, rivets, or bolts. Table comes with integrated sink, waste disposer, grid plates for flat work area and perimeter downdraft.

L9715	Table, Autopsy, Mbl, w/Stationary Service Center	1	CC	Mobile autopsy table. The table is used in conjunction with a stationary service center equipped with operator work facilities. The stationary service center shall include a cabinet unit that contains all plumbing and built in operating services; such as an irrigation hose connection controlled by a thermostatic water mixing valve, duplex electrical outlet, a sink equipped with a swing faucet spout and wrist-blades, a specimen basket to hang in the sink and a removable swing drain to receive the mobile table drainage.
M3072	Frame, Infectious Waste Bag w/Lid	2	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P6350	Sink, Flushing Rim, China	1	CC	Flushing rim sink approximately 18" H x 26" D x 22" W. Also called a clinic service sink. Unit is constructed of vitreous china with an integral flushing rim. It includes: faucet with a fork brace; 6 inch wrist control handles; plain end spout with bucket hook; stainless steel spring type front rim guard; and grid drain. If it is to be floor mounted, a base must be provided. Unit is used in utility rooms to clean equipment and materials.

3 - LBM R1 - Mortuary Refrigerator (Cold Room)

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
L9700	Lift, Manual, Mortuary, 300 Lb. Capacity (Minimum)	1	VV	Manual cadaver lift. This is a manually operated 300 pound (minimal) capacity lift. It has launderable canvas straps or tray for holding and lifting cadavers. It uses a heavy duty manual winch for raising and lowering the cadaver and has heavy duty swivel casters with locks to aid in positioning the unit.
R7900	Refrigerator, Morgue, 2 Cadaver	1	CC	Mortuary refrigerator. This unit's entire front, including doors, is finished in polished stainless steel. It includes a removable body tray and supports two cadaver. The refrigerator is used in hospital morgues and funeral homes for refrigerated cadaver storage. The user must specify side or end-loading when ordering.
R7950	Refrigerator, Morgue, Side Opening, 3 Cadaver	1	CC	Mortuary refrigerator. This unit is designed for three cadaver capacity. To be used in hospital morgues and funeral homes for refrigerated cadaver storage.
R8000	Refrigerator, Morgue, 4 Cadaver	1	CC	Mortuary refrigerator approximately 73" W x 96" D x 76" H. This unit accommodates four cadavers. The unit is used in hospital morgues and funeral homes for refrigerated cadaver storage.

4 - LBT S1 - Gross Specimen Storage

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5108	Waste Disposal Unit, Sharps	1	VV	A container for collecting and transporting syringes and other sharps for decontamination and disposal. Available in 2 gallon and 8 gallon with locking rotor. Complies with OSHA regulations for handling sharps.
A5125	Rack, Crutch, Wall Mounted	1	VV	Wall mounted crutch rack. Constructed of natural finished wood with chrome plated adjustable hangers. Designed for hanging crutches and accessories.
C0039	Rail, Apron, 4x48x1	1	CC	Apron rail. Also referred to as an apron front, apron panel, or knee space rail. Used to close in front knee space area and/or provide work surface support between two base cabinets or a base cabinet and wall. Apron rails should be ordered in pairs to provide both front and rear work surface support.
C0046	Frame, Apron, 2 Drawer, 4x48x22	1	CC	Apron frame with two standard drawers. Also referred to as a drawer frame or table frame. Used for a knee space as a combination frame and drawers to support a top between base cabinets or a base cabinet and a wall.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.
C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CA040	Cabinet, Open, W/H, 2 Shelf, Sloping Top, 38x36x13	1	CC	Wall hung open front cabinet with two adjustable shelves and sloping top. Also referred to as an open case. For general purpose use throughout the facility.
CS260	Sink, Epoxy Resin, 10x25x15 ID	1	CC	One-piece cast epoxy resin sink (composition of molded epoxy resins and inert materials) connected with a drain and provided with a mixing faucet. For use in suspended or U/C/B sink cabinets and mounted under the epoxy resin countertops/work surfaces found in lab areas requiring optimum physical chemical resisting properties. For general purpose use in a lab area.
CT060	Countertop, Modified Epoxy Resin	1	CC	Modified epoxy resin countertop (composition of molded epoxy resins and inert materials) having a low sheen surface finish, standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab areas requiring optimum physical and chemical resisting properties.
F0230	Chair, Drafting, Rotary	1	VV	Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
F3010	Board, Bulletin, 48 x 48	1	VV	Open face bulletin board. Cork posting panel with moisture proof backing. Variety of frames to choose from. Used for posting notes and messages.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

L0100	Microscope, Binocular	1	VV	Binocular microscope. Equipped with plan achromatic objectives to suit work in brightfield, phase contrast, darkfield, photomicrography, dual viewing and projection screen. Microscope has a high light intensity, 100 watt halogen lamp, for constant color temperature and illumination, a three step variable transformer, focusable aspheric abbe condenser system; heat absorbing glass; centerable field diaphragm; two built-in filter turrets permitting a combination of selective light balancing and color compensating filters. Other components/features include a swing-in condenser, 4X objective, quadruple nosepiece, 10X wide field eyepieces and a graduated stage. Other observation tubes can be added. It is used in laboratories for cell counting and other observation techniques.
L1502	Centrifuge, Tabletop	1	VV	Tabletop laboratory centrifuge. This unit has a variable speed range of 1500 to 13000 RPM in part dependent on rotor assembly used. It includes a no brake option allowing rotor to spin to a gradual stop as well as the capability to enter combinations of time and RPM into the memory, and a door lock safety system. Heads accommodate a wide variety of tubes and can accommodate up to at least 76 tubes. Used in laboratories to prepare samples for further analysis.
L2336	Cabinet, Bio Safety, Class II/B2, Bench Top, 4ft	1	CC	Class II, Type B2, benchtop biological safety cabinet. The unit includes two HEPA filters, one supply and one exhaust, zero probed, high intake velocity that averages 105 fpm, an audible alarm to notify operator of unsafe window positions an audio-visual alarm to monitor exhaust pressure, interior of type 304 stainless steel with side walls slotted for high velocity air return, an exterior of 16 gauge or heavier steel, two ground key petcocks, a grounded duplex receptacle. Used for low to moderate risk biological agents treated with toxic chemicals and radionucleotides. This unit requires 100% exhaust to the atmosphere. 4 foot model presented, other sizes are available.
M3072	Frame, Infectious Waste Bag w/Lid	1	VV	Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation.
P1965	Eyewash, Eye/Face, Sink Mounted, Hands-free	1	CC	A sink mounted eyewash station. The unit is designed for emergency eye and face rinsing from soft flow dual spray-heads. The Flow must be activated by the single momentary action and remain on until terminated.
R6200	Refrigerator, U/C or F/S, 5 Cu Ft	1	VV	Utility refrigerator approximately 35" H x 24" W x 26" D. The unit has a two tray ice cube cooling system. The refrigerator fits standard architectural dimensions for undercounter installation. The unit is perfect for use in nurses' station, wards, and laboratories, pharmacies or wherever space is limited.

5 - TLTS1 - Bathroom, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
-----	------	-----	---------	-------------

A1090	Mirror, Float Glass, With SS Frame & Shelf	1	CC	A high quality 1/4" polished float glass mirror, approximately 36' H X 18' W framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners and an integral stainless steel, stain finish, shelf. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in restroom areas, Doctor examination areas, offices, etc. May also be used above double lavatories, either wall or countertop mounted.
A5030	Bench, Stall, Shower, Built In	1	CC	Shower bench; built-in. Eighteen (18) gauge stainless steel frame with anchors built-in into the wall. Size and shape as required.
A5075	Dispenser, Soap, Disposable	2	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.
A5110	Grab Bar, 1-1/4" Dia., SS, 2 Wall, Shower Use	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall shower, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical applications in shower stalls where ADA (American's With Disabilities Act) requirements must be met.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5170	Rod, Shower Curtain, 1"Diameter, W/Curtain & Hooks	1	CC	A concealed mounted, 1" outside diameter, satin finish stainless steel, shower curtain rod with white vinyl shower curtain (72" H) and SS shower curtain hooks. Rod and curtain available in various widths. For general purpose use at shower stall or bathtub locations. Pricing based upon standard shower stall dimensions of 36" x 36" and a standard curtain height of 72".

A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
A5205	Bar, Towel, 1" Diameter, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, 1" diameter, towel bar. Support posts and flanges are one piece, chrome-plated, cast heavy brass with satin finish. Towel bar shall not rotate within support posts. Available in 18", 24" and 30" widths. For general purpose use in shower or bathtub rooms. Pricing based upon a suggested standard width of 18".
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P5040	Shower, Single, Hand-Held	1	CC	A complete, barrier-free, single hand-held, personal shower system. The shower system includes: pressure balanced mixing valve with high temperature limit stop; personal hand shower; shower hose; wall supply; and slide bar. For general purpose use throughout the facility in shower stalls.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

6 - LR002 - Locker Room, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A1030	Locker, 2 Person, Over/Under	10	VV	Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal belongings. Other width and depths are available.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.
A5020	Bench, Locker Room, Floor Mounted	1	CC	Locker room bench. Floor mounting -1-1/4" thick. Benches are sanded smooth with two coats of moisture-resistant sealer to ensure a protective, satin gloss surface, and mounted on strong steel pedestal anchored to the floor. Over all height of 18" includes pedestal. Size as required.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

7 - JANC1 - Housekeeping Aides Closet (HAC)

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5135	Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd	1	CC	A surface mounted, satin finish stainless steel, utility shelf with a maximum of 6 mop/broom holders and 5 rag hooks. Utility shelf features: 8" deep shelf; mounting brackets welded to shelf; spring activated rubber cam holders; and drying rod. Unit is available in various widths 30" (minimum, 3 holders and 2 hooks) to 48" (maximum, 6 holders and 5 hooks). For use in janitor closets. Pricing based on a 36" width.
F0500	Cart, Janitor's	1	VV	Janitors cart, 38" high X 66" wide X 20" deep with 25 gallon heavy duty collection bag. Accommodations for locking vault and janitorial support items (broom, dust pan, chemicals, mop and mop bucket; not included).
F0505	Bucket, Mop, With Wringer, 26 Quart	1	VV	Mobile mop bucket / wringer combination, approximately 35" H x 17" W x 22" D with four 2" casters. Total capacity is 26 quarts. Unit used for general hard surface floor maintenance.
P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.
P4700	Sink, Mop, Molded Stone	1	CC	Mop service sink approximately 10"H x 36"W x 24"D. Also called a mop service basin and a mop receptor. Unit is made of molded stone and is a one piece item. It shall include a service faucet hose, hose bracket and mop hanger. Used in utility rooms for cleaning mops and floor cleaning equipment.

8 - SUPPORT AREA

1 - CSSS2 - Storage, Sterilization and Preparation Room

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.

S0432	Sterilizer,Stm,VAC,1DO,RCSD 1WLL,24x36x48 Chamber	2	CC	A recessed mounted (through one wall), single door (right or left-hinged, appropriate door configuration to be indicated on equipment elevation drawings), vacuum, sterilizer utilizing a remote electric steam generator. The unit is controlled by a microcomputer that monitors and controls all unit operations and functions and provides both audible and visual indications of deviations. A printer-recorder documents and records each cycle performance. For general purpose pre-vacuum or gravity steam sterilization of hospital and laboratory supplies at temperatures in the range from 110°C to 135°C (230°F to 275°F). A liquid cycle is also provided at temperatures in the range from 100°C to 121°C (212°F to 250°F). NOTE: For the electric steam generator, refer to JSN: S1830. Door may be power operated.
S0495	Loading Car & Transfer Carriage, 24x36x48 Chamber	4	CC	Loading car and transfer carriage for use with sterilizers having a 24x36x48 chamber. Loading car is a welded, CRS framework with two full-length adjustable shelves of CRS welded sheet metal and wire. Transfer carriage is constructed of a welded CRS or painted for corrosion protection frame and provided two fixed and two swivel casters. Loading car is secured to the transfer carriage by a locking mechanism. For loading and unloading 24x36x48 sterilizers and for transferring goods to and from processing areas.
S1830	Generator, Steam, Electric, 75 KW	2	CC	A 68 to 75 kW electric steam generator/boiler with low water cut-off/level control, water level sight glass, main off/on switch, pilot light, blowdown/drain valves, safety valve, and steam pressure gauge. The unit can deliver steam at operating pressures up to 90 PSIG and produce a minimum steam output of 205 lbs./hr. Unit provides condensate free steam, between 97% to 100% vapor quality, needed to power sterilizers, water stills, utensil sanitizers, and other steam powered equipment when facility supplied steam is not available. Various electrical configurations are available for the heaters, for pricing purposes 208V, 60HZ, 3PH, 209AMPS is used.

2 - SRS01 - Storage, Bulk

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1014	Telephone, Wall Mounted, 1 Line, With Speaker	1	VV	Telephone, wall mounted, 1 line, with speaker.
M2055	Shelving, Storage, Wire, CRS, w/Adjustable Shelves	6	VV	Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price provided is for a unit approximately 74"H x 18"D x 48"W with four shelves.

3 - SRR01 - Storage, Refrigerated

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
R8600	Refrigerator, Prefab, 320 Cubic Feet	1	CC	Prefabricated refrigerator, approximately 108x108x108. Unit is an architect planned, custom-sized, walk-in cooler. It has a side or ceiling mounted self-contained and easily serviced refrigeration system. Unit is used for bulk, indoor cold storage in commercial institutions and hospital kitchens. Size and shape may vary depending on site configuration.

4 - SRGC2 - Storage, Flammable and Toxic Substance				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
M2025	Rack, Storage, Cylinder, Gas	1	VV	Medical gas cylinder storage rack. Unit is a modular cage frame for holding various sizes of gas cylinders. Nylon or fabric securing straps can be attached to the frame bars to stabilize gas cylinders. Add additional units or specify size as required when ordering. This item is often locally fabricated.
M2117	Truck, Hand, 2 Wheel, Gas Cylinder	1	VV	A gas cylinder hand truck for a single 12" cylinder with a minimum capacity of 300 lbs.
5 - JANC1 - Housekeeping Aides Closet (HAC)				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5107	Dispenser, Glove, Surgical/Examination, Wall Mntd	1	VV	Examination glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Provided with wall bracket to facilitate mounting and demounting.
A5135	Shelf, Utility W/ Mop/Broom Holders, SS, Surf Mntd	1	CC	A surface mounted, satin finish stainless steel, utility shelf with a maximum of 6 mop/broom holders and 5 rag hooks. Utility shelf features: 8" deep shelf; mounting brackets welded to shelf; spring activated rubber cam holders; and drying rod. Unit is available in various widths 30" (minimum, 3 holders and 2 hooks) to 48" (maximum, 6 holders and 5 hooks). For use in janitor closets. Pricing based on a 36" width.
F0500	Cart, Janitor's	1	VV	Janitors cart, 38" high X 66" wide X 20" deep with 25 gallon heavy duty collection bag. Accommodations for locking vault and janitorial support items (broom, dust pan, chemicals, mop and mop bucket; not included).
F0505	Bucket, Mop, With Wringer, 26 Quart	1	VV	Mobile mop bucket / wringer combination, approximately 35" H x 17" W x 22" D with four 2" casters. Total capacity is 26 quarts. Unit used for general hard surface floor maintenance.
P2000	Eyewash, Wall Mounted, Hands-Free	1	CC	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.
P2450	Valve, Mixing, Thermostatic	1	CC	Thermostatic mixing valve with washout hose. Used with portable whirlpool equipment. Thermostatic valve is used to maintain temperature between 70 and 110 degree Fahrenheit, with a flow rate of 20 gallons a minute. The washout hose assembly is used to wash out tanks after treatment. Used in physical therapy department to provide comfortable water temperature for patient treatments.

P4700	Sink, Mop, Molded Stone	1	CC	Mop service sink approximately 10"H x 36"W x 24"D. Also called a mop service basin and a mop receptor. Unit is made of molded stone and is a one piece item. It shall include a service faucet hose, hose bracket and mop hanger. Used in utility rooms for cleaning mops and floor cleaning equipment.
-------	-------------------------	---	----	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

9 - STAFF AND ADMINISTRATIVE AREA

1 - OFA09 - Office, Pathology and Laboratory Medicine Chief

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
2 - OFA09 - Office, Pathology and Laboratory Section Chief				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

4 - SEC01 - Secretary / Waiting

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0078	Workstation, L-Shaped w/Peninsula, Free Std, 78x72	1	VV	This section will provide a whole work station typical to quickly plan work areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 standard solid panels; 2 panel connectors, 2-way corner; 1 panel-to-panel connector; 2 finished end hardware; 1 cantilevered work surface; 1 peninsula work surface; 2 lockable flipper units; 2 shelf, storage/display; 2 lights; 1 tack board, 48"W; 1 tool rail, 30"W; 1 paper tray; 1 diagonal tray; 1 adjustable keyboard tray; 1 mobile pedestal, box/file.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0305	Chair, Waiting Room, Single	2	VV	Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included.
F0405	Cabinet, Filing, Full Height, 4-5 Drawer	1	VV	Four (4) or five (5) drawer letter size, vertical filing cabinet, 53" high X 15" wide X 29" deep with locking device. Each drawer has label holder, handle and roller cradle.

F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1825	Printer, Computer	1	VV	High resolution computer printer with a variety of type styles and sheet/envelope feeder trays. Database information reflects network ready, medium duty office style laser printers. Other types of printers (bubble jet, dot matrix, line or plotter) as well as light or heavy use capabilities are available.

5 - OFA07 - Workstation, Clerical

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.

F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

6 - OFA07 - Workstation, Administrative Assistant

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
7 - OFA09 - Office, Chief Medical Technologist				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	<p>THIS TYPICAL INCLUDES:</p> <ul style="list-style-type: none"> 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
8 - OFA09 - Office, Chief Clinical Laboratory Scientist				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
E0090	Workstation, L-Shaped, Free Standing, 72x72	1	VV	THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel-to-Panel Connectors 1 Panel Connector, 2-Way Corner 2 Finished End Hardware 2 Lockable Flipper Units 2 Shelves, Storage/Display 3 Lights 3 Tackboards 2 Cantilevered Work Surfaces 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 2 Support Panels
F0205	Chair, Side With Arms	1	VV	Upholstered side chair, 32" high X 21" wide X 23" deep with arms, padded seats and padded backs. Seat height is a minimum of 17". Available with or without sled base.
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
-------	-------------------------------------------------	---	----	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

9 - OFA07 - Workstation, Clinical Laboratory Scientist

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

10 - CRA01 - Conference Room				
JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	3	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	1	VV	A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA compliant unit with a load capacity of up to 130 lbs.
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.
F0220	Chair, Conference	8	VV	Conference chair designed to complement the executive furniture package selected. Foam rubber cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel casters.
F0690	Workstation, Computer, Enclosed, With Lock	1	VV	Computer operator workstation ,approximately 58" high X 36" wide X 25" deep. A fully enclosed workstation for a computer, monitor, printer and supplies. Cabinet has two lockable doors.
F0755	Table, Conference, Wood	1	VV	Executive conference table. Dimensions are approximately 30" high, 48" wide with lengths varying from 74" to 96". These tables add traditional elegance to any conference room.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0385	Projector, Multimedia/Data	1	VV	The projector shall provide computer and video projections. Minimum features included: Brightness of not less than 1500 ANSI (American National Standards Institute) Lumens, and a minimum resolution format of 1024 X 768 pixels (XGA). The projector shall be portable and weigh no more than 10 pounds. It shall include a zoom lens and computer and video input ports.
M0400	Screen, Projection, 144x144, Remote Control	1	CC	Wall or ceiling mounted, roll-up type screen with remote control. Includes multiple controls to operate the screen from two or more locations, wireless remote control, adjustable preset limit switches, and black borders on all sides. Screen is housed in a solid wood or metal case with removable motor module. For a classroom, conference room, or large auditorium.
M0507	Video Teleconferencing System	1	VV	Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing capabilities to dispersed geographic sites.

M0512	Television, HDTV, Large Screen, 60"	1	VV	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1875	Board, Copy, Electronic Facsimile	1	VV	Electronic facsimile copy board for use in conference rooms and classrooms. Available in a variety of sizes. Unit scans writing surface and makes a paper copy of the board's contents. The user can make multiple copies of a single scanning. Single sided version, single copy version, and office size boards are options. May have a PC interface option. Database pricing reflects a mobile two-panel copy-board with a minimum 33" x 66" writing surface. Depth dimension refers to depth at the caster level of the supporting frame.

11 - SL001 - Lounge, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	1	VV	Telecommunication outlet location.
A1012	Telephone, Wall Mounted, 1 Line	1	VV	Telephone, wall mounted, 1 line.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5080	Dispenser, Paper Towel, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.
A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5210	Bracket, Television, Wall Mounted, w/Adjust Arm	1	VV	Wall mounted television bracket with adjustable arm. Consists of movable arm with minimum 120 degree swivel. Designed for holding wall mounted, flat panel television units in patient rooms.
A5220	Bracket, Television, Wall Backing	1	CC	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing.
C02C0	Cabinet, U/C/B, 1 Shelf, 1 Drawer, 1 DO, 36x24x22	1	CC	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above a solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings). Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.
C02D0	Cabinet, U/C/B, 4 Drawer, 36x24x22	1	CC	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

C04P0	Cabinet, Sink, U/C/B, 2 Door, 36x36x22	1	CC	Standing height under counter base sink cabinet with solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.
CB020	Cabinet, W/H, 2 Shelf, 1 DO, Sloping Top, 38x24x13	2	CC	Wall hung cabinet with two adjustable shelves, solid right or left-hinged door (appropriate door hinge configuration to be indicated on equipment elevation drawings), and sloping top. Also referred to as a solid hinged single door case. For general purpose use throughout the facility.
CS010	Sink, SS, Single Compartment, 7.5x12x12 ID	1	CC	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. For general purpose use throughout the facility.
CT020	Countertop, Solid Surface	7	CC	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring optimum physical and chemical resisting properties.
F0225	Chair, Dining Room	4	VV	Dining room chair with glides. Chair has straight legs with cushioned cloth or vinyl seat.
F0795	Table, Dining	1	VV	Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons.
F2015	Basket, Wastepaper, Metal/Plastic, 2 Swinging Doors	1	VV	Metal receptacle for soiled / used towels or waste. Equipped with a removable tapered top with two independently operating self-closing, spring hinged doors. Used in public facilities for the collection and temporary storage of refuse.
F3065	Whiteboard/Bulletin Board, Combination	1	VV	A combination whiteboard and bulletin board, half LCS and half cork. Available with either aluminum or wood frame. It can be used in patient rooms or in any appropriate space in the facility.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
K1552	Brewer, Coffee, Auto, Elect, 3 Burner, Front/Back	1	VV	Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.
K4665	Oven, Microwave, Consumer	1	VV	Counter mounted microwave oven for average duty use. The exterior cabinet can be metal or heavy duty impact resistant plastic. The oven delivers instant energy for rapid heating, defrosting or prime cooking. The oven has touch pad controls, digital timer, power level selector and preprogrammed selectors for commonly cooked items. This oven is commonly found in staff lounges.

M0515	Television, Plasma	1	VV	42" diagonal screen, high definition (HDTV) multimedia flat panel plasma display television. The TV will have a 16:9 wide screen aspect ratio, a minimum of 1024 x 768 display resolution, NTSC tuner, built-in stereo speakers and surround sound.
R7250	Refrigerator/Freezer, 20 Cubic Feet	1	VV	Refrigerator/freezer unit. This type unit includes a food saver system that helps keep food fresher. It also includes roll out wheels and is equipped for an optional automatic icemaker. This unit is of commercial or residential design and use.

12 - LR001 - Locker Room, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1030	Locker, 2 Person, Over/Under	4	VV	Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal belongings. Other width and depths are available.
A1080	Mirror, Posture, Wall Mounted	1	CC	Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.

13 - TLTU1 - Toilet, Staff

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1067	Mirror, Float Glass, ADA Accessible	1	CC	A high quality 1/4" polished float glass mirror with a stainless steel frame. Frame holds mirror in a tilted position for accessibility and compliance with ADA requirements. Mirror has a galvanized steel back secured to frame with concealed screws with integral horizontal hanging brackets. Mirror shall be approximately 18" wide and 36" high. Other sizes are available.
A5075	Dispenser, Soap, Disposable	1	VV	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve.
A5082	Dispenser, Paper Towel, Sensor, Hands Free	1	CC	A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are placed in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.
A5090	Disposal, Sanitary Napkin, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.
A5109	Grab Bar, 1-1/4" Dia, SS, 2 Wall, W/C Accessible	1	CC	A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met.

A5145	Hook, Garment, Double, SS, Surface Mounted	1	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mntd	1	CC	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.
F2010	Basket, Wastepaper, Step-On	1	VV	"Step-on" wastepaper basket with inner liner and foot pedal activated flip top.
P3000	Lavatory, Vitreous China, Straight Back	1	CC	Wall mounted, vitreous china lavatory (approximate bowl size 7"x15"x10") with: straight-front apron, straight or contoured back; faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care areas.
P9050	Toilet, Wall Hung, Siphon Jet	1	CC	Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care facility.

10 - EDUCATION AREA

1 - OFA07 - Workstation, Pathology Resident

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File

F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

2 - OFA07 - Workstation, Education Coordinator

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.

PATHOLOGY AND LABORATORY MEDICINE SERVICE (240) - Contents - VA PG-18-5 (18 Jul 2016 04:59PM ET)

F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.

3 - CRA02 - Classroom / Laboratory

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	4	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A5145	Hook, Garment, Double, SS, Surface Mounted	2	CC	A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the facility to hang various items of apparel.
A5212	Bracket, Television, Wall-Mounted, Tilt/Angle	2	VV	A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA compliant unit with a load capacity of up to 130 lbs.
A6046	Artwork, Decorative, With Frame	2	VV	This JSN is to be used for determining and defining location of decorative artwork.
F0220	Chair, Conference	10	VV	Conference chair designed to complement the executive furniture package selected. Foam rubber cushioned seats and backs covered with either woven fabric or vinyl. Base with 5 (five) swivel casters.
F0295	Chair, Stacking	8	VV	Stacking chair, approximately 34" H X 21" W X 24" D. May be stacked up to 20 high depending upon the model selected. These chairs are intended primarily as overflow capacity for conference rooms.
F0600	Credenza, Executive, Wood	1	VV	Executive credenza with two (2) box drawers, two (2) file drawers, a center closed storage area with adjustable shelf and floor glides.
F0690	Workstation, Computer, Enclosed, With Lock	1	VV	Computer operator workstation, approximately 58" high X 36" wide X 25" deep. A fully enclosed workstation for a computer, monitor, printer and supplies. Cabinet has two lockable doors.
F0755	Table, Conference, Wood	2	VV	Executive conference table. Dimensions are approximately 30" high, 48" wide with lengths varying from 74" to 96". These tables add traditional elegance to any conference room.
F2005	Basket, Wastepaper, Executive, Wood	1	VV	Executive wastepaper basket, approximately 15" high X 13" wide X 13" deep.
F3200	Clock, Battery, 12" Diameter	1	VV	Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries not included).
M0507	Video Teleconferencing System	1	VV	Shall be a video conferencing unit consisting of a camera, microphone, video/audio compression components, a component cart and a 32 inch monitor. It shall provide live audio-visual conferencing capabilities to dispersed geographic sites.
M0512	Television, HDTV, Large Screen, 60"	2	VV	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand.

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROM/DVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
M1875	Board, Copy, Electronic Facsimile	1	VV	Electronic facsimile copy board for use in conference rooms and classrooms. Available in a variety of sizes. Unit scans writing surface and makes a paper copy of the board's contents. The user can make multiple copies of a single scanning. Single sided version, single copy version, and office size boards are options. May have a PC interface option. Database pricing reflects a mobile two-panel copy-board with a minimum 33" x 66" writing surface. Depth dimension refers to depth at the caster level of the supporting frame.

4 - OFA07 - Workstation, Student

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1015	Telephone, Desk, Multiple Line	1	VV	Telephone, desk, multiple line.
E0123	Workstation, Straight, Free Standing, 72" W	1	VV	This JSN will provide a whole work station typical to quickly plan work in areas in clinical or administrative spaces. There will be a price decrease if typical work stations are used with vertical hanging strips instead of panels. THIS TYPICAL INCLUDES: 4 Standard Solid Panels 2 Panel Connectors, 2-Way Corner 1 Panel-to-Panel Connector 2 Finished End Hardware 1 Cantilevered, Work Surface 2 Lockable Flipper Units 2 Shelf, Storage/Displays 2 Lights 1 Tack board 1 Tool Rail 1 Paper Tray 1 Diagonal Tray 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File
F0275	Chair, Swivel, High Back	1	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0420	Cabinet, Filing, Lateral, Half Height	1	VV	Half height two (2) or three (3) drawer lateral filing cabinet, 28" high X 42" wide X 18" deep with recessed handles, locking device and drawer label holders. Drawers are adaptable to either letter or legal size materials.
F2000	Basket, Wastepaper, Round, Metal	1	VV	Round wastepaper basket, approximately 18" high X 16" diameter. This metal unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations.

M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.
-------	-------------------------------------------------	---	----	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

5 - LIBB1 - Library

JSN	NAME	QTY	ACQ/INS	DESCRIPTION
A1010	Telecommunication Outlet	2	VV	Telecommunication outlet location.
A1011	Telephone, Desk, 1 Line	1	VV	Telephone, desk, 1 line.
A6046	Artwork, Decorative, With Frame	1	VV	This JSN is to be used for determining and defining location of decorative artwork.
F0255	Chair, Easy	2	VV	Easy chair approximately 35" high X 28" wide X 32" deep with arms and floor glides. Arms, back and seat are foam padded and upholstered in woven textile fabric or vinyl.
F0275	Chair, Swivel, High Back	2	VV	Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.
F0715	Carrel, Study Table	2	VV	Study carrel with table. Equipped with shelf for one (1) 12" monitor and book shelf, wire access grommets, built-in cable chase for wire management and adjustable floor glides. A convenience outlet is required at point of use to service computer equipment if used. Work surface is 29" high.
F2005	Basket, Wastepaper, Executive, Wood	1	VV	Executive wastepaper basket, approximately 15" high X 13" wide X 13" deep.
F3230	Rack, Hat / Coat, Wall Mounted	1	VV	Wall mounted hat / coat rack. Decoratively styled and equipped with bars, hooks and hat shelf. For use in waiting rooms.
M1801	Computer, Microprocessing, w/Flat Panel Monitor	1	VV	Desk top microprocessing computer. The unit shall consist of a central processing mini tower, flat panel monitor, keyboard, mouse and speakers. The system shall have the following minimum characteristics: a 2.8 GHz Pentium processor; 512 MB memory; 80GB hard drive; 32/48x CD-ROMDVD combo; 1.44MB network interface card; video 32 MB NVIDIA; a 18 inch flat panel monitor. The computer is used throughout the facility to input, manipulate and retrieve information.