

MASTER KEYNOTE LIST

1. EXTERIOR SHEATHING
2. AIR AND VAPOR BARRIER MEMBRANE, WRAP INTO OPENING
3. MASTIC AT LEADING EDGE OF OVERLAP OF MEMBRANE OR ELASTOMERIC FLASHING
4. RIGID INSULATION (WITHOUT VOIDS)
5. CAVITY DRAINAGE MATERIAL (MORTAR NETTING)
6. FACE BRICK
7. MORTAR
8. SELF-ADHERING MEMBRANE FLASHING, 3" MINIMUM OVERLAP AT MEMBRANE JOINTS (VERIFY COMPATIBILITY WITH AIR & VAPOR BARRIERS)
9. TWO PIECE METAL FLASHING WITH END DAMS (HEMMED EDGE AT FACE OF BRICK)
10. LINE OF METAL FLASHING END DAM (DASHED)
11. BRICK LINTEL WITH OPEN JOINT WEEPS 24" O.C.
12. LINTEL SUPPORT ANGLE SHOWN (RELIEVING ANGLE SIMILAR)
13. SEALANT AND BACKER ROD
14. THERMAL BREAK
15. HEEL BEAD OF SEALANT TO PROVIDE AIR TIGHTNESS (SNAP-IN GLAZING BEAD LEAKS AIR) CONTINUOUS AT ALL FOUR SIDES OF GLASS
16. HIGH PERFORMANCE INSULATING GLASS UNIT (TRIPLE GLAZED INSULATED UNIT WILL IMPROVE ENERGY PERFORMANCE)
17. SPRAY POLYURETHANE FOAM TO IMPROVE THERMAL PERFORMANCE
18. MINERAL WOOL
19. SEALANT AND BACKER ROD (VERIFY COMPATIBILITY WITH ELASTOMERIC FLASHING, IF PRESENT)
20. INTERIOR GYPSUM BOARD AND CASING BEAD
21. WINDOW ANCHOR CLIP AND FASTENER (SIZE AND SPACING AS REQUIRED)
22. BLOCKING AS REQUIRED
23. ELASTOMERIC FLASHING (EXTRUDED SILICONE SET IN SILICONE SEALANT OR SELF-ADHERING MEMBRANE FLASHING) (VERIFY COMPATIBILITY WITH AIR AND VAPOR BARRIER), 3" MINIMUM OVERLAP AT MEMBRANE JOINTS
24. BRICK AT JAMB BEYOND
25. SPRAY POLYURETHANE FOAM (PREFERRED), OR RIGID INSULATION
26. STOOL
27. METAL SILL PAN FLASHING WITH END CAPS
28. HOODED WEEP
29. CONTINUOUS BUTYL TAPE
30. ADJUSTABLE STRUCTURAL BRACKET
31. WINDOW RECEPTOR
32. METAL PANEL CLADDING SYSTEM
33. INSULATION RETAINER
34. ALUMINUM WINDOW
35. STUD CAVITY (NO INSULATION)
36. REMOVABLE TRIM HERE TO FACILITATE FUTURE WINDOW REPLACEMENT
37. LINE OF ELASTOMERIC FLASHING BETWEEN ANCHOR CLIPS
38. MASONRY SILL
39. METAL FLASHING